

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE SURVEY OF  
PORTIONS OF THE  
SUBDIVISIONAL LINES  
AND  
THE SUBDIVISION OF CERTAIN SECTIONS  
**TOWNSHIP 32 NORTH, RANGE 9 EAST,**  
OF THE GILA AND SALT RIVER MERIDIAN,  
IN THE STATE OF ARIZONA.

**EXECUTED BY**

**Craig S. Dukart, Cadastral Surveyor**

Under Special Instructions dated May 3, 2012, approved May 3, 2012, which provided for the surveys included under Group No. 1107, and assignment instructions dated May 3 and May 24, 2012.

**Survey commenced May 22, 2012**

**Survey completed August 22, 2012**

**INDEX DIAGRAM**

TOWNSHIP 32 NORTH                      RANGE 9 EAST  
 GILA AND SALT RIVER MERIDIAN, ARIZONA

6	5	4	3 17	18 2 8 16	1
7	8	9	10 15	11 7 14	12
18	17	16	15 14	14 6 13	13
19	20	21	22 12	23 6 12	24
30	29	28	27 11	26 5 10	25
31	32	33	34 9	35 4	36

Subdivision of Section 2 ..... Pages 18-19  
 Subdivision of Section 11 ..... Pages 20-21  
 Subdivision of Section 14 ..... Pages 21-22  
 Subdivision of Section 23 ..... Pages 22-23  
 Subdivision of Section 26 ..... Pages 23-24  
 Subdivision of Section 35 ..... Pages 24-25

## T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the survey of portions of the subdivisional lines and the subdivision of certain sections, Township 32 North, Range 9 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Philip Contzen surveyed the Second Guide Meridian East (west boundary, cancelled August 19, 2009), the Eighth Standard Parallel North (north boundary), and the south and west boundaries of Township 32 North, Range 10 East, in 1905. Robin T. Mathews surveyed Tracts 37 and 38, inside Township 32 North, Range 9 East, and remonumented the corner of Townships 31 and 32 North, Ranges 9 and 10 East in 1990. W. William Foster dependently resurveyed a portion of the Eighth Standard Parallel North and the west boundary of Township 32 North, Range 10 East in 2006. Jones Curtis surveyed the Second Guide Meridian East (west boundary) and resurveyed a portion of the Eighth Standard Parallel North (north boundary) in 2009. Leonard R. Sandoval established an electronic control monument, Township 32 North, Range 9 East, in 2009. The plat-only survey of Township 32 North, Range 9 East, conducted under Group 1059, Arizona, approved on February 9, 2010, was utilized in the production of an Amended Protraction Diagram, approved on March 7, 2011, which superseded that portion of Arizona Protraction Diagram No. 41 for this area. A portion of the north boundary (south boundary), Township 31 North, Range 9 East, was surveyed by Geoffrey A. Graham, in 2012, concurrently under this same group.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions (2009), and the Special Instructions dated May 3, 2012, for Group Number 1107, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700, 5800 and R8 model receivers.

The "standard monument" referred to in these notes is a stainless steel post, 28 ins. long, 2 1/2 ins. diam., with a brass cap. Unless otherwise indicated, a magnet in a white plastic case is deposited at the base of the stainless steel post.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DK8419 AZPG CITY OF PAGE CORS ARP, DJ8981 FST5 FLAGSTAFF 5 CORS ARP, AI8820 FERN FERNO MESA CORS ARP and AI8805 FRED FREDONIA CORS ARP. The NAD 83 (2011) (EPOCH: 2010), geographic position of the following two corners.

## T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona

## CHAINS

The corner of sections 1, 2, 35 and 36 on the south boundary of the township is as follows:

Latitude: 36°06'15.21" N.                      Longitude: 111°23'25.65" W.

The closing corner of the sections 1 and 2 only, on the Eighth Standard Parallel North, is as follows:

Latitude: 36°11'28.69" N.                      Longitude: 111°23'25.65" W.

The mean magnetic declination is 11° E.

---

**Survey of a portion of the Subdivisional Lines,  
T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona**

---

From the cor. of secs. 1, 2, 35 and 36, on the south boundary, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, encircled by a rock collar, with brass cap mkd. T32N R9E S35 S36 S2 S1 T31N 2012.

A steel "T-Post" fence post is set nearby.

North, bet. of secs. 35 and 36.

Over level to rolling terrain.

40.00      Point for the 1/4 sec. cor. of secs. 35 and 36.

Set a standard monument, 25 ins. in the ground, mkd.

T 32 N R 9 E  
          1/4  
          S 35 | S 36

2012

80.00      Point for the cor. of secs. 25, 26, 35 and 36, falls in Hamblin Wash, 130 ft. wide, drains S. 15° W.

At the true point, set a magnet, in a white plastic case, 30 ins. below the ground.

from which

A standard monument, set 27 ins. in the ground for a reference monument, bears S. 55°00' W., 210.0 ft. dist. with brass cap mkd. RM T32N R9E 210.0 FT. TO COR. S35 2012 and an arrow pointing to the cor. A steel "T-Post" fence post, set nearby.

Survey of the Subdivisional Lines,  
T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	<p style="text-align: center;">A standard monument, set 25 ins. in the ground for a reference monument, bears N. 35°00' W., 250.0 ft. dist. with brass cap mkd. RM T32N R9E 250.0 FT. TO COR. S26 2012 and an arrow pointing to the cor. A steel "T-Post" fence post, set nearby.</p> <p>Terrain, level to rolling. Soil, sand and sandstone. Timber, none. Undergrowth, various desert vegetation.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>North, bet. secs. 25 and 26.</p> <p>Over level to rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs 25 and 26.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 32 N R 9 E</p> <p>1/4</p> <p>S 26   S 25</p> <p>2012</p> </div> <p>Set a steel "T-post" fence post near the cor.</p> <p>Cor. is located 17 lks. west of the westerly edge of dirt road, 8 ft. wide, bears S. 1° E. and N. 1° W..</p>
80.00	<p>Point for the cor. of secs. 23, 24, 25 and 26, falls in Hamblin Wash flood plain.</p> <p>At the true point, set a magnet, in a white plastic case, 30 ins. below the ground.</p> <p>from which</p> <p style="text-align: center;">A standard monument, set 26 ins. in the ground for a reference monument, bears S. 40°00' W., 150.0 ft. dist. with brass cap mkd. RM T32N R9E 150.0 FT. TO COR. S26 2012 and an arrow pointing to the cor. A steel "T-Post" fence post, set nearby.</p> <p style="text-align: center;">A standard monument, set 24 ins. in the ground for a reference monument, bears N. 50°00' W., 200.0 ft. dist. with brass cap mkd. RM T32N R9E 200.0 FT. TO COR. S23 2012 and an arrow pointing to the cor. A steel "T-Post" fence post, set nearby.</p>

Survey of the Subdivisional Lines,  
T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Terrain, level to rolling. Soil, sand and sandstone. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>North, bet. secs. 23 and 24.</p> <p>Over level to rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24, falls in the interwoven Hamblin Wash flood plain.</p> <p>Set a standard monument, 26 ins. in the ground, underpinned with a steel "T-Post" fence post, mkd.</p> <p style="text-align: center;">T 32 N R 9 E 1/4 S 23   S 24</p> <p style="text-align: center;">2012</p> <p>Set a steel "T-post" fence post near the cor.</p>
80.00	<p>Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p> <p style="text-align: center;">T 32 N R 9 E S 14   S 13 S 23   S 24</p> <p style="text-align: center;">2012</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.</p> <p>Terrain, level to rolling. Soil, sand and gravel. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>North, bet. secs. 13 and 14.</p> <p>Over level to rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p>

Survey of the Subdivisional Lines,  
T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 32 N R 9 E 1/4 S 14   S 13  2012
80.00	Set a steel "T-post" fence post near the cor.  Point for the cor. of secs. 11, 12, 13 and 14.  Set a standard monument, 25 ins. in the ground, mkd.
	T 32 N R 9 E S 11   S 12 S 14   S 13  2012
	Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of corner.  From this cor. point, Angle Point 3, Tract 38, T. 32 N., R. 9 E., bears N. 74°55' E., 34.37 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with the ground, with brass cap mkd. T32N R9E TR38 AP3 1990.  Terrain, level to rolling. Soil, sand and gravel. Timber, none. Undergrowth, various desert vegetation.
	<hr/> North, bet. secs. 11 and 12.  Over level to rolling terrain.
18.10	Indian Route 23, graded road, 30 ft. wide, bears N. 80° E. and S. 80° W.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12.  Set a standard monument, 25 ins. in the ground, mkd.
	T 32 N R 9 E 1/4 S 11   S 12  2012

Survey of the Subdivisional Lines,  
T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>From this cor. point, Angle Point 2, Tract 38, T. 32 N., R. 9 E., bears N. 74°55' E., 34.37 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, in a mound of stone, 3 1/2 ft. base, to brass cap mkd. T32N R9E AP2 TR38 1990.</p>										
47.35	Power line, 2 strand, bears N. 76° E. and S. 76° W.										
80.00	<p>Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 32 N</td><td>R 9 E</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td>S 11</td><td>S 12</td></tr> </table> <p>2012</p> </div> <p>Terrain, level to rolling. Soil, sand and gravel. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>North, bet. secs. 1 and 2.</p> <p>Over level to rolling terrain.</p>	T 32 N	R 9 E	S 2	S 1	S 11	S 12				
T 32 N	R 9 E										
S 2	S 1										
S 11	S 12										
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 32 N</td><td>R 9 E</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S 2</td><td>S 1</td></tr> </table> <p>2012</p> </div>	T 32 N	R 9 E	1/4		S 2	S 1				
T 32 N	R 9 E										
1/4											
S 2	S 1										
80.425	<p>Point for the closing cor. of secs. 1 and 2, on the Eighth Standard Parallel North.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 33 N</td><td>R 9 E</td></tr> <tr><td>S 35</td><td></td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td>C</td><td>C</td></tr> <tr><td>T 32 N</td><td>R 9 E</td></tr> </table> <p>2012</p> </div> <p>Set a steel "T-post" fence post near the cor.</p>	T 33 N	R 9 E	S 35		S 2	S 1	C	C	T 32 N	R 9 E
T 33 N	R 9 E										
S 35											
S 2	S 1										
C	C										
T 32 N	R 9 E										

**Survey of the Subdivisional Lines,  
T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, the stan. cor. of secs. 35 and 36, T. 33 N., R. 9 E., bears S. 89°55' E., 19.97 chs. dist., monumented with a brass tablet, 3 1/4 ins. diam., firmly set, flush with an exposed sandstone, mkd. SC T33N R9E S35 S36 2009. Add the marks 2012 to the brass cap.</p> <p>From this same cor. point, the stan. cor. of the 1/4 sec. cor. of sec. 35, bears N. 89°55' W., 20.605 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. SC T33N R9E 1/4 S35 2009. Add the marks 2012 to the brass cap.</p> <p>From this same cor. point, a rebar, 1/2 in. diam., firmly set by persons unknown, projecting 3 ins. above the ground, bears S. 89°15' W., 18.13 chs. dist.</p> <p>Terrain, level to rolling. Soil, sand and gravel. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>From the the cor. of secs. 2, 3, 34 and 35, on the south boundary, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, encircled by a rock collar, with brass cap mkd. T32N R9E S34 S35 S3 S2 T31N 2012.</p> <p>A steel "T-Post" fence post is set nearby.</p> <p>N. 0°01' W., bet. of secs. 34 and 35.</p> <p>Over rolling and broken terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35, falls in an area of a wash that would be a 6 ft. waterfall, if there were any water.</p> <p>From this true point, the point selected for the witness cor. bears N. 46°00' W., 1.20 chs. dist.</p> <p>At the witness cor. point</p> <p>Set a standard monument, 24 ins. in a drill hole, 3 ins. diam., in sandstone, mkd.</p>

Survey of the Subdivisional Lines,  
T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	WC T 32 N R 9 E  1/4 S 34   S 35  2012
80.00	Point for the cor. of secs. 26, 27, 34 and 35.  Set a standard monument, 25 ins. in the ground, mkd.  <div style="text-align: center;">             T 32 N R 9 E              S 27   S 26              S 34   S 35                2012           </div> Terrain, broken mesa and sandstone hills. Soil, sand and sandstone. Timber, none. Undergrowth, various desert vegetation.
	<hr/> From the cor. of secs. 25, 26, 35 and 36.  West, bet. secs. 26 and 35.  Over rolling to broken terrain.
0.55	Hamblin Wash, 130 ft. wide, 2 ft. deep, drains S. 10° W.
3.85	Power line, 2 strand, bears N. 18° E. and S. 18° W.
16.60	Easterly right-of-way fence, bears N. and S.
19.29	Easterly edge of Highway No. 89, asphalt surfaced, 40 ft. wide, bears N. and S. 5° W.
19.90	Westerly edge of Highway No. 89, bears N. and S. 5° W.
22.60	Westerly right-of-way fence, bears N. and S.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 35.  Set a standard monument, 23 ins. in a drill hole, 3 ins. diam., in sandstone, mkd.

Survey of the Subdivisional Lines,  
T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 32 N R 9 E S 26 1/4 ——— S 35  2012
80.00	<p>The cor. of secs. 26, 27, 34 and 35.</p> <p>Terrain, broken mesa and sandstone hills. Soil, sand and sandstone. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>N. 0°01' W., bet. of secs. 26 and 27.</p> <p>Over rolling and broken terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a standard monument, 26 ins. in the ground, 12 ins. in a drill hole, 3 ins. diam., in sandstone, mkd.</p>
	T 32 N R 9 E 1/4 S 27   S 26  2012
80.00	<p>This cor. falls at the base of a sandstone bank of a wash, 10 ft. wide, drains N. 60° E.</p> <p>Point for the cor. of secs. 22, 23, 26 and 27.</p> <p>Set a standard monument, 24 ins. in the ground, 12 ins. in a drill hole, 3 ins. diam., in sandstone, mkd.</p>
	T 32 N R 9 E S 22   S 23 S 27   S 26  2012
	<p>Terrain, broken mesa and sandstone hills. Soil, sand and sandstone. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>West, bet. secs. 23 and 26.</p>

Survey of the Subdivisional Lines,  
T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling to broken terrain.
3.90	Power line, 2 strand, bears S. 14° E. and N. 14° W.
20.42	Easterly right-of-way fence, bears S. 7° E. and N. 7° W.
23.23	Easterly edge of Highway No. 89, asphalt surfaced, 40 ft. wide, bears S. 7° E. and N. 7° W.
23.83	Westerly edge of Highway No. 89, bears S. 7° E. and N. 7° W.
26.58	Westerly right-of-way fence, bears S. 7° E. and N. 7° W.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 26.  Set a standard monument, 23 ins. in a drill hole, 3 ins. diam., in sandstone, mkd.
	T 32 N R 9 E S 23 1/4 ——— S 26  2012
80.00	The cor. of secs. 22, 23, 26 and 27.  Terrain, broken mesa and sandstone hills. Soil, sand and sandstone. Timber, none. Undergrowth, various desert vegetation.
	N. 0°01' W., bet. of secs. 22 and 23.  Over rolling and broken terrain.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 23.  Set a standard monument, 24 ins. in the ground, mkd.
	T 32 N R 9 E 1/4 S 22   S 23  2012
	Set a steel "T-post" fence post near the cor.
80.00	Point for the cor. of secs. 14, 15, 22 and 23.  Set a standard monument, 25 ins. in sandstone, mkd.

Survey of the Subdivisional Lines,  
T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 32 N</td><td>R 9 E</td></tr> <tr><td>S 15</td><td>S 14</td></tr> <tr><td>S 22</td><td>S 23</td></tr> </table>	T 32 N	R 9 E	S 15	S 14	S 22	S 23		
T 32 N	R 9 E								
S 15	S 14								
S 22	S 23								
	2012								
	Raise a mound of petrified wood, 2 ft. base, 2 ft. high, W. of cor.								
	This cor. is located 50 lks. N. of, and above, the left bank of a canyon, 40 ft. deep. Left bank bears S. 85° E. and S. 75° W.								
	Terrain, rolling and broken. Soil, sand and sandstone. Timber, none. Undergrowth, various desert vegetation.								
	<hr/>								
	From the cor. of secs. 13, 14, 23 and 24.								
	West, bet. secs. 14 and 23.								
	Over rolling to broken terrain.								
12.45	Hamblin Wash, braided, 230 ft. wide, 2 ft. deep, drains S.								
17.90	Abandoned highway, degrading asphalt, 25 ft. wide, bears S. 5° E. and N. 5° W.								
18.05	Power line, 2 strand, bears S. 8° E. and N. 8° W.								
26.73	Easterly right-of-way fence, bears S. 5° E. and N. 5° W.								
29.43	Easterly edge of Highway No. 89, asphalt surfaced, 40 ft. wide, bears S. 5° E. and N. 5° W.								
30.05	Westerly edge of Highway No. 89, bears S. 5° E. and N. 5° W.								
32.77	Westerly right-of-way fence, bears S. 5° E. and N. 5° W.								
40.00	Point for the 1/4 sec. cor. of secs. 14 and 23.								
	Set a standard monument, 22 ins. in a drill hole, 3 ins. diam., in sandstone, mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 32 N</td><td>R 9 E</td></tr> <tr><td>S 14</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 23</td><td></td></tr> </table>	T 32 N	R 9 E	S 14		1/4	—	S 23	
T 32 N	R 9 E								
S 14									
1/4	—								
S 23									
	2012								

Survey of the Subdivisional Lines,  
T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Terrain, broken mesa and sandstone hills. Soil, sand and sandstone. Timber, none. Undergrowth, various desert vegetation.</p> <hr/>
	<p>N. 0°01' W., bet. of secs. 14 and 15.</p> <p>Over rolling and broken terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <div style="text-align: center;"> <p>T 32 N R 9 E</p> <p>1/4</p> <p>S 15   S 14</p> <p>2012</p> </div>
80.00	<p>Point for the cor. of secs. 10, 11, 14 and 15.</p> <p>Set a standard monument, 26 ins. in ground, mkd.</p> <div style="text-align: center;"> <p>T 32 N R 9 E</p> <p>S 10   S 11</p> <p>S 15   S 14</p> <p>2012</p> </div> <p>Set a steel "T-post" fence post near the cor.</p> <p>Terrain, rolling and broken. Soil, sand and sandstone. Timber, none. Undergrowth, various desert vegetation.</p> <hr/>
	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>West, bet. secs. 11 and 14.</p> <p>Over rolling to broken terrain.</p>
10.05	<p>Hamblin Wash, braided, 330 ft. wide, 2 ft. deep, drains S. 5° E.</p>
25.40	<p>Abandoned highway, degrading asphalt, 30 ft. wide, bears N. and S.</p>
29.20	<p>Power line, 2 strand, bears S. 6° E. and N. 6° W.</p>

Survey of the Subdivisional Lines,  
T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
32.89	Easterly right-of-way fence, bears S. 4° E. and N. 4° W.
35.61	Easterly edge of Highway No. 89, asphalt surfaced, 40 ft. wide, bears S. 4° E. and N. 4° W.
36.25	Westerly edge of Highway No. 89, bears S. 4° E. and N. 4° W.
38.98	Westerly right-of-way fence, bears S. 4° E. and N. 4° W.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 14.  Set a standard monument, 24 ins. in ground, mkd.  <div style="text-align: center;">           T 32 N R 9 E                      S 11                  1/4 ———                      S 14             2012         </div>
	Set a steel "T-post" fence post near the cor.
40.62	Wash, 24 ft. wide, drains S. 40° E.
80.00	The cor. of secs. 10, 11, 14 and 15.  Terrain, broken mesa and sandstone hills. Soil, sand and sandstone. Timber, none. Undergrowth, various desert vegetation.
	N. 0°01' W., bet. of secs. 10 and 11.  Over rolling and broken terrain.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11.  Set a standard monument, 25 ins. in the ground, mkd.  <div style="text-align: center;">           T 32 N R 9 E                      1/4                  S 10   S 11             2012         </div>
	Set a steel "T-post" fence post near the cor.
80.00	Point for the cor. of secs. 2, 3, 10 and 11.  Set a standard monument, 25 ins. in sandstone, mkd.

Survey of the Subdivisional Lines,  
T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table border="0"> <tr> <td>T 32 N</td> <td>R 9 E</td> </tr> <tr> <td>S 3</td> <td>S 2</td> </tr> <tr> <td>S 10</td> <td>S 11</td> </tr> </table>	T 32 N	R 9 E	S 3	S 2	S 10	S 11		
T 32 N	R 9 E								
S 3	S 2								
S 10	S 11								
	2012								
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.								
	Set a steel "T-post" fence post near the cor.								
	Terrain, rolling and broken.								
	Soil, sand and sandstone.								
	Timber, none.								
	Undergrowth, various desert vegetation.								
	<hr/>								
	From the cor. of secs. 1, 2, 11 and 12.								
	West, bet. secs. 2 and 11.								
	Over rolling to broken terrain.								
1.60	Power line, 2 strand, bears S. 2° E. and N. 2° W.								
6.20	Hamblin Wash, braided, 260 ft. wide, 2 ft. deep, drains S. 5° W.								
19.35	Underground waterline, bears N. 5° E. and S. 5° W.								
19.95	Abandoned highway, degrading asphalt, 30 ft. wide, bears N. 5° E. and S. 5° W.								
39.87	Easterly edge of Highway No. 89, asphalt surfaced, 40 ft. wide, bears N. 9° E. and S. 9° W.								
40.00	Point for the 1/4 sec. cor. of secs. 2 and 11, falls in the asphalt of Highway No. 89, at the easterly white line.								
	Drive a railroad spike, flush with the asphalt, mkd.								
	<table border="0"> <tr> <td>T 32 N</td> <td>R 9 E</td> </tr> <tr> <td>S 2</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 11</td> <td></td> </tr> </table>	T 32 N	R 9 E	S 2		1/4	—	S 11	
T 32 N	R 9 E								
S 2									
1/4	—								
S 11									
	2012								
	BLM								
	from which								

Survey of the Subdivisional Lines,  
T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A standard monument, set 21 ins. in the ground, with a rock collar, for a reference monument, bears N. 64°58' W., 66.0 ft. dist. with brass cap mkd. RM T32N R9E 66.0 FT. TO 1/4 COR. S2 2012 and an arrow pointing to the cor.</p>
40.51	Westerly edge of Highway No. 89, bears N. 9° E. and S. 9° W.
41.58	Westerly right-of-way fence, bears N. 9° E. and S. 9° W.
80.00	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Terrain, broken mesa and sandstone hills. Soil, sand and sandstone. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>N. 0°01' W., bet. of secs. 2 and 3.</p> <p>Over rolling and broken terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a standard monument, 24 ins. in the ground, mkd.</p> <div style="text-align: center;"> <p>T 32 N R 9 E 1/4 S 3   S 2 2012</p> </div> <p>Set a steel "T-post" fence post near the cor.</p>
80.545	<p>Point for the closing cor. of secs. 2 and 3, on the Eighth Standard Parallel North.</p> <p>Set a standard monument, 19 ins. in the ground, with supporting mound of stone, 4 1/2 ft. base, to cap, mkd.</p> <div style="text-align: center;"> <p>T 33 N R 9 E S 34 ----- S 3   S 2 C C T 32 N R 9 E 2012</p> </div> <p>From this cor. point, the stan. cor. of secs. 34 and 35, T. 33 N., R. 9 E., bears S. 89°55' E., 18.815 chs. dist., monumented with brass tablet, 3 1/4 ins. diam., firmly set, flush with sandstone, mkd. SC T33N R9E S34 S35 2009. Add the marks 2012 to the brass cap.</p>

**Survey of the Subdivisional Lines,  
T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this same cor. point, the stan. cor. of the 1/4 sec. cor. of sec. 34, bears N. 89°55' W., 21.155 chs. dist., monumented with brass tablet, 3 1/4 ins. diam., firmly set, 3 ins. below ground, mkd. SC T33N R9E 1/4 S34 2009, with a mound of earth, 3 ft. base, 1 ft. high, north of the cor. Add the marks 2012 to the brass cap.


Terrain, level to rolling.  
Soil, sand and gravel.  
Timber, none.  
Undergrowth, various desert vegetation.

Point for the 1/4 sec. cor. of sec. 2 only, T. 32 N., R. 9 E., at midpoint on the N. bdy. of sec. 2, on the Eighth Standard Parallel North, falls on the NW face of a sandstone cliff, 35 ft. wide, 11 ft. high, bears N. 55° E. and S. 55° W., which is also the right bank of a wash, 15 ft. wide; not monumented.

From this true point, the point selected for the witness cor. bears S. 23°01' E., 67 lks. dist.

At the witness cor. point

Set a standard monument, 24 ins. in ground, in a mound of stone, 3 1/2 ft. base, to cap mkd.



From the true point, the stan. 1/4 sec. cor. of sec. 35, T. 33 N., R. 9 E., bears S. 89°55' E., 19.39 chs. dist., hereinbefore described.

From the same true point, the stan. cor. of secs. 34 and 35, T. 33 N., R. 9 E., bears N. 89°55' W., 21.185 chs. dist., hereinbefore described.

**Subdivision of Section 2,  
T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona**

From the 1/4 sec. cor. of secs. 2 and 11.

North, on the N. and S. center line of sec. 2.

Subdivision of Section 2,  
T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
2.80	Northerly edge of Highway No. 89, 40 ft. wide, bears N. 12° E. and S. 12° W.
7.70	Northerly right-of-way fence, bears N. 15° E. and S. 15° W.
40.00	Point for the center 1/4 sec. cor. of sec. 2, at intersection with the E. and W. center line.  Set a standard monument, 24 ins. in sandstone, mkd.  T 32 N R 9 E  C 1/4 S 2  2012  Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, N. of cor.  This cor. is located on top of the left bank of a wash, 20 ft. wide, drains east.
80.485	The 1/4 sec. cor. of sec. 2 only. <hr/> From the 1/4 sec. cor. of secs. 1 and 2.  West, on the E. and W. center line of sec. 2.
15.50	Hamblin Wash, braided, 110 ft. wide, 2 ft. deep, drains S. 5° E.
19.45	Underground waterline, bears S. 4° E. and N. 4° W.
20.00	Abandoned highway, degrading asphalt, 24 ft. wide, bears S. 10° E. and N. 5° W.
23.73	Easterly right-of-way fence, bears N. 23° E. and S. 23° W.
25.04	Easterly edge of Highway No. 89, asphalt surfaced, 40 ft. wide, bears N. 23° E. and S. 23° W.
25.73	Westerly edge of Highway No. 89, bears N. 23° E. and S. 23° W.
27.03	Westerly right-of-way fence, bears N. 25° E. and S. 25° W.
40.00	The center 1/4 sec. cor. of sec. 2.
80.00	The 1/4 sec. cor. of secs. 2 and 3. <hr/> Subdivision of Section 11, T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona <hr/>

Subdivision of Section 11,  
T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the 1/4 sec. cor. of secs. 11 and 14.
	North, on the N. and S. center line of sec. 11.
38.55	Fence, bears N. 55° E. and S. 55° W.
40.00	Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E. and W. center line.
	Set a standard monument, 26 ins. in sand, underpinned by a steel "T-post", mkd.
	T 32 N R 9 E
	C 1/4 S 11
	2012
	From this cor. point, an Arizona Highway Department brass tablet, set in the concrete of bridge, bears S. 45°13' E., 94 1/2 lks. dist., mkd. ELEV. 4761.13 + STA 1076+15.25 1961.
	From this same cor. point, an Arizona Highway Department concrete post, 6 x 6 ins., firmly set, projecting 3 ins. above the ground, bears S. 33°12' W., 3.375 chs. dist., with brass tablet mkd. 1075+00 1961.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	This cor. is located on flood plain of a wash.
40.58	Fence, bears S. 34° E. and N. 34° W.
48.42	Southerly edge of Highway No. 89, asphalt surfaced, 40 ft. wide, bears S. 4° E. and N. 4° W.
56.73	Northerly edge of Highway No. 89, bears S. 4° E. and N. 4° W.
72.60	Fence at edge of wash, bears S. 50° E.
73.35	Wash, 50 ft. wide, drains S. 80° E.
73.98	Fence at edge of wash, bears N. 70° E.
79.12	Southerly edge of Highway No. 89, asphalt surfaced, 40 ft. wide, bears N. 8° E. and S. 8° W.
80.00	The 1/4 sec. cor. of secs. 2 and 11.
	<hr/>
	From the 1/4 sec. cor. of secs. 11 and 12.

Subdivision of Section 11,  
T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	West, on the E. and W. center line of sec. 11.
16.70	Hamblin Wash, braided, 150 ft. wide, 2 ft. deep, drains S. 10° W.
22.45	Underground waterline, bears N. and S.
23.05	Abandoned highway, degrading asphalt, 24 ft. wide, bears S. 4° W. and N. 4° W.
37.58	Easterly right-of-way fence, bears N. 55° E. and S. 55° W.
38.71	Easterly edge of Highway No. 89, asphalt surfaced, 40 ft. wide, bears S. 5° E. and N. 5° W.
39.35	Westerly edge of Highway No. 89, bears S. 5° E. and N. 5° W.
39.62	Westerly right-of-way fence, bears S. 34° E. and N. 34° W.
40.00	The center 1/4 sec. cor. of sec. 11.
80.00	The 1/4 sec. cor. of secs. 10 and 11.
<hr/> <p>Subdivision of Section 14, T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 14 and 23.
	North, on the N. and S. center line of sec. 14.
40.00	Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E. and W. center line.
	Set a standard monument, 26 ins. in a drill hole, 3 ins. diam., in sandstone, mkd.
	T 32 N R 9 E
	C 1/4 S 14
	2012
80.00	The 1/4 sec. cor. of secs. 11 and 14.
<hr/>	
	From the 1/4 sec. cor. of secs. 13 and 14.
	West, on the E. and W. center line of sec. 14.
7.75	Hamblin Wash, braided, 215 ft. wide, 2 ft. deep, drains S.

**Subdivision of Section 14,  
T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
21.65	Abandoned highway, degrading asphalt, 24 ft. wide, bears S. 5° E. and N. 5° W.
23.65	Power line, 2 strand, bears S. 6° E. and N. 6° W.
29.79	Easterly right-of-way fence, bears S. 5° E. and N. 5° W.
32.51	Easterly edge of Highway No. 89, asphalt surfaced, 40 ft. wide, bears S. 5° E. and N. 5° W.
33.16	Westerly edge of Highway No. 89, bears S. 5° E. and N. 5° W.
34.96	Westerly right-of-way fence, bears N. 32° E. and S. 32° W.
40.00	The center 1/4 sec. cor. of sec. 14.
80.00	The 1/4 sec. cor. of secs. 14 and 15.
<hr/> <p><b>Subdivision of Section 23, T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
	From the 1/4 sec. cor. of secs. 23 and 26.
	North, on the N. and S. center line of sec. 23.
40.00	Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E. and W. center line.
	Set a standard monument, 26 ins. in sandstone, mkd.
	T 32 N R 9 E
	C 1/4 S 23
	2012
	Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, W. of cor.
80.00	The 1/4 sec. cor. of secs. 14 and 23.
<hr/>	
	From the 1/4 sec. cor. of secs. 23 and 24.
	West, on the E. and W. center line of sec. 23.
2.20	Hamblin Wash, braided, 400 ft. wide, 2 ft. deep, drains S. 20° E.
12.50	Power line, 2 strand, bears S. 10° E. and N. 10° W.

**Subdivision of Section 23,  
T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
20.55	Abandoned highway, degrading asphalt, 24 ft. wide, bears N. 5° E. and S. 5° W.
23.58	Easterly right-of-way fence, bears S. 7° E. and N. 7° W.
26.33	Easterly edge of Highway No. 89, asphalt surfaced, 40 ft. wide, bears S. 7° E. and N. 7° W.
26.98	Westerly edge of Highway No. 89, bears S. 7° E. and N. 7° W.
29.68	Westerly right-of-way fence, bears S. 7° E. and N. 7° W.
40.00	The center 1/4 sec. cor. of sec. 23.
80.00	The 1/4 sec. cor. of secs. 22 and 23.
<hr/> <p><b>Subdivision of Section 26, T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
	From the 1/4 sec. cor. of secs. 26 and 35.
	North, on the N. and S. center line of sec. 26.
40.00	Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E. and W. center line.
	Set a standard monument, 25 ins. in a drill hole, 3 ins. diam., in sandstone, mkd.
	T 32 N R 9 E
	C 1/4 S 26
	2012
80.00	The 1/4 sec. cor. of secs. 23 and 26.
<hr/>	
	From the 1/4 sec. cor. of secs. 25 and 26.
	West, on the E. and W. center line of sec. 26.
15.10	Abandoned highway, degrading asphalt, 24 ft. wide, bears S. 22° E. and N. 22° W.
17.35	Easterly right-of-way fence, bears S. 7° E. and N. 7° W.
20.12	Easterly edge of Highway No. 89, asphalt surfaced, 40 ft. wide, bears S. 7° E. and N. 7° W.
20.75	Westerly edge of Highway No. 89, bears S. 7° E. and N. 7° W.

**Subdivision of Section 26,  
T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
22.64	Westerly right-of-way fence, bears N. 24° E. and S. 24° W.
40.00	The center 1/4 sec. cor. of sec. 26.
80.00	The 1/4 sec. cor. of secs. 26 and 27.
<hr/> <p><b>Subdivision of Section 35, T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
	From the 1/4 sec. cor. of secs. 2 and 35, on the south boundary, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with a brass cap mkd. T32N R9E 1/4 S35 S2 T31N 2012.
	North, on the N. and S. center line of sec. 35.
40.00	Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E. and W. center line.
	Set a standard monument, 21 ins. in a drill hole, 3 ins. diam., in sandstone, in a mound of stone, 3 ft. base, to cap, mkd.
	T 32 N R 9 E C 1/4 S 35 2012
80.00	The 1/4 sec. cor. of secs. 26 and 35.
	From the 1/4 sec. cor. of secs. 35 and 36.
	West, on the E. and W. center line of sec. 35.
4.65	Hamblin Wash, braided, 200 ft. wide, 2 ft. deep, drains S. 5° W.
14.25	Power line, 2 strand, bears N. 10° E. and S. 10° W.
15.20	Abandoned highway, degrading asphalt, 24 ft. wide, bears N. 10° E. and S. 10° W.
19.58	Easterly right-of-way fence, bears N. 1° E. and S. 1° W.
22.31	Easterly edge of Highway No. 89, asphalt surfaced, 40 ft. wide, bears N. 1° E. and S. 1° W.
22.94	Westerly edge of Highway No. 89, bears N. 1° E. and S. 1° W.
25.68	Westerly right-of-way fence, bears N. 1° E. and S. 1° W.

Subdivision of Section 35,  
T. 32 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	The center 1/4 sec. cor. of sec. 35.
80.00	The 1/4 sec. cor. of secs. 34 and 35.
<hr/> GENERAL DESCRIPTION <hr/>	
<p>The intent of this survey is to monument the sections along the Highway 89 corridor, which runs northerly and southerly through the township. The south boundary of the township is located approximately 2 miles northerly of the junction with Highway 160. The terrain varies from level in the Hamblin Wash area, to broken, rugged land west of the wash and steep cliffs and broken, rugged land east of the wash.</p> <p>The elevation varies from 4,600 to 5,000 feet above sea level. The soil is sand with areas of sandstone outcrops and ledges. The vegetation is salt brush, Mormon tea, rabbit brush and native grasses throughout the township, with some areas of scattered juniper trees.</p> <p>The mean magnetic declination of 11° E. was derived from the National Geophysical Data Center's magnetic declination calculator, for the dates of the survey.</p> <hr/>	

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

**FIELD ASSISTANTS**

NAMES	CAPACITY
Robert J. Lyle	Surveying Technician
Mark R. Searles	Surveying Technician
Daniel A. Bryon	Engineering Technician
Byron J. Shorty	Engineering Technician
Kevin Tso	Engineering Technician
Luke R. Hullinger	Survey Aid
Alyssa M. Little	Survey Aid
Rafael J. Tapaha	Survey Aid

