

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
SUBDIVISION OF
CERTAIN SECTIONS
TOWNSHIP 35 NORTH, RANGE 8 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Craig S. Dukart, Cadastral Surveyor

Under Special Instructions dated May 3, 2012, approved May 3, 2012, and Supplemental Special Instructions dated August 7, 2012, approved August 7, 2012, which provided for the surveys included under Group No. 1107, and assignment instructions dated May 3 and May 24, 2012.

Survey commenced August 1, 2012

Survey completed August 29, 2012

INDEX DIAGRAM

TOWNSHIP 35 NORTH RANGE 8 EAST
GILA AND SALT RIVER MERIDIAN, ARIZONA

SUBDIVISION OF CERTAIN SECTIONS

Subdivision of Section 5	Pages	4-5
Subdivision of Section 8	Pages	5-6
Subdivision of Section 9	Pages	6-7
Subdivision of Section 16	Pages	7-9
Subdivision of Section 21	Pages	9-10
Subdivision of Section 27	Pages	11-12
Subdivision of Section 28	Pages	12-13
Subdivision of Section 34	Pages	13-14

T. 35 N., R. 8 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the survey of the subdivision of certain sections, Township 35 North, Range 8 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Craig S. Dukart surveyed the Second Guide Meridian East (east boundary), south, west and north boundaries and the subdivisional lines in 2010.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions (2009), and the Supplemental Special Instructions dated August 7, 2012, for Group Number 1107, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700, 5800 and R8 model receivers.

The "standard monument" referred to in these notes is a stainless steel post, 28 ins. long, 2 1/2 ins. diam., with a brass cap. Unless otherwise indicated, a magnet in a white plastic case is deposited at the base of the stainless steel post.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DK8419 AZPG CITY OF PAGE CORS ARP, DL1882 AZFL NAU FLAGSTAFF CORS ARP, and AI8805 FRED FREDONIA CORS ARP. The NAD 83 (2011) (EPOCH: 2010), geographic position of the following two corners.

The 1/4 section corner of the sections 3 and 34, on the south boundary of the township, is as follows:

Latitude: 36°22'54.08" N. Longitude: 111°31'40.01" W.

The 1/4 section corner of sections 5 and 32 on the north boundary of the township is as follows:

Latitude: 36°28'07.25" N. Longitude: 111°33'49.46" W.

T. 35 N., R. 8 E., Gila and Salt River Meridian, Arizona

CHAINS

The mean magnetic declination is 11° E.

Subdivision of Section 5,
T. 35 N., R. 8 E., Gila and Salt River Meridian, Arizona

From the 1/4 sec. cor. of secs. 5 and 8, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T35N R8E S5 1/4 S8 2010, with a steel "T-post" nearby.

Add the marks 2012 to the brass cap.

N. 0°03' W., on the N. and S. center line of sec. 5.

- 11.35 Westerly right-of-way fence, bears S. 20° E. and N. 20° W.
- 16.05 Westerly edge of Highway No. 89, asphalt surfaced, 40 ft. wide, bears S. 20° E. and N. 20° W.
- 17.65 Easterly edge of Highway No. 89, bears S. 20° E. and N. 20° W.
- 20.45 Easterly right-of-way fence, bears S. 20° E. and N. 20° W.
- 25.75 Utility line, 4 strand, bears S. 23° E. and N. 23° W.
- 33.65 Underground waterline, bears S. 20° E. and N. 20° W.
- 40.00 Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E. and W. center line.

Set a standard monument, 26 ins. in the ground, mkd.

T 35 N R 8 E

C 1/4 S 5

2012

Set a steel "T-post" fence post near the cor.

- 63.45 Tanner Wash, 50 ft. wide, 5 ft. deep, drains N. 5° E.
- 80.00 The 1/4 sec. cor. of secs. 5 and 32, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. T36N R8E S32 1/4 S5 T35N 2010, with a steel "T-post" nearby.

Add the marks 2012 to the brass cap.

**Subdivision of Section 5,
T. 35 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 4 and 5, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. T35N R8E 1/4 S5 S4 2010, with a steel "T-post" nearby.</p> <p>Add the marks 2012 to the brass cap.</p> <p>West, on the E. and W. center line of sec. 5.</p>
33.85	Tanner Wash, 80 ft. wide, 4 ft. deep, drains N. 5° W.
40.00	The center 1/4 sec. cor. of sec. 5.
42.30	Underground waterline, bears S. 21° E. and N. 21° W.
46.00	Utility line, 4 strand, bears S. 23° E. and N. 23° W.
48.90	Easterly right-of-way fence, bears S. 20° E. and N. 20° W.
50.15	Easterly edge of Highway No. 89, asphalt surfaced, 40 ft. wide, bears S. 20° E. and N. 20° W.
50.90	Westerly edge of Highway No. 89, bears S. 20° E. and N. 20° W.
53.20	Westerly right-of-way fence, bears S. 20° E. and N. 20° W.
80.00	<p>The 1/4 sec. cor. of secs. 5 and 6, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T35N R8E 1/4 S6 S5 2010, with a mound of stone, 4 ft. base, 2 1/2 ft. high, E. of cor., and with a steel "T-post" nearby.</p> <p>Add the marks 2012 to the brass cap.</p> <hr/> <p style="text-align: center;">Subdivision of Section 8, T. 35 N., R. 8 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 8 and 17, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T35N R8E S8 1/4 S17 2010, with a steel "T-post" nearby.</p> <p>Add the marks 2012 to the brass cap.</p> <p>N. 0°03' W., on the N. and S. center line of sec. 8.</p>
40.00	<p>Point for the center 1/4 sec. cor. of sec. 8, at intersection with the E. and W. center line.</p> <p>Set a standard monument, 24 ins. in the ground, mkd.</p>

Subdivision of Section 8,
T. 35 N., R. 8 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 35 N R 8 E
	C 1/4 S 8
	2012
80.00	The 1/4 sec. cor. of secs. 5 and 8.
	<hr/> <p>From the 1/4 sec. cor. of secs. 8 and 9, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T35N R8E 1/4 S8 S9 2010, with a steel "T-post" nearby.</p> <p>Add the marks 2012 to the brass cap.</p> <p>West, on the E. and W. center line of sec. 8.</p>
8.45	Tanner Wash, 40 ft. wide, 3 ft. deep, drains N. 15° W.
9.00	Underground waterline, bears S. 23° E. and N. 23° W.
10.50	Utility line, 4 strand, bears S. 25° E. and N. 25° W.
12.30	Easterly right-of-way fence, bears S. 20° E. and N. 20° W.
13.55	Easterly edge of Highway No. 89, asphalt surfaced, 40 ft. wide, bears S. 20° E. and N. 20° W.
14.30	Westerly edge of Highway No. 89, bears S. 20° E. and N. 20° W.
16.45	Westerly right-of-way fence, bears S. 20° E. and N. 20° W.
40.00	The center 1/4 sec. cor. of sec. 8.
80.00	The 1/4 sec. cor. of secs. 7 and 8, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. T35N R8E 1/4 S7 S8 2010, with a steel "T-post" nearby.
	Add the marks 2012 to the brass cap.
	<hr/> <p>Subdivision of Section 9, T. 35 N., R. 8 E., Gila and Salt River Meridian, Arizona</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 9 and 16, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T35N R8E S9 1/4 S16 2010, with a steel "T-post" nearby.</p> <p>Add the marks 2012 to the brass cap.</p>

Subdivision of Section 9,
T. 35 N., R. 8 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°02' W., on the N. and S. center line of sec. 9.
40.00	Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E. and W. center line, falls on a sandstone cliff edge, 12 ft. high, bears S. and N. 60° W., and is unstable for monumentation.
	From this true point, the point selected for the witness cor. bears S. 45°05' W., 20 lks. dist.
	At the witness cor. point
	Set a standard monument, 24 ins. in the ground, mkd.
	WC T 35 N R 8 E ↗ C 1/4 S 9 2012
80.00	The 1/4 sec. cor. of secs. 4 and 9, monumented with a brass tablet, 3 1/4 ins. diam., firmly set, in a sandstone slab, mkd. T35N R8E S4 1/4 S9 2010, with a mound of stone, 3 ft. base, 3 1/2 ft. high, N. of cor.
	Add the marks 2012 to the brass cap.
	<hr/> From the 1/4 sec. cor. of secs. 9 and 10, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, in a collar of sandstone, with brass cap mkd. T35N R8E 1/4 S9 S10 2010.
	Add the marks 2012 to the brass cap.
	West, on the E. and W. center line of sec. 9.
40.00	The center 1/4 sec. cor. of sec. 9.
80.00	The 1/4 sec. cor. of secs. 8 and 9.
	<hr/> Subdivision of Section 16, T. 35 N., R. 8 E., Gila and Salt River Meridian, Arizona <hr/>
	From the 1/4 sec. cor. of secs. 16 and 21, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with the ground, with a brass cap mkd. T35N R8E S16 1/4 S21 2010, from which

Subdivision of Section 16,
T. 35 N., R. 8 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A reference monument, bears N. 25°00' E., 95.1 ft. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. RM T35N R8E S16 95.1 FT. TO COR 2010 and an arrow pointing to the cor. Add the marks 2012 to the brass cap.</p> <p>A reference monument, bears S. 65°00' E., 95.0 ft. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. RM T35N R8E S21 95.0 FT. TO COR 2010 and an arrow pointing to the cor. Add the marks 2012 to the brass cap.</p> <p>Add the marks 2012 to the brass cap.</p> <p>The 1/4 sec. cor. falls near the edge of the pavement of Highway 89.</p> <p>N. 0°02' W., on the N. and S. center line of sec. 16.</p>
0.20	Utility line, 4 strand, bears N. 65° E. and S. 65° W.
3.05	Northerly right-of-way fence, bears S. 25° E. and N. 25° W.
8.85	Utility line, 4 strand, bears S. 25° E. and N. 25° W.
28.90	Tanner Wash, 20 ft. wide, 2 ft. deep, drains N. 15° W.
40.00	Point for the center 1/4 sec. cor. of sec. 16, at intersection with the E. and W. center line.
	Set a standard monument, 24 ins. in the ground, mkd.
	T 35 N R 8 E
	C 1/4 S 16
	2012
	Set a steel "T-post" fence post near the cor.
80.00	The 1/4 sec. cor. of secs. 9 and 16.
	<hr/> <p>From the 1/4 sec. cor. of secs. 15 and 16, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T35N R8E 1/4 S16 S15 2010, with a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, W. of the cor.</p> <p>Add the marks 2012 to the brass cap.</p>

**Subdivision of Section 16,
T. 35 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>West, on the E. and W. center line of sec. 16.</p> <p>40.00 The center 1/4 sec. cor. of sec. 16.</p> <p>44.10 Tanner Wash, 20 ft. wide, 1 ft. deep, drains N. 40° W.</p> <p>52.45 Underground waterline, bears S. 25° E. and N. 25° W.</p> <p>53.85 Utility line, 4 strand, bears S. 25° E. and N. 25° W.</p> <p>55.60 Easterly right-of-way fence, bears S. 20° E. and N. 20° W.</p> <p>56.90 Easterly edge of Highway No. 89, asphalt surfaced, 40 ft. wide, bears S. 20° E. and N. 20° W.</p> <p>57.60 Westerly edge of Highway No. 89, bears S. 20° E. and N. 20° W.</p> <p>60.60 Westerly right-of-way fence, bears S. 20° E. and N. 20° W.</p> <p>80.00 The 1/4 sec. cor. of secs. 16 and 17, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T35N R8E 1/4 S17 S16 2010, with a steel "T-post" nearby.</p> <p>Add the marks 2012 to the brass cap.</p> <hr/> <p style="text-align: center;">Subdivision of Section 21, T. 35 N., R. 8 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 21 and 28, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T35N R8E S21 1/4 S28 2010, with a steel "T-post" nearby.</p> <p>Add the marks 2012 to the brass cap.</p> <p>N. 0°02' W., on the N. and S. center line of sec. 21.</p> <p>40.00 Point for the center 1/4 sec. cor. of sec. 21, at intersection with the E. and W. center line.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <p style="text-align: center;">T 35 N R 8 E</p> <p style="text-align: center;">C 1/4 S 21</p> <p style="text-align: center;">2012</p> <p>Set a steel "T-post" fence post near the cor.</p>
--------	--

**Subdivision of Section 21,
T. 35 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
68.00	Underground waterline, bears S. 20° E. and N. 20° W.
69.95	Utility line, 4 strand, bears S. 20° E. and N. 20° W.
72.45	Southerly right-of-way fence, bears S. 25° E. and N. 25° W.
77.90	Southerly edge of Highway No. 89, asphalt surfaced, 40 ft. wide, bears S. 25° E. and N. 25° W.
79.80	Northerly edge of Highway No. 89, bears S. 25° E. and N. 25° W.
80.00	The 1/4 sec. cor. of secs. 16 and 21.
<hr/>	
	From the 1/4 sec. cor. of secs. 21 and 22, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T35N R8E 1/4 S21 S22 2010, with a steel "T-post" nearby.
	Add the marks 2012 to the brass cap.
	West, on the E. and W. center line of sec. 21.
15.05	Tanner Wash, 15 ft. wide, 3 ft. deep, drains N. 45° W.
22.60	Easterly right-of-way fence, bears S. 30° E. and N. 30° W.
23.90	Easterly edge of Highway No. 89, asphalt surfaced, 40 ft. wide, bears S. 30° E. and N. 30° W.
24.65	Westerly edge of Highway No. 89, bears S. 30° E. and N. 30° W.
26.75	Westerly right-of-way fence, bears S. 30° E. and N. 30° W.
27.60	Utility line, 4 strand, bears S. 25° E. and N. 25° W.
28.40	Underground waterline, bears S. 25° E. and N. 25° W.
40.00	The center 1/4 sec. cor. of sec. 21.
80.00	The 1/4 sec. cor. of secs. 20 and 21, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T35N R8E 1/4 S20 S21 2010, with a steel "T-post" nearby.
	Add the marks 2012 to the brass cap.
<hr/>	
<p>Subdivision of Section 27, T. 35 N., R. 8 E., Gila and Salt River Meridian, Arizona</p>	
<hr/>	

Subdivision of Section 27,
T. 35 N., R. 8 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 27 and 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T35N R8E S27 1/4 S34 2010.</p> <p>Add the marks 2012 to the brass cap.</p> <p>From this cor., an Arizona Department of Transportation cor., bears N. 13°18' W., 7.03 chs. dist., monumented with an alum. cap, 3 ins. diam., flush in concrete, with a 4 in. angle iron, projecting 26 ins. above the ground, marked POT 2044+99.00 HWY R. OF W. nearby.</p> <p>N. 0°02' W., on the N. and S. center line of sec. 27.</p>
0.02	Southerly right-of-way fence, bears S. 40° E. and N. 40° W.
1.95	Southerly edge of Highway No. 89, asphalt surfaced, 40 ft. wide, bears S. 40° E. and N. 40° W.
2.95	Northerly edge of Highway No. 89, bears S. 40° E. and N. 40° W.
4.85	Northerly right-of-way fence, bears S. 40° E. and N. 40° W.
40.00	<p>Point for the center 1/4 sec. cor. of sec. 27, at intersection with the E. and W. center line.</p> <p>Set a standard monument, 24 ins. in the ground, mkd.</p> <p style="text-align: center;">T 35 N R 8 E</p> <p style="text-align: center;">C 1/4 S 27</p> <p style="text-align: center;">2012</p>
	Set a steel "T-post" fence post near the cor.
80.00	<p>The 1/4 sec. cor. of secs. 22 and 27, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, in a downhill mound of stone, 3 ft. base, 1 1/2 ft. high, with brass cap mkd. T35N R8E S22 1/4 S27 2010, with a steel "T-post" nearby.</p> <p>Add the marks 2012 to the brass cap.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 26 and 27, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T35N R8E 1/4 S27 S26 2010.</p> <p>Add the marks 2012 to the brass cap.</p>

**Subdivision of Section 27,
T. 35 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	West, on the E. and W. center line of sec. 27.
40.00	The center 1/4 sec. cor. of sec. 27.
63.35	Tanner Wash, 15 ft. wide, 3 ft. deep, drains N. 5° W.
65.95	Easterly right-of-way fence, bears S. 30° E. and N. 30° W.
67.25	Easterly edge of Highway No. 89, asphalt surfaced, 40 ft. wide, bears S. 30° E. and N. 30° W.
68.00	Westerly edge of Highway No. 89, bears S. 30° E. and N. 30° W.
69.35	Westerly right-of-way fence, bears S. 30° E. and N. 30° W.
73.75	Utility line, 4 strand, bears S. 25° E. and N. 25° W.
80.00	The 1/4 sec. cor. of secs. 27 and 28, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. T35N R8E 1/4 S28 S27 2010, with a steel "T-post" nearby.
	Add the marks 2012 to the brass cap.
<hr/> <p>Subdivision of Section 28, T. 35 N., R. 8 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 28 and 33, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, and in a mound of stone, 3 ft. base to brass cap mkd. T35N R8E S28 1/4 S33 2010.
	Add the marks 2012 to the brass cap.
	N. 0°02' W., on the N. and S. center line of sec. 28.
40.00	Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E. and W. center line.
	Set a standard monument, 24 ins. in the ground, mkd.
	T 35 N R 8 E
	C 1/4 S 28
	2012
	Set a steel "T-post" fence post near the cor.
80.00	The 1/4 sec. cor. of secs. 21 and 28.

Subdivision of Section 28,
T. 35 N., R. 8 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>From the 1/4 sec. cor. of secs. 27 and 28.</p> <p>West, on the E. and W. center line of sec. 28.</p> <p>40.00 The center 1/4 sec. cor. of sec. 28.</p> <p>80.00 The 1/4 sec. cor. of secs. 28 and 29, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T35N R8E 1/4 S29 S28 2010, with a steel "T-post" nearby.</p> <p>Add the marks 2012 to the brass cap.</p> <hr/> <p style="text-align: center;">Subdivision of Section 34, T. 35 N., R. 8 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, and in a mound of stone, 2 ft. base, to brass cap mkd. T35N R8E S34 1/4 S3 T34N 2010, with a mound of stone, 3 ft. base, 2 1/2 ft. high, N. of cor.</p> <p>Add the marks 2012 to the brass cap.</p> <p>N. 0°02' W., on the N. and S. center line of sec. 34.</p> <p>40.00 Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E. and W. center line, falls under the porch of a local residence, not monumented.</p> <p>From this true point, the point selected for the witness cor. bears S. 29°45' E., 2.653 chs. dist.</p> <p>At the witness cor. point</p> <p>Set a standard monument, flush with the ground, mkd.</p> <p style="text-align: center;">WC T 35 N R 8 E C 1/4 S 34 2012</p> <p>Set a steel "T-post" fence post near the cor.</p> <p>50.05 Indian Route 6110, graded road, 25 ft. wide, bears N. 55° E. and S. 55° W.</p> <p>74.95 Utility line, 4 strand, bears S. 20° E. and N. 20° W.</p>
--------	---

Subdivision of Section 34,
T. 35 N., R. 8 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The 1/4 sec. cor. of secs. 27 and 34.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 34 and 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T35N R8E 1/4 S34 S35 2010, with a steel "T-post" nearby.</p> <p>Add the marks 2012 to the brass cap.</p> <p>West, on the E. and W. center line of sec. 34.</p>
17.65	Easterly right-of-way fence, bears S. 20° E. and N. 20° W.
18.90	Easterly edge of Highway No. 89, asphalt surfaced, 45 ft. wide, bears S. 20° E. and N. 20° W.
19.60	Westerly edge of Highway No. 89, bears S. 20° E. and N. 20° W.
20.90	Westerly right-of-way fence, bears S. 20° E. and N. 20° W.
40.00	The point for the center 1/4 sec. cor. of sec. 34.
52.90	Indian Route 6110, graded road, 25 ft. wide, bears N. 50° E. and S. 50° W.
80.00	<p>The 1/4 sec. cor. of secs. 33 and 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, and in a mound of stone, 5 ft. base, to brass cap mkd. T35N R8E 1/4 S33 S34 2010.</p> <p>Add the marks 2012 to the brass cap.</p> <hr/>

T. 35 N., R. 8 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The intent of this survey is to monument the center 1/4 section corners of the sections that Highway 89 traverses through. Highway 89 runs northwesterly and southeasterly through the township. The terrain varies from level in the Tanner Wash and Hamblin Wash areas, to broken and rugged land

The elevation varies from 4,600 to 5,000 feet above sea level. The soil is sand with areas of sandstone outcrops and ledges. The vegetation is salt brush, Mormon tea, rabbit brush and native grasses throughout the township, with some areas of scattered juniper trees.

The mean magnetic declination of 11° E. was derived from the National Geophysical Data Center's magnetic declination calculator, for the dates of the survey.

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD ASSISTANTS

NAMES	CAPACITY
Robert J. Lyle	Surveying Technician
Mark R. Searles	Surveying Technician
Daniel Bryon	Engineering Technician
Byron J. Shorty	Engineering Technician
Kevin Tso	Engineering Technician
Alyssa M. Little	Survey Aid
Luke R. Hullinger	Survey Aid
Rafael J. Tapaha	Survey Aid

CERTIFICATE OF SURVEY

I, Craig S. Dukart, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of supplemental special instructions bearing date of the 7th day of August, 2012, I have surveyed the subdivision of certain sections, Township 35 North, Range 8 East, Gila and Salt River Meridian, Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions (2009), and in specific manner described in the foregoing field notes.

5/5/13
(Date)

Craig S. Dukart
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the survey of the subdivision of certain sections, Township 35 North, Range 8 East, Gila and Salt River Meridian, Arizona, executed by Craig S. Dukart, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

5/9/2013
(Date)

Stephen H. Hansen
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 35 N., R. 8 E., of the Gila and Salt River Meridian, in the State of Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~