

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF
A PORTION OF THE FIFTH STANDARD PARALLEL NORTH (SOUTH BOUNDARY)
AND THE WEST BOUNDARY,
THE SURVEY OF THE EAST BOUNDARY
AND THE SUBDIVISIONAL LINES,
AND METES-AND-BOUNDS SURVEY,
TOWNSHIP 21 NORTH, RANGE 12 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Wayne S. Hancock, Cadastral Surveyor

Under Special Instructions dated January 22, 2014, approved January 22, 2014, which provided for the surveys included under Group No. 1129, and assignment instructions dated January 22, 2014.

Survey commenced January 28, 2014

Survey completed April 16, 2014

INDEX DIAGRAM

TOWNSHIP 21 NORTH RANGE 12 EAST
GILA AND SALT RIVER MERIDIAN, ARIZONA

| | | | | | |
|---------------------|---------------|---------------|---------------|---------------|---------------|
| 18 6 67 66 | 5 57 66 | 4 50 57 | 3 41 49 | 2 35 41 | 1 23 35 |
| 17 7 65 65 | 8 56 64 | 9 48 56 | 10 40 48 | 11 34 39 | 12 22 33 |
| 16 18 63 63 | 17 55 62 | 16 47 54 | 15 39 46 | 14 33 38 | 13 21 32 |
| 15 19 62 61 | 20 53 61 | 21 46 53 | 22 37 45 | 23 31 37 | 24 20 31 |
| 13 30 59 29 | 29 52 27 | 28 44 26 | 27 36 25 | 26 30 24 | 25 20 24 |
| 12 31 58 4 | 32 50 5 | 33 42 6 | 34 36 8 | 35 29 10 | 36 19 11 |

Metes-and-Bounds Survey of Burlington Northern
& Santa Fe Railway R-O-WPages 68-80

T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the Fifth Standard Parallel North (South boundary) and the West boundary, the survey of the East boundary and the subdivisional lines, and metes-and-bounds survey, Township 21 North, Range 12 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Johnston B. McLaughlin surveyed the Fifth Standard Parallel North through R. 12 E., in 1883. Thomas B. Matthews independently resurveyed the Fifth Standard Parallel North through R. 12 E., in 1917, and set closing corners on the Fifth Standard Parallel North in the course of his survey of the subdivision of T. 20 N., R. 12 E., in 1917. Benjamin J. Kinsey surveyed the East boundary (West boundary) of T. 21 N., R. 11 E., in 1932. Joe R. Salazar surveyed the South boundary (North boundary) of T. 22 N. R. 12 E., under Group No. 1067, in 2009.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions for the Survey of the Public Lands of the United States, 2009, and the Special Instructions dated January 22, 2014, for Group Number 1129, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation R8 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented when necessary in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DK8419 AZPG CITY OF PAGE CORS, DL1898 AZPS PRESCOTT CORS, DL6010 AZSV STAR VALLEY CORS, AI8820 FERN FERNO MESA CORS, DL1882 AZFL NAU FLAGSTAFF CORS, DH4513 P015 DUECECLUBSAZ2005 CORS, D12245 P011 SPIDERROCKAZ2005 CORS, AH3759 COSA SCOTTSDALE CORS, DN2121 AZPA PEORIA FIREST 195 CORS, and DN6063 AZST SAN TAN PARK CORS. The NAD 83 (CORS 2011) (EPOCH: 2010.00), geographic position of the standard corner of Townships 21 North, Ranges 12 and 12 1/2 East, on the South boundary of the township, is as follows:

Latitude: 35°09'23.746" N. Longitude: 111°03'38.580" W.

The geographic position of the corner of Townships 21 and 22 North, Ranges 11 and 12 East, is as follows:

T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

CHAINS

Latitude: 35°14'37.089" N. Longitude: 111°10'00.218" W.

The mean magnetic declination is 10 3/4° E.

**Dependent Resurvey of a Portion of the
Fifth Standard Parallel North (South Boundary),
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona**

Restoring the independent resurvey executed by
Thomas B. Matthews, in 1917

Beginning at the stan. cor. of Tps. 21 N., Rs. 11 and 12 E., monumented with an iron post, 3 ins. diam., firmly set and leaning north, projecting 20 ins. above ground, in an embedded collar of stone, 5 ft. diam., with brass cap mkd. SC T21N R11E R12E S36 S31 1917, with a scattered mound of stone N. of cor.

Add the marks 2014 to the brass cap.

Rehabilitate monument and raise a mound of stone, 5 ft. base, to top of cap.

Cor. is located in a 4-strand barbed wire fence, bears E. and W.

S. 89°23' E., on the S. bdy. of sec. 31.

Over nearly level grassland, in and along 4-strand barbed wire fence.

40.00 Point for the stan. 1/4 sec. cor. of sec. 31, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.

S C
T 21 N R 12 E
 1/4 S 31

2014

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located in remains of an ancient fence line, bears E. and W., 1 1/2 lks. S. of a 4-strand barbed wire fence, bears E. and W., and 36 lks. S. of a 2-track dirt road, 8 ft. wide, bears E. and W.

Dependent Resurvey of a Portion of the Fifth Standard Parallel North
(S. Bdy.), T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 43.00 | <p>The monument for the closing cor. of secs. 5 and 6, T. 20 N., R. 12 E., an iron post, 3 ft. long, 2 ins. diam., lying loose, not in its original position, in 4-strand barbed wire fence line, bears E. and W., with brass cap mkd. T21N R12E S31 CC S6 S5 T20N R12E 1917. Located for informational purposes only.</p> <p>Cor. not reestablished.</p> |
| 44.05 | <p>BIA Route No. 6910, graded dirt road, 20 ft. wide, bears N. 27° E. and S. 2° W.</p> |
| 55.78 | <p>Left rim of Yellow Jacket Canyon, bears S. 22° E. and N. 22° W.</p> |
| 57.45 | <p>Right rim of Yellow Jacket Canyon, bears S. 15° E. and N. 15° W.</p> |
| 80.00 | <p>The stan. cor. of secs. 31 and 32, monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, in a collar of stone, 3 ft. diam., with brass cap mkd. SC T21N R12E S31 S32 1917.</p> <p>Add the marks 2014 to the brass cap.</p> <p>Raise mound of stone, 4 ft. base, to top of cap.</p> <p>Cor. is located in remains of an ancient fence line, bears E. and W., alongside a 4-strand barbed wire fence, bears E. and W.</p> <hr/> <p>N. 89°04' E., on the S. bdy. of sec. 32.</p> <p>Over grassland and greasewood brush, in and along 4-strand barbed wire fence.</p> <p>Descend gentle E. facing slope.</p> |
| 39.99 | <p>The stan. 1/4 sec. cor. of sec. 32, monumented with an embedded collar of stone, 3 ft. diam., with hole in center, 3 ins. diam., 10 ins. deep, with hollow cut into limestone bedrock. This is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S C T 21 N R 12 E <u>1/4 S 32</u></p> |
| | 2014 |

Dependent Resurvey of a Portion of the Fifth Standard Parallel North
(S. Bdy.), T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

CHAINS

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located in remains of an ancient fence line, bears E. and W., 3 lks. N. of a 4-strand barbed wire fence, bears E. and W., and 12 lks. S. of a 2-track dirt road, 7 ft. wide, bears E. and W.

N. 89°44' E., beginning new measurement.

Over nearly level grassland, in and along 4-strand barbed wire fence.

26.89 Left rim of Canyon Diablo, bears N. 44° E. and S. 44° W.

27.60 The monument for the closing cor. of secs. 4 and 5, T. 20 N., R. 12 E., an iron post, 3 ft. long, 2 ins. diam., lying loose, not in its original position, at end of 4-strand barbed wire fence line, bears W., with brass cap mkd. T21N R12E S32 S5 S6 T20N R12E CC 1917. Located for informational purposes only.

Cor. not reestablished.

39.05 Right rim of Canyon Diablo, bears N. 2° E. and S. 2° W.

40.11 The stan. cor. of secs. 32 and 33, monumented with a chiseled hole cut into limestone ledge, 3 ins. diam., 2 ins. deep, containing rust particles, in center of a mound of stone, 3 ft. base, 2 ft. high, and with a mound of stone, 3 ft. base, 1 1/2 ft. high, N. of cor. This is accepted as the best available evidence of the orig. cor. position.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. in bedrock, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.

| | |
|--------|--------|
| S C | |
| T 21 N | R 12 E |
| S32 | S 33 |

2014

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located on level rocky ground.

S. 89°59' E., on the S. bdy. of sec. 33.

Dependent Resurvey of a Portion of the Fifth Standard Parallel North
(S. Bdy.), T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | Over rocky canyons, in sparse juniper timber. |
| 0.68 | Right rim of Canyon Diablo, bears N. 5° E. and S. 5° W. |
| 12.63 | Left rim of Canyon Diablo, bears N. 53° E. and S. 53° W. |
| 27.72 | Left rim of Canyon Diablo, bears N. 62° E. and S. 62° W. |
| 39.98 | Point for the stan. 1/4 sec. cor. of sec. 33, at proportionate dist.; there is no remaining evidence of the orig. cor. Set a brass tablet, 3 1/2 ins. diam., with stem, 2 3/8 ins. long, 1 in. diam., cemented in drill hole in limestone ledge, with top mkd. |
| | S C T 21 N R 12 E <u>1/4 S 33</u> |
| | 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the brass tablet, and set a steel T-post alongside. |
| | Cor. is located on NW facing slope of Canyon Diablo. |
| 40.69 | Right rim of Canyon Diablo, bears N. 38° E. and S. 53° W. |
| 40.76 | West end of 4-strand barbed wire fence, bears E. Thence, in and along 4-strand barbed wire fence. |
| 79.96 | The stan. cor. of secs. 33 and 34, monumented with an embedded mound of stone, 3 1/2 ft. base, 1 ft. high, with hole in center, 7 ins. diam., 13 ins. deep. This is accepted as the best available evidence of the orig. cor. position. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, 3 1/2 ft. diam., with brass cap mkd. |
| | S C T 21 N R 12 E <u>S 33 S 34</u> |
| | 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, N. of cor. |

Dependent Resurvey of a Portion of the Fifth Standard Parallel North
(S. Bdy.), T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>Cor. is located in remains of an ancient fence line, bears E. and W., 1 lk. N. of 4-strand barbed wire fence, bears E. and W.</p> |
| | <p>S. 89°59' E., on the S. bdy. of sec. 34.</p> |
| | <p>Over nearly level grassland, in and along 4-strand barbed wire fence.</p> |
| 1.21 | <p>Dirt road, 17 ft. wide, bears S. 32° E. and N. 32° W.</p> |
| 39.31 | <p>Point for AP 7, sec. 34, of the metes-and-bounds survey of the right-of-way of the Burlington Northern and Santa Fe Railway, hereinafter described.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> |
| | <p style="text-align: center;"> T 21 N R 12 E S 34 / AP 7 / / S 3 T 20 N 2014 </p> |
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> |
| | <p>Cor. is located in a 4-strand barbed wire fence, bears S. 62° E. and N. 62° W.</p> |
| | <p>Thence, within the Burlington Northern and Santa Fe Railway right-of-way.</p> |
| 39.83 | <p>Dirt road, 13 ft. wide, bears S. 62° E. and N. 62° W.</p> |
| 40.07 | <p>Point for the stan. 1/4 sec. cor. of sec. 34, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> |
| | <p>Set a brass tablet, 3 1/2 ins. diam., with stem, 3 ins. long, 3/4 in. diam., cemented in drill hole in limestone bedrock, 2 ins. below grade, with top mkd.</p> |
| | <p style="text-align: center;"> S C T 21 N R 12 E 1/4 / S 34 / / 2014 </p> |
| | <p>Deposit a magnet, in a white plastic case, at the base of the brass tablet.</p> |

Dependent Resurvey of a Portion of the Fifth Standard Parallel North
(S. Bdy.), T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N. of cor. |
| 42.05 | Center of SW tracks of the Burlington Northern and Santa Fe Railway, bears S. 61°35' E. and N. 61°35' W. |
| 42.50 | Center of NE tracks of the Burlington Northern and Santa Fe Railway, bears S. 61°32' E. and N. 61°32' W. |
| 42.94 | Center of siding tracks of the Burlington Northern and Santa Fe Railway, bears S. 61°31' E. and N. 61°31' W. |
| 45.21 | Dirt road, 12 ft. wide, bears S. 61° E. and N. 61° W. |
| 45.49 | Power line, bears S. 61°30' E. and N. 61°30' W. |
| 45.68 | Point for AP 1, sec. 34, of the metes-and-bounds survey of the right-of-way of the Burlington Northern and Santa Fe Railway, hereinafter described. |
| | Set a brass tablet, 3 1/2 ins. diam., with stem, 3 ins. long, 3/4 in. diam., cemented in drill hole in concrete set around steel angle fence corner, 2 x 2 ins., with top mkd. |
| | <div style="text-align: center;"> <p>T 21 N R 12 E</p> <p>AP 1 S 34</p> <hr style="width: 50%; margin: 0 auto;"/> <p> S 3</p> <p> T 20 N</p> <p> 2014</p> </div> |
| | Deposit a magnet, in a white plastic case, at the base of the brass tablet. |
| | Cor. is located in a 4-strand barbed wire fence corner, fences bear E., S. 62° E. and N. 62° W. |
| | Thence, exit the Burlington Northern and Santa Fe Railway right-of-way, in and along a 4-strand barbed wire fence. |
| 53.52 | Closing cor. of secs. 2 and 3, T. 20 N., R. 12 E., monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above ground, in a scattered mound of stone, with brass cap mkd. CC S3 S2 T20N R12E 191. |
| | Add the marks 2014 to the brass cap. |
| | Raise mound of stone, 3 1/2 ft. base, to top of cap. |
| | Cor. is located in 4-strand barbed wire fence, bears E. and W., and 25 lks. S. of a 2-track dirt road, 9 ft. wide, bears E. and W. |

Dependent Resurvey of a Portion of the Fifth Standard Parallel North
(S. Bdy.), T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 80.14 | <p>The stan. cor. of secs. 34 and 35, monumented with an iron post, 36 ins. long, 3 ins. diam., loosely set, projecting 28 ins. above ground, in a scattered mound of stone, with brass cap mkd. SC T21N R12E S34 S35 1917.</p> <p>Add the marks 2014 to the brass cap.</p> <p>Rehabilitate monument to firmly set, projecting 25 ins. above ground, in a mound of stone, 3 ft. base, to top.</p> <p>Deposit a magnet, in a white plastic case, at the base of the iron post.</p> <p>Cor. is located in a 4-strand barbed wire fence, bears E. and W.</p> <hr/> <p>S. 89°57' E., on the S. bdy. of sec. 35.</p> <p>Over nearly level grassland, in and along 4-strand barbed wire fence.</p> |
| 40.00 | <p>The stan. 1/4 sec. cor. of sec. 35, monumented with an iron post, 1 in. diam., firmly set, projecting 20 ins. above ground, in a scattered mound of stone, with brass cap mkd. SC 1/4 S35 1917.</p> <p>Add the marks T21N, R12E, and 2014 to the brass cap.</p> <p>Raise mound of stone, 3 ft. base, to top of cap.</p> <p>Cor. is located in 4-strand barbed wire fence, bears E. and W., and 18 lks. S. of a 2-track dirt road, 9 ft. wide, bears E. and W.</p> <hr/> <p>S. 89°53' E., beginning new measurement.</p> <p>Over nearly level grassland, in and along 4-strand barbed wire fence.</p> |
| 40.02 | <p>The stan. cor. of secs. 35 and 36, monumented with an embedded mound of stone, 3 ft. base, 1 ft. high, with hollow in center. This is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, 4 ft. diam., with brass cap mkd.</p> |

Dependent Resurvey of a Portion of the Fifth Standard Parallel North
(S. Bdy.), T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

CHAINS

| | |
|-------------|-------------|
| S C | |
| T 21 N | R 12 E |
| <u>S 35</u> | <u>S 36</u> |

2014

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located in remains of ancient fence line, bears E. and W., 1 1/2 lks. S. of 4-strand barbed wire fence, bears E. and W.

S. 89°58' E., on the S. bdy. of sec. 36.

Over nearly level grassland, in and along 4-strand barbed wire fence.

40.03 Point for the stan. 1/4 sec. cor. of sec. 36, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

| | |
|------------|-------------|
| S C | |
| T 21 N | R 12 E |
| <u>1/4</u> | <u>S 36</u> |

2014

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located in remains of an ancient fence line, bears E. and W., 2 lks. S. of a 4-strand barbed wire fence, bears E. and W., and 50 lks. S. of a 2-track dirt road, 10 ft. wide, bears E. and W.

52.92 From this point the original closing cor. of Tps. 20 N., Rs. 12 and 12 1/2 E., bears North 0.03 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, leaning West, projecting 16 ins. above ground, in a mound of stone, 2 ft. base, 10 ins. high, with brass cap mkd. CC S1 S3 T20N R12E R12 1/2E 1917.

Add the marks 2014 to the brass cap.

Rehabilitate monument and raise mound of stone, 2 ft. base, to top of cap.

Dependent Resurvey of a Portion of the Fifth Standard Parallel North
(S. Bdy.), T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>Cor. is located in a 4-strand barbed wire fence, at a fence corner, bears E., S., and W., 16 lks. N. of a 2-track dirt road, 10 ft. wide, bears E. and W., and 25 lks. S. of a 2-track dirt road, 10 ft. wide, bears E. and W.</p> <p>From this same point, the U.S. Coast & Geodetic Survey station "Sunshine" 1936, bears N. 4°50' E., 0.256 chs. dist., monumented with a brass cap, 3 1/2 ins. diam., set in top of concrete pillar, 10 x 10 ins., projecting 11 ins. above ground, with top mkd. SUNSHINE 1936.</p> <p>from which reference monuments</p> <p style="padding-left: 40px;">A brass cap, 3 1/2 ins. diam., set in top of concrete pillar, 10 x 10 ins., projecting 6 ins. above ground, with top mkd. SUNSHINE 1936 NO 1, and with an arrow pointing to the station, bears S. 70°53' E., 0.515 chs. dist.</p> <p style="padding-left: 40px;">A brass cap, 3 1/2 ins. diam., set in top of concrete pillar, 10 x 10 ins., projecting 6 ins. above ground, with top mkd. SUNSHINE 1936 NO 2, and with an arrow pointing to the station, bears S. 72°51' W., 0.633 chs. dist.</p> |
| 80.06 | <p>The stan. cor. of Tps. 21 N., Rs. 12 and 12 1/2 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 14 ins. above ground, in a scattered mound of stone, with brass cap mkd. SC T21N R12E R12 1/2E S36 S31 2007 191.</p> <p>Correct S31 to S34 and add the marks 2014 to the brass cap.</p> <p>Raise a mound of stone, 3 ft. base, to top of cap.</p> <p>Cor. is located in 4-strand barbed wire fence, bears E. and W.</p> |
| | <hr/> <p>Dependent Resurvey of the West Boundary, T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona.</p> <hr/> |
| | <p>Restoring the survey executed by Benjamin J. Kinsey, in 1932</p> <hr/> |
| 0.26 | <p>From the stan. cor. of Tps. 21 N., Rs. 11 and 12 E., hereinbefore described.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over nearly level grassland.</p> <p>2-track dirt road, 9 ft. wide, bears E. and W.</p> |

Dependent Resurvey of the West Boundary,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona


| CHAINS | |
|--------|--|
| 40.00 | <p>The 1/4 sec. cor. of secs. 31 and 36, monumented with an X chiseled in limestone bedrock, at bottom of a hole, 12 ins. diam., 8 ins. deep, in center of an embedded mound of stone, 4 ft. base, 1 ft. high. This is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 N R 11 E R 12 E 1/4 S 36 S 31 2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°02' W., beginning new measurement.</p> |
| 35.12 | Dirt road, 12 ft. wide, bears S. 69° E. and N. 69° W. |
| 39.98 | <p>The cor. of secs. 25, 30, 31, and 36, monumented with an iron post, 2 ins. diam., loosely set, projecting 22 ins. above ground, in an embedded mound of stone, 4 ft. base, 1 ft. high, with brass cap mkd. T21N R11E R12E S25 S30 S36 S31 1932.</p> <p>Add the marks 2014 to the brass cap.</p> <p>Rehabilitate monument to firmly set, projecting 22 ins. above ground, in a mound of stone, 4 ft. base, to top.</p> <p>Deposit a magnet, in a white plastic case, at the base of the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>North, bet. secs. 25 and 30.</p> <p>Over nearly level grassland.</p> |
| 4.96 | Dirt road, 12 ft. wide, bears S. 51° E. and N. 51° W. |
| 40.01 | <p>The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 22 ins. above ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd. 1/4 S25 S30 1932.</p> |

Dependent Resurvey of the West Boundary,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Add the marks T21N R11E R12E 2014 to the brass cap.</p> <p>Rehabilitate mound of stone, 4 ft. base, to top.</p> <p>Set a steel fence post alongside.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°01' E., beginning new measurement.</p> |
| 20.55 | <p>Point for AP 3, sec. 30, of the metes-and-bounds survey of the right-of-way of the Burlington Northern and Santa Fe Railway, hereinafter described.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar, 3 ft. diam., with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T 21 N R 11 E R 12 E AP 3 S 25 S 30</p> <p style="margin-top: 10px;">2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Thence, within the Burlington Northern and Santa Fe Railway right-of-way.</p> |
| 20.57 | 4-strand barbed wire fence, bears S. 65° E. and N. 65° W. |
| 22.22 | Center of SW tracks of the Burlington Northern and Santa Fe Railway, bears S. 64°36' E. and N. 64°36' W. |
| 22.46 | Center of NE tracks of the Burlington Northern and Santa Fe Railway, bears S. 64°36' E. and N. 64°36' W. |
| 23.90 | <p>Point for AP 2, sec. 30, of the metes-and-bounds survey of the right-of-way of the Burlington Northern and Santa Fe Railway, hereinafter described.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> |

Dependent Resurvey of the West Boundary,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

CHAINS



2014

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.


Cor. is located in a 4-strand barbed wire fence, bears S. 65° E. and N. 65° W.

Thence, exit the Burlington Northern and Santa Fe Railway right-of-way.

40.00 The cor. of secs. 19, 24, 25, and 30, monumented with an X chiseled in limestone bedrock, 10 ins. below grade, in center of an embedded mound of stone, 5 ft. base, 1 ft. high. This is accepted as the best available evidence of the orig. cor. position.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, to top, with brass cap mkd.



2014

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

North, bet. secs. 19 and 24.

Over nearly level grassland.

39.98 The 1/4 sec. cor. of secs. 19 and 24, monumented with an X chiseled in limestone bedrock, 8 ins. below grade, in center of an embedded mound of stone, 6 ft. base, 10 ins. high, and with a rebar, 17 ins. long, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with no cap. This is accepted as the best available evidence of the orig. cor. position.

At the corner point

Dependent Resurvey of the West Boundary,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 6 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 N R 11 E R 12 E 1/4 S 24 S 19 2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> |
| 40.00 | <p>N. 0°03' W., beginning new measurement.</p> <p>Point for the cor. of secs. 13, 18, 19, and 24, at proportionate dist.; falls in center of embedded collar of stone, 5 ft. diam.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 N R 11 E R 12 E S 13 S 18 S 24 S 19 2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> |
| 40.00 | <p>N. 0°03' W., bet. secs. 13 and 18.</p> <p>Over nearly level grassland.</p> <p>The 1/4 sec. cor. of secs. 13 and 18, monumented with an X chiseled in limestone bedrock, 12 ins. below grade, in center of an embedded mound of stone, 6 ft. base, 1 ft. high. This is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 6 ft. base, to top, with brass cap mkd.</p> |

Dependent Resurvey of the West Boundary,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p style="text-align: center;">T 21 N R 11 E R 12 E 1/4 S 13 S 18 2014</p> |
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post and set a steel fence post alongside.</p> <hr style="width: 20%; margin: auto;"/> |
| | <p>N. 0°03' W., beginning new measurement.</p> |
| 40.00 | <p>Point for the cor. of secs. 7, 12, 13, and 18, at proportionate dist.; falls in embedded collar of stone, 4 ft. diam.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, 4 ft. diam., with brass cap mkd.</p> |
| | <p style="text-align: center;">T 21 N R 11 E R 12 E S 12 S 7 S 13 S 18 2014</p> |
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> |
| | <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor., and set a steel fence post alongside.</p> <hr style="width: 20%; margin: auto;"/> |
| | <p>N. 0°03' W., bet. secs. 7 and 12.</p> |
| | <p>Descend a gentle N. facing slope, in native grasses and Mormon Tea brush.</p> |
| 1.88 | <p>Babbitt Wash, 36 lks. wide, course N. 84° E.</p> |
| 40.00 | <p>The 1/4 sec. cor. of secs. 7 and 12, monumented with an X chiseled in limestone bedrock, at bottom of a hole, 6 ins. diam., 5 ins. deep, in center of an embedded mound of stone, 5 ft. base, 2 ft. high. This is accepted as the best available evidence of the orig. cor. position.</p> |
| | <p>At the corner point</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> |

Dependent Resurvey of the West Boundary,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p style="text-align: center;">T 21 N R 11 E R 12 E 1/4 S 12 S 7 2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>N. 0°05' E., beginning new measurement.</p> |
| 39.99 | <p>The cor. of secs. 1, 6, 7, and 12, monumented with an iron post, 2 ins. diam., firmly set, projecting 34 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. T21N R11E R12E S1 S6 S12 S7 1932.</p> <p>Add the marks 2014 to the brass cap.</p> <hr/> <p>N. 0°03' E., bet. secs. 1 and 6.</p> <p>Over nearly level grassland.</p> |
| 25.42 | Right rim of Padre Canyon, bears S. 59° E. and N. 59° W. |
| 28.07 | Left rim of Padre Canyon, bears S. 68° E. and N. 68° W. |
| 39.98 | <p>The 1/4 sec. cor. of secs. 1 and 6, monumented with a rebar, 16 ins. long, 1/2 in. diam., firmly set, 4 ins. below grade, with no cap, in a scattered mound of stone, with volcanic stone, 10 x 8 x 5 ins., firmly set alongside, mkd. X. This is accepted as a careful and faithful perpetuation of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, 4 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 11 E R 12 E 1/4 S 1 S 6 2014</p> |

**Dependent Resurvey of the West Boundary,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona**

| CHAINS | |
|--------|--|
| | <p>Deposit the rebar and a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence alongside.</p> <p>Bury the orig. stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°04' E., beginning new measurement.</p> |
| 40.00 | <p>The cor. of Tps. 21 and 22 N., Rs. 11 and 12 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd. T22N R11E R12E S36 S31 S1 S6 T21N 2009 1932, and with a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, S. of cor.</p> <p>Add the marks 2014 to the brass cap.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">Survey of the East Boundary, T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the stan. cor. of Tps. 21 N., Rs. 12 and 12 1/2 E., hereinbefore described.</p> <p>North, bet. secs. 34 and 36.</p> <p>Over nearly level grassland.</p> |
| 0.30 | <p>2-track dirt road, 10 ft. wide, bears E. and W.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 34 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, 1 1/2 ft. diam., with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 21 N</p> <p>R 12 E R 12 1/2 E</p> <p> 1/4</p> <p> </p> <p> S 36 S 34</p> <p> </p> <p> 2014</p> </div> |
| 80.00 | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> <p>Point for the cor. of secs. 25, 27, 34, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> |

Survey of the East Boundary,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | T 21 N R 12 E R 12 1/2 E S 25 S 27 S 36 S 34 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | <hr/> North, bet. secs. 25 and 27. Over nearly level grassland. |
| 37.92 | Dirt road, 9 ft. wide, bears N. 72° E. and S. 72° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 25 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, 1 1/2 ft. diam., with brass cap mkd. |
| | T 21 N R 12 E R 12 1/2 E 1/4 S 25 S 27 2014 |
| 80.00 | Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside. Point for the cor. of secs. 22, 24, 25, and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd. |
| | T 21 N R 12 E R 12 1/2 E S 24 S 22 S 25 S 27 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside. |
| | <hr/> North, bet. secs. 22 and 24. |

Survey of the East Boundary,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | Over nearly level grassland. |
| 14.41 | BIA Route No. 6930, graded dirt road, 22 ft. wide, bears N. 39° E. and S. 39° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 22 and 24. Set a brass tablet, 3 1/2 ins. diam., with stem, 3 ins. long, 3/4 in. diam., cemented in drill hole in limestone bedrock, flush with ground, with top mkd. <div style="text-align: center;"> T 21 N R 12 E R 12 1/2 E 1/4 S 24 S 22 2014 </div> |
| | Deposit a magnet, in a white plastic case, at the base of the brass tablet. |
| | Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, W. of cor. |
| 80.00 | Point for the cor. of secs. 13, 15, 22, and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T 21 N R 12 E R 12 1/2 E S 13 S 15 S 24 S 22 2014 </div> |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | North, bet. secs. 13 and 15. |
| | Over nearly level grassland. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 13 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 7 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, to top, with brass cap mkd. |

Survey of the East Boundary,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | T 21 N R 12 E R 12 1/2 E 1/4 S 13 S 15 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| 40.61 | Dirt road, 14 ft. wide, bears S. 32° E. and N. 32° W. |
| 80.00 | Point for the cor. of secs. 10, 12, 13, and 15. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd. |
| | T 21 N R 12 E R 12 1/2 E S 12 S 10 ----- S 13 S 15 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside. |
| | North, bet. secs. 10 and 12. |
| | Over nearly level grassland. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 10 and 12. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, 3 1/2 ft. diam., with brass cap mkd. |
| | T 21 N R 12 E R 12 1/2 E 1/4 S 12 S 10 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside. |
| 56.89 | Right rim of Canyon Diablo, bears N. 71° E. and S. 71° W. |

Survey of the East Boundary,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | | | |
|---|---|--------|--|--------|------------|-----|-----|---|-----|------|------|
| 60.70 | Left rim of Canyon Diablo, bears N. 85° E. and S. 83° W. | | | | | | | | | | |
| 80.00 | Point for the cor. of secs. 1, 3, 10, and 12. Set a brass tablet, 3 1/2 ins. diam., with stem, 3 ins. long, 1 in. diam., cemented in drill hole in limestone bedrock, flush with ground, with top mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 21 N</td></tr> <tr><td>R 12 E</td><td>R 12 1/2 E</td></tr> <tr><td>S 1</td><td>S 3</td></tr> <tr><td colspan="2"><hr style="width: 50%; margin: 0 auto;"/></td></tr> <tr><td>S 12</td><td>S 10</td></tr> </table> <p>2014</p> </div> Deposit a magnet, in a white plastic case, at the base of the brass tablet. Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, W. of cor. <hr style="width: 50%; margin: 10px auto;"/> North, bet. secs. 1 and 3. Over nearly level ground, in greasewood brush, yucca, and scattered juniper timber. | T 21 N | | R 12 E | R 12 1/2 E | S 1 | S 3 | <hr style="width: 50%; margin: 0 auto;"/> | | S 12 | S 10 |
| T 21 N | | | | | | | | | | | |
| R 12 E | R 12 1/2 E | | | | | | | | | | |
| S 1 | S 3 | | | | | | | | | | |
| <hr style="width: 50%; margin: 0 auto;"/> | | | | | | | | | | | |
| S 12 | S 10 | | | | | | | | | | |
| 40.00 | Point for the 1/4 sec. cor. of secs. 1 and 3. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 21 N</td></tr> <tr><td>R 12 E</td><td>R 12 1/2 E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 1</td><td>S 3</td></tr> </table> <p>2014</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside. Cor. is located on nearly level grassland. | T 21 N | | R 12 E | R 12 1/2 E | 1/4 | | S 1 | S 3 | | |
| T 21 N | | | | | | | | | | | |
| R 12 E | R 12 1/2 E | | | | | | | | | | |
| 1/4 | | | | | | | | | | | |
| S 1 | S 3 | | | | | | | | | | |
| 80.00 | The cor. of Tps. 21 and 22 N., Rs. 12 and 12 1/2 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with the ground, with brass cap mkd. T22N R12E R12 1/2E S36 S34 S1 S3 T21N 2007 2009. Add the marks 2014 to the brass cap. Set a steel fence post alongside. | | | | | | | | | | |

Survey of the East Boundary,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | |
|--------|---|--------|--------|------|------|------|------|--|------|
| | Cor. is located on nearly level grassland. | | | | | | | | |
| | <hr/> <p style="text-align: center;">Survey of the Sectional Correction Line, T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona.</p> <hr/> | | | | | | | | |
| | From the cor. of secs. 25, 27, 34, and 36, on the E. bdy. of the Tp., hereinbefore described. | | | | | | | | |
| | West, bet. secs. 25 and 36. | | | | | | | | |
| | Over nearly level land. | | | | | | | | |
| 40.00 | Point for the 1/4 sec. cor. of secs. 25 and 36. | | | | | | | | |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd. | | | | | | | | |
| | <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 21 N</td> <td>R 12 E</td> </tr> <tr> <td></td> <td>S 25</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 36</td> </tr> </table> | T 21 N | R 12 E | | S 25 | 1/4 | — | | S 36 |
| T 21 N | R 12 E | | | | | | | | |
| | S 25 | | | | | | | | |
| 1/4 | — | | | | | | | | |
| | S 36 | | | | | | | | |
| | 2014 | | | | | | | | |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. | | | | | | | | |
| 40.50 | Dirt road, 9 ft. wide, bears N. and S. | | | | | | | | |
| 80.00 | Point for the cor. of secs. 25, 26, 35, and 36. | | | | | | | | |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. | | | | | | | | |
| | <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 21 N</td> <td>R 12 E</td> </tr> <tr> <td>S 26</td> <td>S 25</td> </tr> <tr> <td>S 35</td> <td>S 36</td> </tr> </table> | T 21 N | R 12 E | S 26 | S 25 | S 35 | S 36 | | |
| T 21 N | R 12 E | | | | | | | | |
| S 26 | S 25 | | | | | | | | |
| S 35 | S 36 | | | | | | | | |
| | 2014 | | | | | | | | |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside. | | | | | | | | |
| | <hr/> | | | | | | | | |
| | West, bet. secs. 26 and 35. | | | | | | | | |
| | Over nearly level grassland. | | | | | | | | |
| 40.00 | Point for the 1/4 sec. cor. of secs. 26 and 35. | | | | | | | | |

Survey of the Sectional Correction Line,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, 1 1/2 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E S 26 1/4 ——— S 35</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, N. of cor.</p> |
| 42.88 | 2-track dirt road, 8 ft. wide, bears S. 61° E. and N. 61° W. |
| 79.83 | 2-track dirt road, 9 ft. wide, bears N. 20° E. and S. 20° W. |
| 80.00 | Point for the cor. of secs. 26, 27, 34, and 35. |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E S 27 S 26 S 34 S 35</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> <hr/> <p>West, bet. secs. 27 and 34.</p> <p>Over nearly level grassland.</p> |
| 20.72 | BIA Route No. 6930, graded dirt road, 12 ft. wide, bears N. 36° E. and S. 36° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 27 and 34. |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> |

Survey of the Sectional Correction Line,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | T 21 N R 12 E S 27 1/4 ——— S 34 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside. |
| | From this cor. point, a windmill bears N. 52°53' W., 15.77 chs. dist. |
| 78.41 | 2-track dirt road, 9 ft. wide, bears N. 15° E. and S. 15° W. |
| 80.00 | Point for the cor. of secs. 27, 28, 33, and 34. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd. |
| | T 21 N R 12 E S 28 S 27 S 33 S 34 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside. |
| | <hr/> West, bet. secs. 28 and 33. |
| | Over nearly level grassland. |
| 29.34 | Right rim of Canyon Diablo, bears N. 24° E. and S. 24° W. |
| 39.35 | Left rim of Canyon Diablo, bears N. 63° E. and S. 63° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 28 and 33. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd. |
| | T 21 N R 12 E S 28 1/4 ——— S 33 2014 |

Survey of the Sectional Correction Line,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | |
|--------|--|--------|--------|------|------|------|------|
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Ascend a gentle SE facing slope, in grassland.</p> | | | | | | |
| 43.31 | 2-track dirt road, 9 ft. wide, bears N 16° E. and S. 16° W. | | | | | | |
| 80.00 | <p>Point for the cor. of secs. 28, 29, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T 21 N</td><td>R 12 E</td></tr> <tr><td>S 29</td><td>S 28</td></tr> <tr><td>S 32</td><td>S 33</td></tr> </table> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> <hr/> <p>West, bet. secs. 29 and 32.</p> <p>Over nearly level grassland.</p> | T 21 N | R 12 E | S 29 | S 28 | S 32 | S 33 |
| T 21 N | R 12 E | | | | | | |
| S 29 | S 28 | | | | | | |
| S 32 | S 33 | | | | | | |
| 0.58 | 2-track dirt road, 8 ft. wide, bears N 4° W. and S. 4° E. | | | | | | |
| 25.15 | <p>Point for AP 1, sec. 29, identical with AP 3, sec. 32, of the metes-and-bounds survey of the right-of-way of the Burlington Northern and Santa Fe Railway, hereinafter described.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T 21 N</td><td>R 12 E</td></tr> <tr><td>AP 1</td><td>S 29</td></tr> <tr><td>AP 3</td><td>S 32</td></tr> </table> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in a 4-strand barbed wire fence, bears S. 65° E. and N. 65° W.</p> <p>Thence, within the Burlington Northern and Santa Fe Railway right-of-way.</p> | T 21 N | R 12 E | AP 1 | S 29 | AP 3 | S 32 |
| T 21 N | R 12 E | | | | | | |
| AP 1 | S 29 | | | | | | |
| AP 3 | S 32 | | | | | | |

Survey of the Sectional Correction Line,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 27.58 | Right rim of Yellow Jacket Canyon, bears N. 38° E. and S. 38° W. |
| 28.19 | Center of NE tracks of the Burlington Northern and Santa Fe Railway, bears S. 64°37' E. and N. 64°37' W. |
| 28.69 | Center of SW tracks of the Burlington Northern and Santa Fe Railway, bears S. 64°37' E. and N. 64°37' W. |
| 29.01 | BIA Route No. 6910, graded dirt road, 20 ft. wide, bears N. 29° E. and S. 29° W. |
| 30.23 | Left rim of Yellow Jacket Canyon, bears N. 42° E. and S. 42° W. |
| 32.18 | 4-strand barbed wire fence, bears S. 65° E. and N. 65° W. |
| 32.22 | Point for AP 4, sec. 29, identical with AP 4, sec. 32, of the metes-and-bounds survey of the right-of-way of the Burlington Northern and Santa Fe Railway, hereinafter described. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, 2 1/2 ft. diam., with brass cap mkd. <div style="text-align: center;"> <p>T 21 N R 12 E</p> <p>S 29 AP 4</p> <p> / \ S 32 AP 4</p> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Thence, exit the Burlington Northern and Santa Fe Railway right-of-way.</p> |
| 40.00 | Point for the 1/4 sec. cor. of secs. 29 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd. <div style="text-align: center;"> <p>T 21 N R 12 E</p> <p> S 29</p> <p> 1/4 ———</p> <p> S 32</p> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> |
| 80.00 | Point for the cor. of secs. 29, 30, 31, and 32. |

**Survey of the Sectional Correction Line,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona**

| CHAINS | |
|--------|--|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <p align="center"> T 21 N R 12 E S 30 S 29 ----- S 31 S 32 </p> <p align="center">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> <hr/> <p>N. 89°52' W., bet. secs. 30 and 31.</p> <p>Over nearly level grassland, in scattered greasewood brush.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <p align="center"> T 21 N R 12 E S 30 1/4 ——— S 31 </p> <p align="center">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> |
| 80.19 | <p>The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p align="center"> Survey of the Subdivisional Lines, T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona. </p> <hr/> <p>From the cor. of secs. 25, 26, 35, and 36, hereinbefore described.</p> <p>S. 0°02' W., bet. secs. 35 and 36.</p> <p>Over nearly level grassland.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E 1/4 S 35 S 36</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> |
| 79.68 | 2-track dirt road, 7 ft. wide, bears E. and W. |
| 79.96 | The stan. cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described. |
| | <hr/> <p>From the cor. of secs. 25, 26, 35, and 36, hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over nearly level grassland, in scattered greasewood brush.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, 1 1/2 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E 1/4 S 26 S 25</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> |
| 55.33 | BIA Route No. 6930, graded dirt road, 22 ft. wide, bears N. 63° E. and S. 63° W. |
| 80.00 | <p>Point for the cor. of secs. 23, 24, 25, and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, 1 1/2 ft. diam., with brass cap mkd.</p> |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | T 21 N R 12 E S 23 S 24 S 26 S 25 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside. |
| | <hr/> From the cor. of secs. 22, 24, 25, and 27, on the E. bdy. of the Tp., hereinbefore described. |
| | West, bet. secs. 24 and 25. |
| | Over nearly level grassland, in scattered greasewood brush. |
| 15.13 | BIA Route No. 6930, graded dirt road, 22 ft. wide, bears N. 52° E. and S. 52° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 24 and 25. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd. |
| | T 21 N R 12 E S 24 1/4 ——— S 25 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| 80.00 | The cor. of secs. 23, 24, 25, and 26. |
| | <hr/> N. 0°01' W., bet. secs. 23 and 24. |
| | Over nearly level grassland, in scattered greasewood brush. |
| 39.02 | Dirt road, 9 ft. wide, bears N. 61° E. and S. 61° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 23 and 24. Set a brass tablet, 3 1/2 ins. diam., with stem, 3 ins. long, 3/4 in. diam., cemented in drill hole in limestone bedrock, flush with ground, with top mkd. |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | T 21 N R 12 E 1/4 S 23 S 24 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the brass tablet. |
| | Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. |
| 80.00 | Point for the cor. of secs. 13, 14, 23, and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, 1 1/2 ft. diam., with brass cap mkd. |
| | T 21 N R 12 E S 14 S 13 S 23 S 24 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | <hr/> From the cor. of secs. 13, 15, 22, and 24, on the E. bdy. of the Tp., hereinbefore described. |
| | West, bet. secs. 13 and 24. |
| | Over nearly level grassland, in scattered prickly pear cactus. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 13 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd. |
| | T 21 N R 12 E S 13 1/4 ——— S 24 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| 80.00 | The cor. of secs. 13, 14, 23, and 24. |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | N. 0°01' W., bet. secs. 13 and 14. Over nearly level grassland. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 13 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, 1 ft. diam., with brass cap mkd. <div style="text-align: center;"> T 21 N R 12 E 1/4 S 14 S 13 2014 </div> |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| 76.86 | Dirt road, 15 ft. wide, bears S. 72° E. and N. 72° W. |
| 80.00 | Point for the cor. of secs. 11, 12, 13, and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, 1 1/2 ft. diam., with brass cap mkd. <div style="text-align: center;"> T 21 N R 12 E S 11 S 12 S 14 S 13 2014 </div> |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | From the cor. of secs. 10, 12, 13, and 15, on the E. bdy. of the Tp., hereinbefore described. |
| | West, bet. secs. 12 and 13. Over nearly level grassland. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 12 and 13. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd. |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | T 21 N R 12 E S 12 1/4 ——— S 13 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| 80.00 | The cor. of secs. 11, 12, 13, and 14. |
| | <hr/> N. 0°01' W., bet. secs. 11 and 12. Over nearly level grassland. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 11 and 12. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, 1 1/2 ft. diam., with brass cap mkd. |
| | T 21 N R 12 E 1/4 S 11 S 12 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside. |
| 41.95 | Dirt road, 8 ft. wide, bears S. 56° E. and N. 56° W. |
| 47.39 | Right rim of Canyon Diablo, bears S. 71° E. and N. 64° W. |
| 51.56 | Left rim of Canyon Diablo, bears S. 62° E. and N. 54° W. |
| 80.00 | Point for the cor. of secs. 1, 2, 11, and 12. |
| | Set a brass tablet, 3 1/2 ins. diam., with stem, 3 ins. long, 3/4 in. diam., cemented in drill hole in limestone bedrock, flush with ground, with top mkd. |
| | T 21 N R 12 E S 2 S 1 ——— S 11 S 12 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the brass tablet. |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.</p> <hr/> <p>From the cor. of secs. 1, 3, 10, and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 1 and 12.</p> <p>Over nearly level land, in greasewood brush, yucca, and scattered juniper timber.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E S 1 1/4 ——— S 12</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> |
| 80.00 | <p>The cor. of secs. 1, 2, 11, and 12.</p> <hr/> <p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Ascend gentle S. sloping grassland, in scattered yucca and juniper timber.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E 1/4 S 2 S 1</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 80.03 | <p>The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. T22N R12E S35 S36 S2 S1 T21N 2009.</p> <p>Add the marks 2014 to the brass cap.</p> <hr/> <p>From the cor. of secs. 26, 27, 34, and 35, hereinbefore described.</p> <p>S. 0°02' W., bet. secs. 34 and 35.</p> <p>Over nearly level grassland.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, 1 1/2 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E 1/4 S 34 S 35</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> |
| 79.68 | 2-track dirt road, 9 ft. wide, bears E. and W. |
| 79.86 | <p>The stan. cor. of secs. 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 26, 27, 34, and 35, hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over nearly level grassland.</p> |
| 11.68 | BIA Route No. 6930, graded dirt road, 12 ft. wide, bears N. 59° E. and S. 59° W. |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | T 21 N R 12 E 1/4 S 27 S 26 2014 |
| 80.00 | Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside. Point for the cor. of secs. 22, 23, 26, and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd. |
| | T 21 N R 12 E S 22 S 23 S 27 S 26 2014 |
| 40.00 | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. <hr/> From the cor. of secs. 23, 24, 25, and 26. West, bet. secs. 23 and 26. Over nearly level grassland, in scattered greasewood brush. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd. |
| | T 21 N R 12 E S 23 1/4 ——— S 26 2014 |
| 80.00 | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. The cor. of secs. 22, 23, 26, and 27. <hr/> N. 0°01' W., bet. secs. 22 and 23. Over nearly level grassland, in scattered greasewood brush. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 22 and 23. |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 80.00 | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E 1/4 S 22 S 23</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> |
| 40.00 | <p>Point for the cor. of secs. 14, 15, 22, and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a collar of stone, 1 1/2 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E S 15 S 14 S 22 S 23</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>West, bet. secs. 14 and 23.</p> <p>Over nearly level grassland.</p> |
| 80.00 | <p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E S 14 1/4 ——— S 23</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> |
| 80.00 | <p>The cor. of secs. 14, 15, 22, and 23.</p> <hr/> |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | N. 0°01' W., bet. secs. 14 and 15. Over nearly level grassland. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, 2 1/2 ft. diam., with brass cap mkd. <div style="text-align: center;"> T 21 N R 12 E 1/4 S 15 S 14 2014 </div> |
| 80.00 | Point for the cor. of secs. 10, 11, 14, and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd. <div style="text-align: center;"> T 21 N R 12 E S 10 S 11 --- --- S 15 S 14 2014 </div> |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | From the cor. of secs. 11, 12, 13, and 14. West, bet. secs. 11 and 14. Over nearly level grassland, in scattered yucca and greasewood brush. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 11 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, 1 1/2 ft. diam., with brass cap mkd. |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | T 21 N R 12 E S 11 1/4 ——— S 14 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside. |
| 80.00 | The cor. of secs. 10, 11, 14, and 15. |
| | <hr/> N. 0°01' W., bet. secs. 10 and 11. Over nearly level grassland, in scattered yucca. |
| 2.90 | 2-track road, 9 ft. wide, bears S. 85° E. and N. 85° W. |
| 28.56 | Right rim of Canyon Diablo, bears E. and W. |
| 31.84 | Left rim of Canyon Diablo, bears N. 86° E. and S. 89° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 10 and 11. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, 3 ft. diam., with brass cap mkd. |
| | T 21 N R 12 E 1/4 S 10 S 11 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| 79.77 | Dirt road, 9 ft. wide, bears N. 87° E. and S. 87° W. |
| 80.00 | Point for the cor. of secs. 2, 3, 10, and 11. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, 1 1/2 ft. diam., with brass cap mkd. |
| | T 21 N R 12 E S 3 S 2 — — S 10 S 11 2014 |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>West, bet. secs. 2 and 11.</p> <p>Over gently S. sloping grassland, in scattered yucca and juniper timber.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, 1 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E S 2 1/4 ——— S 11</p> <p style="text-align: center;">2014</p> |
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> <p>Cor. is located on a gentle N. sloping grassland, in scattered greasewood and tumbleweed brush.</p> |
| 80.00 | <p>The cor. of secs. 2, 3, 10, and 11.</p> <hr/> <p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over nearly level grassland.</p> |
| 0.48 | <p>Dirt road, 9 ft. wide, bears N. 67° E. and S. 61° W.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E 1/4 S 3 S 2</p> <p style="text-align: center;">2014</p> |
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> |


Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 80.05 | <p>The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, in a circular concrete form, 11 ins. diam., to top, with brass cap mkd. T22N R12E S34 S35 S3 S2 T21N 2009.</p> <p>Add the marks 2014 to the brass cap.</p> <hr/> <p>From the cor. of secs. 27, 28, 33, and 34, hereinbefore described.</p> <p>S. 0°08' W., bet. secs. 33 and 34.</p> <p>Over nearly level grassland, in scattered greasewood brush.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, 1 1/2 ft. diam., with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 N R 12 E</p> <p>1/4</p> <p>S 33 S 34</p> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> |
| 46.52 | <p>Point for AP 1, sec. 33, identical with AP 5, sec. 34, of the metes-and-bounds survey of the right-of-way of the Burlington Northern and Santa Fe Railway, hereinafter described.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 N R 12 E</p> <p>S 33 S 34</p> <p>AP 1 AP 5</p> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 2 lks. N. of old stone wall and remains of fence line, bears S. 62° E. and N. 62° W.</p> |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| | |
|--------|---|
| CHAINS | <p>Thence, within the Burlington Northern and Santa Fe Railway right-of-way.</p> |
| 50.85 | <p>Point for AP 15, sec. 33, identical with AP 3, sec. 34, of the metes-and-bounds survey of the right-of-way of the Burlington Northern and Santa Fe Railway, hereinafter described.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 N R 12 E</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Thence, exit the Burlington Northern and Santa Fe Railway right-of-way.</p> |
| 55.13 | <p>Point for AP 13, sec. 33, identical with AP 2, sec. 34, of the metes-and-bounds survey of the right-of-way of the Burlington Northern and Santa Fe Railway, hereinafter described.</p> <p>Set a brass tablet, 3 1/2 ins. diam., with stem, 2 3/8 ins. long, 1 in. diam., cemented in drill hole in limestone bedrock, 3 ins. below grade, with top mkd.</p> <div style="text-align: center;"> <p>T 21 N R 12 E</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the brass tablet.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Cor. is located in a 4-strand barbed wire fence, bears S. 62° E. and N. 62° W.</p> <p>Thence, within the Burlington Northern and Santa Fe Railway right-of-way.</p> |
| 55.20 | <p>Power line, bears S. 62° E. and N. 62° W.</p> |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 56.55 | Center of siding tracks of the Burlington Northern and Santa Fe Railway, bears S. 60°43' E. and N. 60°43' W. |
| 56.79 | Center of NE tracks of the Burlington Northern and Santa Fe Railway, bears S. 60°40' E. and N. 60°40' W. |
| 57.04 | Center of SW tracks of the Burlington Northern and Santa Fe Railway, bears S. 60°39' E. and N. 60°39' W. |
| 58.56 | 4-strand barbed wire fence, bears S. 62° E. and N. 62° W. |
| 58.57 | Point for AP 12, sec. 33, identical with AP 6, sec. 34, of the metes-and-bounds survey of the right-of-way of the Burlington Northern and Santa Fe Railway, hereinafter described. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd. <div style="text-align: center;"> <p>T 21 N R 12 E</p>  <p>2014</p> </div> |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Thence, exit the Burlington Northern and Santa Fe Railway right-of-way. |
| 79.33 | 2-track dirt road, 7 ft. wide, bears S. 75° E. and N. 75° W. |
| 79.83 | The stan. cor. of secs. 33 and 34, on the S. bdy. of the Tp., hereinbefore described. |
| | <hr/> From the cor. of secs. 27, 28, 33, and 34, hereinbefore described. N. 0°02' W., bet. secs. 27 and 28. Over nearly level grassland. |
| 32.71 | Right rim of Canyon Diablo, bears N. 64° E. and S. 64° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 27 and 28. Set a brass tablet, 3 1/2 ins. diam., with stem, 2 3/8 ins. long, 1 in. diam., cemented in drill hole in limestone ledge on left side of Canyon Diablo, with top mkd. |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | T 21 N R 12 E 1/4 S 28 S 27 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the brass tablet. |
| 41.41 | Left rim of Canyon Diablo, bears N. 62° E. and S. 62° W. |
| 48.36 | Left rim of Canyon Diablo, bears S. 33° E. and N. 33° W. |
| 59.01 | Left rim of Canyon Diablo, bears N. 37° E. and S. 37° W. |
| 77.81 | Left rim of Canyon Diablo, bears S. 70° E. and N. 70° W. |
| 80.00 | Point for the cor. of secs. 21, 22, 27, and 28. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, 1 1/2 ft. diam., with brass cap mkd. |
| | T 21 N R 12 E S 21 S 22 S 28 S 27 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside. |
| | From the cor. of secs. 22, 23, 26, and 27. |
| | West, bet. secs. 22 and 27. |
| | Over nearly level grassland, in greasewood brush. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 22 and 27. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, 2 1/2 ft. diam., with brass cap mkd. |
| | T 21 N R 12 E S 22 1/4 ——— S 27 2014 |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| 71.35 | Right rim of Canyon Diablo, bears N. 26° E. and S. 26° W. |
| 80.00 | The cor. of secs. 21, 22, 27, and 28. |
| | <hr/> N. 0°02' W., bet. secs. 21 and 22. Ascend SE sloping grassland, in scattered greasewood brush. |
| 9.57 | Right rim of Canyon Diablo, bears S. 61° E. and N. 61° W. |
| 17.15 | Right rim of Canyon Diablo, bears N. 81° E. and S. 81° W. |
| 24.04 | Left rim of Canyon Diablo, bears S. 87° E. and N. 87° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 21 and 22. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, 3 ft. diam., with brass cap mkd. |
| | T 21 N R 12 E 1/4 S 21 S 22 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside. |
| 80.00 | Point for the cor. of secs. 15, 16, 21, and 22. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, 2 1/2 ft. diam., with brass cap mkd. |
| | T 21 N R 12 E S 16 S 15 S 21 S 22 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside. |
| | <hr/> From the cor. of secs. 14, 15, 22, and 23. West, bet. secs. 15 and 22. |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | Over nearly level grassland. |
| 18.77 | Right rim of Canyon Diablo, bears S. 20° E. and N. 20° W. |
| 24.91 | Left rim of Canyon Diablo, bears S. 22° E. and N. 22° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 15 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, 3 ft. diam., with brass cap mkd. |
| | T 21 N R 12 E S 15 1/4 ——— S 22 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| 80.00 | The cor. of secs. 15, 16, 21, and 22. |
| | _____ |
| | N. 0°02' W., bet. secs. 15 and 16. |
| | Over nearly level grassland. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 15 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, 2 1/2 ft. diam., with brass cap mkd. |
| | T 21 N R 12 E 1/4 S 16 S 15 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| 80.00 | Point for the cor. of secs. 9, 10, 15, and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd. |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | T 21 N R 12 E S 9 S 10 S 16 S 15 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside. |
| | <hr/> From the cor. of secs. 10, 11, 14, and 15. |
| | West, bet. secs. 10 and 15. |
| | Over nearly level grassland, in scattered yucca, Mormon Tea, and greasewood brush. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 10 and 15. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd. |
| | T 21 N R 12 E S 10 1/4 ——— S 15 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| 50.02 | Right rim of Canyon Diablo, bears S. 26° E. and N. 26° W. |
| 69.43 | Left rim of Canyon Diablo, bears S. 18° E. and N. 18° W. |
| 80.00 | The cor. of secs. 9, 10, 15, and 16. |
| | <hr/> N. 0°02' W., bet. secs. 9 and 10. |
| | Descend N. sloping grassland. |
| 1.08 | Right rim of Padre Canyon, bears S. 82° E. and N. 82° W. |
| 6.51 | Left rim of Padre Canyon, bears N. 70° E. and S. 70° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 9 and 10. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, 1 1/2 ft. diam., with brass cap mkd. |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | T 21 N R 12 E 1/4 S 9 S 10 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside. |
| 80.00 | Point for the cor. of secs. 3, 4, 9, and 10. Set a brass tablet, 3 1/2 ins. diam., with stem, 3 ins. long, 3/4 in. diam., cemented in drill hole in limestone bedrock, 1 in. below grade, with top mkd. |
| | T 21 N R 12 E S 4 S 3 ——— S 9 S 10 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the brass tablet. |
| | Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor. |
| | From the cor. of secs. 2, 3, 10, and 11. |
| | West, bet. secs. 3 and 10. |
| | Over nearly level grassland. |
| 0.87 | Dirt road, 9 ft. wide, bears N. 60° E. and S. 60° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 3 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd. |
| | T 21 N R 12 E S 3 1/4 ——— S 10 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| 40.35 | Dirt road, 8 ft. wide, bears N. 58° E. and S. 58° W. |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 80.00 | <p>The cor. of secs. 3, 4, 9, and 10.</p> <hr/> <p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over nearly level grassland.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, 1 1/2 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E 1/4 S 4 S 3 2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> <p>From this cor. point, a windmill bears N. 82°46' W., 8.33 chs. dist.</p> |
| 40.73 | <p>Dirt road, 10 ft. wide, bears N. 76° E. and S. 76° W.</p> |
| 80.07 | <p>The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., monumented with brass tablet, 3 1/2 ins. diam., cemented in drill hole in limestone bedrock, 3 ins. below grade, with top mkd. T22N R12E S33 S34 S4 S3 T21N 2009, with a mound of stone, 3 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>Add the marks 2014 to the brass tablet.</p> <hr/> <p>From the cor. of secs. 28, 29, 32, and 33, hereinbefore described.</p> <p>S. 0°05' W., bet. secs. 32 and 33.</p> <p>Over nearly level grassland, in scattered greasewood brush.</p> |
| 11.94 | <p>Point for AP 1, sec. 32, identical with AP 5, sec. 33, of the metes-and-bounds survey of the right-of-way of the Burlington Northern and Santa Fe Railway, hereinafter described.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | T 21 N R 12 E S 32 S 33 AP 1 AP 5 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Thence, within the Burlington Northern and Santa Fe Railway right-of-way. |
| 11.96 | 4-strand barbed wire fence, bears S. 63° E. and N. 64° W. |
| 13.38 | Center of NE tracks of the Burlington Northern and Santa Fe Railway, bears S. 64°28' E. and N. 64°28' W. |
| 13.61 | Center of SW tracks of the Burlington Northern and Santa Fe Railway, bears S. 64°30' E. and N. 64°30' W. |
| 15.32 | Point for AP 6, sec. 32, identical with AP 6, sec. 33, of the metes-and-bounds survey of the right-of-way of the Burlington Northern and Santa Fe Railway, hereinafter described. Set a brass tablet, 3 1/2 ins. diam., with stem, 3 ins. long, 1 in. diam., cemented in drill hole in limestone bedrock, 3 ins. below grade, with top mkd. |
| | T 21 N R 12 E AP 6 AP 6 S 32 S 33 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the brass tablet. Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor. Cor. is located on S. edge of a dirt road, 24 ft. wide, bears S. 63° E. and N. 64° W. Thence, exit the Burlington Northern and Santa Fe Railway right-of-way. |
| 15.54 | 4-strand barbed wire fence, bears S. 62° E. and N. 62° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 32 and 33. |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E 1/4 S 32 S 33</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> |
| 52.06 | Left rim of Canyon Diablo, bears N. 68° E. and S. 68° W. |
| 67.15 | Right rim of Canyon Diablo, bears N. 49° E. and S. 49° W. |
| 79.81 | The stan. cor. of secs. 32 and 33, on the S. bdy. of the Tp., hereinbefore described. |
| | <hr/> <p>From the cor. of secs. 28, 29, 32, and 33, hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 28 and 29.</p> <p>Over nearly level grassland.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E 1/4 S 29 S 28</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> |
| 47.26 | Right rim of Yellow Jacket Canyon, bears N. 51° E. and S. 51° W. |
| 49.16 | Left rim of Yellow Jacket Canyon, bears N. 48° E. and S. 48° W. |
| 74.50 | BIA Route No. 6910, graded dirt road, 26 ft. wide, bears N. 19° E. and S. 19° W. |
| 80.00 | Point for the cor. of secs. 20, 21, 28, and 29. |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | |
|--------|---|--------|--------|------|------|------|-------|--|------|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> | | | | | | | | |
| | <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 21 N</td> <td>R 12 E</td> </tr> <tr> <td>S 20</td> <td>S 21</td> </tr> <tr> <td>S 29</td> <td>S 28</td> </tr> </table> | T 21 N | R 12 E | S 20 | S 21 | S 29 | S 28 | | |
| T 21 N | R 12 E | | | | | | | | |
| S 20 | S 21 | | | | | | | | |
| S 29 | S 28 | | | | | | | | |
| | 2014 | | | | | | | | |
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> <hr/> | | | | | | | | |
| | <p>From the cor. of secs. 21, 22, 27, and 28.</p> | | | | | | | | |
| | <p>West, bet. secs. 21 and 28.</p> | | | | | | | | |
| | <p>Ascend SE facing slope.</p> | | | | | | | | |
| 1.50 | <p>Left rim of Canyon Diablo, bears S. 15° E. and N. 15° W.</p> | | | | | | | | |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> | | | | | | | | |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, 1 ft. diam., with brass cap mkd.</p> | | | | | | | | |
| | <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 21 N</td> <td>R 12 E</td> </tr> <tr> <td></td> <td>S 21</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 28</td> </tr> </table> | T 21 N | R 12 E | | S 21 | 1/4 | _____ | | S 28 |
| T 21 N | R 12 E | | | | | | | | |
| | S 21 | | | | | | | | |
| 1/4 | _____ | | | | | | | | |
| | S 28 | | | | | | | | |
| | 2014 | | | | | | | | |
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> | | | | | | | | |
| | <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.</p> | | | | | | | | |
| 73.19 | <p>Right rim of Yellow Jacket Canyon, bears N. 48° E. and S. 48° W.</p> | | | | | | | | |
| 75.61 | <p>Left rim of Yellow Jacket Canyon, bears N. 49° E. and S. 49° W.</p> | | | | | | | | |
| 77.76 | <p>BIA Route No. 6910, graded dirt road, 26 ft. wide, bears N. 22° E. and S. 22° W.</p> | | | | | | | | |
| 80.00 | <p>The cor. of secs. 20, 21, 28, and 29.</p> <hr/> | | | | | | | | |
| | <p>N. 0°02' W., bet. secs. 20 and 21.</p> | | | | | | | | |
| | <p>Over nearly level grassland.</p> | | | | | | | | |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E 1/4 S 20 S 21</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> |
| 42.24 | Dirt road, 9 ft. wide, bears S. 82° E. and N. 82° W. |
| 62.91 | BIA Route No. 6910, graded dirt road, 26 ft. wide, bears S. 4° E. and N. 4° W. |
| 75.26 | BIA Route No. 6910, graded dirt road, 26 ft. wide, bears N. 18° E. and S. 5° W. |
| 80.00 | <p>Point for the cor. of secs. 16, 17, 20, and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E S 17 S 16 S 20 S 21</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> <hr/> <p>From the cor. of secs. 15, 16, 21, and 22.</p> <p>West, bet. secs. 16 and 21.</p> <p>Over nearly level grassland.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | T 21 N R 12 E S 16 1/4 ——— S 21 2014 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| 78.46 | BIA Route No. 6910, graded dirt road, 26 ft. wide, bears N. 18° E. and S. 18° W. |
| 80.00 | The cor. of secs. 16, 17, 20, and 21. <hr/> N. 0°02' W., bet. secs. 16 and 17. Over nearly level grassland. |
| 39.06 | Dirt road, 8 ft. wide, bears N. 81° E. and S. 81° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 16 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, 2 1/2 ft. diam., with brass cap mkd. |
| | T 21 N R 12 E 1/4 S 17 S 16 2014 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| 72.70 | BIA Route No. 6910, graded dirt road, 26 ft. wide, bears S. 26° E. and N. 26° W. |
| 80.00 | Point for the cor. of secs. 8, 9, 16, and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd. |
| | T 21 N R 12 E S 8 S 9 S 17 S 16 2014 |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> <hr/> <p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>West, bet. secs. 9 and 16.</p> <p>Over rolling grassland and canyons.</p> |
| 5.06 | Right rim of Padre Canyon, bears N. 52° E. and S. 52° W. |
| 13.05 | Left rim of Padre Canyon, bears S. 12° E. and N. 12° W. |
| 13.54 | Left rim of Padre Canyon, bears N. 18° E. and S. 18° W. |
| 22.04 | Right rim of Padre Canyon, bears S. 22° E. and N. 22° W. |
| 38.10 | Dirt road, 9 ft. wide, bears S. 50° E. and N. 50° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 9 and 16. |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, 1 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E S 9 1/4 ——— S 16</p> <p style="text-align: center;">2014</p> |
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> |
| 80.00 | The cor. of secs. 8, 9, 16, and 17. |
| | <hr/> <p>N. 0°02' W., bet. secs. 8 and 9.</p> <p>Over rolling grassland.</p> |
| 40.00 | Point for the 1/4 sec. cor. of secs. 8 and 9. |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, 4 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E 1/4 S 8 S 9</p> <p style="text-align: center;">2014</p> |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | |
|--------|---|--------|--------|-----|-----|-----|-----|--|-----|
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on a S. facing grassy slope.</p> | | | | | | | | |
| 67.42 | Right rim of Padre Canyon, bears S. 28° E. and N. 28° W. | | | | | | | | |
| 80.00 | <p>Point for the cor. of secs. 4, 5, 8, and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 21 N</td><td>R 12 E</td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td>S 8</td><td>S 9</td></tr> </table> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on an E. facing slope.</p> <hr/> <p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>West, bet. secs. 4 and 9.</p> <p>Over rolling grassland.</p> | T 21 N | R 12 E | S 5 | S 4 | S 8 | S 9 | | |
| T 21 N | R 12 E | | | | | | | | |
| S 5 | S 4 | | | | | | | | |
| S 8 | S 9 | | | | | | | | |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 21 N</td><td>R 12 E</td></tr> <tr><td></td><td>S 4</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S 9</td></tr> </table> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> | T 21 N | R 12 E | | S 4 | 1/4 | — | | S 9 |
| T 21 N | R 12 E | | | | | | | | |
| | S 4 | | | | | | | | |
| 1/4 | — | | | | | | | | |
| | S 9 | | | | | | | | |
| 69.69 | Left rim of Padre Canyon, bears S. 14° E. and N. 14° W. | | | | | | | | |
| 80.00 | <p>The cor. of secs. 4, 5, 8, and 9.</p> <hr/> <p>N. 0°03' W., bet. secs. 4 and 5.</p> | | | | | | | | |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | Over rolling grassland and canyons. |
| 13.31 | Left rim of Padre Canyon, bears S. 70° E. and N. 70° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 4 and 5. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, 1 1/2 ft. diam., with brass cap mkd. <div style="text-align: center;">T 21 N R 12 E 1/4 S 5 S 4 2014</div> |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside. |
| | Cor. is located on a W. facing grassy slope, in scattered yucca and Mormon Tea. |
| 40.90 | Dirt road, 9 ft. wide, bears N. 40° E. and S. 40° W. |
| 78.98 | Dirt road, 15 ft. wide, bears N. 89° E. and S. 89° W. |
| 80.10 | The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., monumented with brass tablet, 3 1/2 ins. diam., cemented in drill hole in limestone bedrock, flush with ground, with top mkd. T22N R12E S32 S33 S5 S4 T21N 2009, with a mound of stone, 2 1/2 ft. base, 2 ft. high, N. of cor. Add the marks 2014 to the brass tablet. |
| | <hr/> From the cor. of secs. 29, 30, 31, and 32, hereinbefore described. S. 0°08' W., bet. secs. 31 and 32. Over nearly level grassland, in scattered greasewood brush. |
| 38.28 | Dirt road, 10 ft. wide, bears S. 55° E. and N. 63° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 31 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a collar of stone, 1 1/2 ft. diam., with brass cap mkd. |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | T 21 N R 12 E 1/4 S 31 S 32 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside. Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor. |
| 52.72 | BIA Route No. 6910, graded dirt road, 20 ft. wide, bears N. 77° E. and S. 77° W. |
| 59.24 | Left rim of Yellow Jacket Canyon, bears S. 66° E. and N. 66° W. |
| 61.12 | Right rim of Yellow Jacket Canyon, bears S. 44° E. and N. 44° W. |
| 80.31 | 2-track dirt road, 8 ft. wide, bears E. and W. |
| 80.66 | The stan. cor. of secs. 31 and 32, on the S. bdy. of the Tp., hereinbefore described. |
| | <hr/> From the cor. of secs. 29, 30, 31, and 32, hereinbefore described. N. 0°03' W., bet. secs. 29 and 30. Over nearly level grassland. |
| 22.69 | Point for AP 3, sec. 29, identical with AP 4, sec. 30, of the metes-and-bounds survey of the right-of-way of the Burlington Northern and Santa Fe Railway, hereinafter described. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, 2 1/2 ft. diam., with brass cap mkd. |
| | T 21 N R 12 E AP 4 AP 3 S 30 S 29 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Thence, within the Burlington Northern and Santa Fe Railway right-of-way. |
| 22.71 | 4-strand barbed wire fence, bears S. 65° E. and N. 65° W. |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 24.61 | Center of SW tracks of the Burlington Northern and Santa Fe Railway, bears S. 64°37' E. and N. 64°37' W. |
| | Center of NE tracks of the Burlington Northern and Santa Fe Railway, bears S. 64°37' E. and N. 64°37' W. |
| 26.04 | Point for AP 2, sec. 29, identical with AP 1, sec. 30, of the metes-and-bounds survey of the right-of-way of the Burlington Northern and Santa Fe Railway, hereinafter described. |
| | Set a brass tablet, 3 1/2 ins. diam., with stem, 3 ins. long, 3/4 in. diam., cemented in drill hole in limestone bedrock, 2 ins. below grade, with top mkd. |
| | <p>T 21 N R 12 E</p> <p>AP 1 AP 2</p> <p>2014</p> |
| | Deposit a magnet, in a white plastic case, at the base of the brass tablet. |
| | Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N. of cor. |
| | Cor. is located in a 4-strand barbed wire fence, bears S. 65° E. and N. 65° W. |
| | Thence, exit the Burlington Northern and Santa Fe Railway right-of-way. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 29 and 30. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, 2 1/2 ft. diam., with brass cap mkd. |
| | <p>T 21 N R 12 E</p> <p> 1/4</p> <p> S 30 S 29</p> <p>2014</p> |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside. |
| 80.00 | Point for the cor. of secs. 19, 20, 29, and 30. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 2 ft. base, to top, with brass cap mkd. |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | T 21 N R 12 E S 19 S 20 S 30 S 29 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside. |
| | <hr/> From the cor. of secs. 20, 21, 28, and 29. West, bet. secs. 20 and 29. Over nearly level grassland. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 20 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, 1 1/2 ft. diam., with brass cap mkd. |
| | T 21 N R 12 E S 20 1/4 ——— S 29 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor. |
| 80.00 | The cor. of secs. 19, 20, 29, and 30. |
| | <hr/> N. 89°52' W., bet. secs. 19 and 30. Over nearly level grassland. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 19 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd. |
| | T 21 N R 12 E S 19 1/4 ——— S 30 2014 |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> |
| 80.10 | <p>The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over nearly level grassland, in scattered greasewood brush.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, 3 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E 1/4 S 19 S 20</p> <p style="text-align: center;">2014</p> |
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.</p> |
| 80.00 | <p>Point for the cor. of secs. 17, 18, 19, and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E S 18 S 17 S 19 S 20</p> <p style="text-align: center;">2014</p> |
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> <hr/> <p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>West, bet. secs. 17 and 20.</p> <p>Over nearly level grassland, in scattered greasewood brush.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E S 17 1/4 ——— S 20</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> |
| 80.00 | <p>The cor. of secs. 17, 18, 19, and 20.</p> <hr/> <p>N. 89°52' W., bet. secs. 18 and 19.</p> <p>Over nearly level grassland, in scattered greasewood brush.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> |
| 80.06 | <p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 17, 18, 19, and 20.</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over nearly level grassland, in scattered greasewood brush.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, 2 1/2 ft. diam., with brass cap mkd.</p> |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | T 21 N R 12 E 1/4 S 18 S 17 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| 80.00 | Point for the cor. of secs. 7, 8, 17, and 18. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. |
| | T 21 N R 12 E S 7 S 8 S 18 S 17 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | From the cor. of secs. 8, 9, 16, and 17. |
| | West, bet. secs. 8 and 17. |
| | Over nearly level grassland. |
| 3.60 | BIA Route No. 6910, graded dirt road, 30 ft. wide, bears S. 24° E. and N. 24° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 8 and 17. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, 1 ft. diam., with brass cap mkd. |
| | T 21 N R 12 E S 8 1/4 ——— S 17 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| 78.91 | Dirt road, 9 ft. wide, bears S. 28° E. and N. 28° W. |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 80.00 | <p>The cor. of secs. 7, 8, 17, and 18.</p> <hr/> <p>N. 89°52' W., bet. secs. 7 and 18.</p> <p>Over nearly level grassland.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E S 7 1/4 ——— S 18</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.</p> |
| 40.39 | Dirt road, 8 ft. wide, bears N. 50° E. and S. 50° W. |
| 80.03 | The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., hereinbefore described. |
| | <hr/> <p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 0°03' W., bet. secs. 7 and 8.</p> <p>Over nearly level grassland.</p> |
| 2.15 | Dirt road, 9 ft. wide, bears S. 31° E. and N. 31° W. |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E 1/4 S 7 S 8</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | |
|--------|---|--------|--------|-----|-----|-----|-----|-----|--|
| 80.00 | <p>Point for the cor. of secs. 5, 6, 7, and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, 2 1/2 ft. diam., with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 21 N</td><td>R 12 E</td></tr> <tr><td>S 6</td><td>S 5</td></tr> <tr><td>S 7</td><td>S 8</td></tr> </table> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> <hr/> <p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>West, bet. secs. 5 and 8.</p> <p>Ascend an E. facing slope.</p> | T 21 N | R 12 E | S 6 | S 5 | S 7 | S 8 | | |
| T 21 N | R 12 E | | | | | | | | |
| S 6 | S 5 | | | | | | | | |
| S 7 | S 8 | | | | | | | | |
| 0.88 | <p>Right rim of Padre Canyon, bears S. 4° E. and N. 4° W.</p> <p>Over nearly level grassland.</p> | | | | | | | | |
| 32.95 | <p>BIA Route No. 6910, graded dirt road, 33 ft. wide, bears N. 10° E. and S. 10° W.</p> | | | | | | | | |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 21 N</td><td>R 12 E</td></tr> <tr><td>S 5</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 8</td><td></td></tr> </table> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> | T 21 N | R 12 E | S 5 | | 1/4 | — | S 8 | |
| T 21 N | R 12 E | | | | | | | | |
| S 5 | | | | | | | | | |
| 1/4 | — | | | | | | | | |
| S 8 | | | | | | | | | |
| 80.00 | <p>The cor. of secs. 5, 6, 7, and 8.</p> <hr/> <p>N. 89°53' W., bet. secs. 6 and 7.</p> <p>Over nearly level grassland, in scattered greasewood brush.</p> | | | | | | | | |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> | | | | | | | | |

Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E S 6 1/4 ——— S 7</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> |
| 79.92 | <p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over nearly level grassland, in scattered greasewood brush.</p> |
| 22.64 | Right rim of Padre Canyon, bears N. 74° E. and S. 74° W. |
| 39.09 | Left rim of Padre Canyon, bears S. 22° E. and N. 22° W. |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a brass tablet, 3 1/2 ins. diam., with stem, 2 3/8 ins. long, 1 in. diam., cemented in drill hole in limestone bedrock, flush with ground, with top mkd.</p> <p style="text-align: center;">T 21 N R 12 E 1/4 S 6 S 5</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the brass tablet.</p> <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.</p> |
| 80.12 | <p>The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. T22N R12E S31 S32 S6 S5 T21N 2009.</p> <p>Add the marks 2014 to the brass cap.</p> <p>Set a steel fence post alongside stainless steel post.</p> |


**Survey of the Subdivisional Lines,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona**

| | |
|--------|---|
| CHAINS | <p>Raise a mound of stone around stainless steel post, 3 ft. base, to top.</p> <p>From this cor. point, BIA Route No. 6910, bears S. 89°59' E., 13.05 chs. dist., graded dirt road, 33 ft. wide, bears S. 12° E. and N. 12° W.</p> <hr/> <p style="text-align: center;">Metes-and-Bounds Survey of the Right-of-Way of the Burlington Northern and Santa Fe Railway, T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona.</p> <hr/> <p>Note: the following metes-and-bounds survey in sections 29, 30, 32, 33, and 34, is derived from the Atlantic and Pacific Rail Road Map of the Twelfth Twenty Five Miles of the Western Division, dated December 1, 1882, the Burlington Northern and Santa Fe Railway Station, Right of Way and Track Maps AZ-2/7 and AZ-2/8, and from recovered local monuments established around the boundaries of Canyon Diablo Station of the Burlington Northern and Santa Fe Railway.</p> <hr/> <p style="text-align: center;">In section 29</p> <hr/> <p>The point for AP 1, sec. 29, identical with AP 3, sec. 32, established on the line bet. secs. 29 and 32, 100 ft. perpendicular to the center of the most southwesterly of two railroad tracks, hereinbefore described.</p> <p>From this cor. point, the cor. of secs. 28, 29, 32, and 33 bears East, 25.15 chs. dist., hereinbefore described.</p> <p>N. 64°37' W., on line 1-2, on the northeasterly right-of-way of the Burlington Northern and Santa Fe Railway.</p> <p>In and along a 4-strand barbed wire fence.</p> <p>1.96 Right rim of Yellow Jacket Canyon, bears N. 33° E. and S. 33° W.</p> <p>3.42 BIA Route No. 6910, graded dirt road, 20 ft. wide, bears N. 24° E. and S. 24° W.</p> <p>3.94 Left rim of Yellow Jacket Canyon, bears N. 42° E. and S. 42° W.</p> <p>30.365 Point selected for a witness point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> |
|--------|---|

Metes-and-Bounds Survey of the Right-of-Way
of the Burlington Northern and Santa Fe Railway,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 60.73 | <p style="text-align: center;">W P T 21 N R 12 E S 29 / 2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in a 4-strand barbed wire fence, bears S. 65° E. and N. 65° W.</p> <p>AP 2, sec. 29, identical with AP 1, sec. 30, on the line bet. secs. 29 and 30, hereinbefore described.</p> <p>From this cor. point, the 1/4 sec. cor. of secs. 29 and 30 bears N. 0°03' W., 13.96 chs. dist., hereinbefore described.</p> <hr/> <p>From AP 3, sec. 29, identical with AP 4, sec. 30, on the line bet. secs. 29 and 30, hereinbefore described.</p> <p>From this cor. point, the cor. of secs. 29, 30, 31, and 32 bears S. 0°03' E., 22.69 chs. dist., hereinbefore described.</p> <p>S. 64°37' E., on line 3-4, on the southwesterly right-of-way of the Burlington Northern and Santa Fe Railway, offset 100 ft. from the center of most southwesterly of two railroad tracks.</p> |
| 26.455 | <p>Point selected for a witness point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, 2 1/2 ft. diam., with brass cap mkd.</p> |
| 52.91 | <p style="text-align: center;">W P T 21 N R 12 E / S 29 2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in a 4-strand barbed wire fence, bears S. 65° E. and N. 65° W.</p> <p>AP 4, sec. 29, identical with AP 4, sec. 32, on the line bet. secs. 29 and 32, hereinbefore described.</p> |

Metes-and-Bounds Survey of the Right-of-Way
of the Burlington Northern and Santa Fe Railway,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>From this cor. point, the 1/4 sec. cor. of secs. 29 and 32 bears West, 7.78 chs. dist., hereinbefore described.</p> <hr/> <p style="text-align: center;">In section 30</p> <hr/> <p>From AP 1, sec. 30, identical with AP 2, sec. 29, on the line bet. secs. 29 and 30, hereinbefore described.</p> <p>N. 64°36' W., on line 1-2, on the northeasterly right-of-way of the Burlington Northern and Santa Fe Railway.</p> <p>In and along a 4-strand barbed wire fence.</p> |
| 44.365 | <p>Point selected for a witness point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <div style="text-align: center;"> <p>W P T 21 N R 12 E S 30</p>  <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in a 4-strand barbed wire fence, bears S. 65° E. and N. 65° W.</p> |
| 88.73 | <p>AP 2, sec. 30, on the W. bdy. of the Tp., hereinbefore described.</p> <p>From this cor. point, the cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., bears N. 0°01' E., 16.10 chs. dist., hereinbefore described.</p> <hr/> <p>From AP 3, sec. 30, on the W. bdy. of the Tp., hereinbefore described.</p> <p>From this cor. point, the 1/4 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp., bears S. 0°01' W., 20.55 chs. dist., hereinbefore described.</p> <p>S. 64°36' E., on line 3-4, on the southwesterly right-of-way of the Burlington Northern and Santa Fe Railway.</p> |
| 44.37 | <p>Point selected for a witness point.</p> |

Metes-and-Bounds Survey of the Right-of-Way
of the Burlington Northern and Santa Fe Railway,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 88.74 | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, 3 ft. diam., with brass cap mkd.</p> <div style="text-align: center;"> <p>W P T 21 N R 12 E / S 30 2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 3 lks. S. of a 4-strand barbed wire fence, bears S. 65° E. and N. 65° W.</p> <p>AP 4, sec. 30, identical with AP 3, sec. 29, on the line bet. secs. 29 and 30, hereinbefore described.</p> <hr/> <p style="text-align: center;">In section 32</p> <hr/> <p>From AP 1, sec. 32, identical with AP 5, sec. 33, on the line bet. secs. 32 and 33, hereinbefore described.</p> <p>From this cor. point, the cor. of secs. 28, 29, 32, and 33 bears N. 0°05' E., 11.94 chs. dist., hereinbefore described.</p> <p>Thence on line 1-2, along a circular curve to the left having a central angle of 0°39'00", and a radius of 5829.65 ft.; the chord of said arc bears N. 64°17' W., 1.005 chs. dist.</p> |
| 1.005 | <p>Point for AP 2, sec. 32, identical with the Point of Tangency.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 N R 12 E / S 32 AP 2 2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 1 1/2 lks. N. of a 4-strand barbed wire fence, bears S. 63° E. and N. 64° W.</p> <hr/> |

Metes-and-Bounds Survey of the Right-of-Way
of the Burlington Northern and Santa Fe Railway,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | N. 64°36'30" W., on line 2-3, on the northeasterly right-of-way of the Burlington Northern and Santa Fe Railway. |
| 26.82 | AP 3, sec. 32, identical with AP 1, sec. 29, on the line bet. secs. 29 and 32, hereinbefore described. |
| | From AP 4, sec. 32, identical with AP 4, sec. 29, on the line bet. secs. 29 and 32, hereinbefore described. |
| | S. 64°36'30" E., on line 4-5, on the southwesterly right-of-way of the Burlington Northern and Santa Fe Railway. |
| 1.54 | Left rim of Yellow Jacket Canyon, bears N. 49° E. and S. 49° W. |
| 2.56 | BIA Route No. 6910, graded dirt road, 20 ft. wide, bears N. 48° E. and S. 48° W. |
| 3.75 | Right rim of Yellow Jacket Canyon, bears N. 30° E. and S. 30° W. |
| 33.21 | Point for AP 5, sec. 32, identical with the Point of Curvature. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd. |
| | <p>T 21 N R 12 E</p> <p>AP 5</p>  <p>S 32</p> <p>2014</p> |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Cor. is located on the S. edge of a dirt road, 24 ft. wide, bears S. 63° E. and N. 64° W., and 14 lks. N. of a 4-strand barbed wire fence, bears S. 60° E. and N. 60° W. |
| | Thence on line 5-6, along a circular curve to the right having a central angle of 1°38'45", and a radius of 5629.65 ft.; the chord of said arc bears S. 63°47' E., 2.452 chs. dist. |
| 2.452 | AP 6, sec. 32, identical with AP 6, sec. 33, on the line bet. secs. 32 and 33, hereinbefore described. |
| | From this cor. point, the 1/4 sec. cor. of secs. 32 and 33 bears S. 0°05' W., 24.68 chs. dist., hereinbefore described. |


Metes-and-Bounds Survey of the Right-of-Way
of the Burlington Northern and Santa Fe Railway,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | In section 33 |
|--------|---|
| | <p>From AP 1, sec. 33, identical with AP 5, sec. 34, on the line bet. secs. 33 and 34, hereinbefore described.</p> <p>From this cor. point, the 1/4 sec. cor. of secs. 33 and 34 bears N. 0°08' E., 6.52 chs. Dist., hereinbefore described.</p> <p>N. 61°33'30" W., on line 1-2, on the northeasterly boundary of Canyon Diablo Station of the Burlington Northern and Santa Fe Railway.</p> |
| 35.04 | Point on line, established by person(s) unknown, monumented with a length of railroad track, 4 x 3 1/2 ins., firmly set, projecting 3 ft. above the ground, in a 4-strand barbed wire fence, bears S. 62° E. and N. 62° W. |
| 42.85 | Point on line, established by person(s) unknown, monumented with a length of railroad track, 4 1/2 x 4 ins., firmly set, projecting 4 ft. above the ground, in a 4-strand barbed wire fence, bears S. 62° E. and N. 62° W. |
| 78.25 | <p>Point for AP 2, sec. 33, identical with the NW corner of Canyon Diablo Station of the Burlington Northern and Santa Fe Railway.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E S 33  AP 2 2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on a N. facing slope, in native grasses and greasewood brush.</p> |
| | <p>S. 28°26'30" W., on line 2-3, on the northwesterly boundary of Canyon Diablo Station of the Burlington Northern and Santa Fe Railway.</p> |
| 6.95 | 4-strand barbed wire fence, bears S. 67° E. and N. 67° W. |
| 7.58 | Point for AP 3, sec. 33, at intersection of the northwesterly boundary of Canyon Diablo Station and the northeasterly right-of-way of the Burlington Northern and Santa Fe Railway. |

Metes-and-Bounds Survey of the Right-of-Way
of the Burlington Northern and Santa Fe Railway,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, 3 1/2 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E S 33  AP 3 2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>N. 61°33'30" W., on line 3-4, on the northeasterly right-of-way of the Burlington Northern and Santa Fe Railway.</p> |
| 3.68 | 4-strand barbed wire fence, bears S. 75° E. and N. 75° W. |
| 4.80 | <p>Point for AP 4, sec. 33, identical with the Point of Curvature.</p> <p>Set a brass tablet, 3 1/2 ins. diam., with stem, 2 3/8 ins. long, 1 in. diam., cemented in drill hole in limestone bedrock, 5 ins. below grade, with top mkd.</p> <p style="text-align: center;">T 21 N R 12 E S 33  AP 4 2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the brass tablet.</p> <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>Cor. is located 10 lks. N. of a 4-strand barbed wire fence, bears S. 63° E. and N. 63° W.</p> <hr/> <p>Thence on line 4-5, along a circular curve to the left having a central angle of 2°24'00", and a radius of 5829.65 ft.; the chord of said arc bears N. 62°45' W., 3.698 chs. dist.</p> |
| 3.698 | <p>AP 5, sec. 33, identical with AP 1, sec. 32, on the line bet. secs. 32 and 33, hereinbefore described.</p> <hr/> <p>From AP 6, sec. 33, identical with AP 6, sec. 32, on the line bet. secs. 32 and 33, hereinbefore described.</p> |

**Metes-and-Bounds Survey of the Right-of-Way
of the Burlington Northern and Santa Fe Railway,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona**

| CHAINS | |
|--------|---|
| 2.090 | <p>Thence on line 6-7, along a circular curve to the right having a central angle of 1°24'15", and a radius of 5629.65 ft.; the chord of said arc bears S. 62°16' E., 2.089 chs. dist.</p> <p>Point for AP 7, sec. 33, identical with the Point of Tangency.</p> <p>Set a brass tablet, 3 1/4 ins. diam., with stem, 3 ins. long, 1 in. diam., cemented in drill hole in limestone bedrock, 2 ins. below grade, with top mkd.</p> <div style="text-align: center;"> <p>T 21 N R 12 E</p> <p>AP 7</p>  <p>S 33 2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the brass tablet.</p> <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>Cor. is located on S. edge of a dirt road, 24 ft. wide, bears S. 62° E. and N. 63° W., and 22 lks. N. of a 4-strand barbed wire fence, bears S. 60° E. and N. 60° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 61°33'30" E., on line 7-8, on the southwesterly right-of-way of the Burlington Northern and Santa Fe Railway.</p> |
| 4.80 | <p>Point for AP 8, sec. 33, at intersection of the northwesterly boundary of Diablo Station and the southwesterly right-of-way of the Burlington Northern and Santa Fe Railway.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 N R 12 E</p> <p>S 33 > AP 8</p>  <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 28°26'30" W., on line 8-9, on the northwesterly boundary of Canyon Diablo Station of the Burlington Northern and Santa Fe Railway.</p> |
| 0.28 | <p>4-strand barbed wire fence, bears S. 62° E. and N. 62° W.</p> |


Metes-and-Bounds Survey of the Right-of-Way
of the Burlington Northern and Santa Fe Railway,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 7.58 | <p>Point for AP 9, sec. 33, identical with the SW corner of Canyon Diablo Station of the Burlington Northern and Santa Fe Railway.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 N R 12 E</p> <p>S 33 </p> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 61°33'30" E., on line 9-10, on the southwesterly boundary of Canyon Diablo Station of the Burlington Northern and Santa Fe Railway.</p> |
| 9.37 | Left rim of Canyon Diablo, bears N. 18° E. and S. 18° W. |
| 17.64 | Right rim of Canyon Diablo, bears N. 32° E. and S. 32° W. |
| 22.43 | Point on line, established by person(s) unknown, monumented with a length of railroad track, 4 x 4 ins., firmly set, projecting 4 ft. above the ground, with a steel U-post set alongside, in remains of a fence line, bears S. 62° E. and N. 62° W. |
| 26.89 | Point on line, established by person(s) unknown, monumented with a length of railroad track, 4 x 3 ins., firmly set, projecting 3 ft. above the ground, mkd. C.E. & I Co. SEC. 851 III 08, with a steel U-post set alongside, in remains of a fence line, bears S. 62° E. and N. 62° W. |
| 34.34 | Point on line, established by person(s) unknown, monumented with a length of railroad track, 4 x 3 ins., firmly set, projecting 3 1/2 ft. above the ground, with a steel U-post set alongside, in remains of a fence line, bears S. 62° E. and N. 62° W. |
| 42.03 | Point on line, established by person(s) unknown, monumented with a length of railroad track, 4 x 3 ins., firmly set, projecting 4 ft. above the ground, mkd. HUTTE 1881 NBC, in remains of a fence line, bears S. 62° E. and N. 62° W. |
| 49.73 | Point on line, established by person(s) unknown, monumented with a length of railroad track, 4 x 3 1/2 ins., firmly set, projecting 3 ft. above the ground, mkd. 1881 NBC, in remains of a fence line, bears S. 62° E. and N. 62° W. |
| 80.30 | Point for AP 10, sec. 33, identical with the SE corner of Diablo Station of the Burlington Northern and Santa Fe Railway. |


Metes-and-Bounds Survey of the Right-of-Way
of the Burlington Northern and Santa Fe Railway,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 12 E AP 10 S 33 2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located N. 30° W., 4 1/2 lks. dist., from end of remains of a fence line, bears N. 28° E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 28°26'30" E., on line 10-11, on the southeasterly boundary of Canyon Diablo Station of the Burlington Northern and Santa Fe Railway.</p> |
| 7.58 | <p>Point for AP 11, sec. 33, at intersection of the southeasterly boundary of Canyon Diablo Station and the southwesterly right-of-way of the Burlington Northern and Santa Fe Railway, established by person(s) unknown, monumented with a length of railroad track, 4 x 3 ins., firmly set, projecting 38 ins. above the ground, mkd. KRUPP 1880 NB & Co., with a railroad tie fencepost, 7 x 7 ins., 6 ft. high, alongside. Not remonumented.</p> <p>Cor. is located at a fence corner, fences bear S. 62° E. and S. 28° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 61°33' E., on line 11-12, on the southwesterly right-of-way of the Burlington Northern and Santa Fe Railway.</p> <p>In and along a 4-strand barbed wire fence.</p> |
| 3.66 | <p>AP 12, sec. 33, identical with AP 6, sec. 34, on the line bet. secs. 33 and 34, hereinbefore described.</p> <p>From this cor. point, the stan. cor. of secs. 33 and 34 bears S. 0°08' W., 21.26 chs. dist., hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From AP 13, sec. 33, identical with AP 2, sec. 34, on the line bet. secs. 33 and 34, hereinbefore described.</p> <p>From this cor. point, the 1/4 sec. cor. of secs. 33 and 34 bears N. 0°08' E., 15.13 chs. dist., hereinbefore described.</p> <p>N. 61°33' W., on line 13-14, on the northeasterly right-of-way of the Burlington Northern and Santa Fe Railway.</p> |


Metes-and-Bounds Survey of the Right-of-Way
of the Burlington Northern and Santa Fe Railway,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| | |
|---|---|
| <p>CHAINS</p> <p>2.03</p> <p>3.76</p> <p>25.945</p> | <p>In and along a 4-strand barbed wire fence.</p> <p>Point for AP 14, sec. 33, at intersection of the southeasterly boundary of Canyon Diablo Station and the northeasterly right-of-way of the Burlington Northern and Santa Fe Railway.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground to bedrock, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 N R 12 E</p>  <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located at a fence corner, fences bear N. 28° E., S. 62° E., and N. 60° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 28°26'30" E., on line 14-15, on the southeasterly boundary of Canyon Diablo Station of the Burlington Northern and Santa Fe Railway.</p> <p>AP 15, sec. 33, identical with AP 3, sec. 34, on the line bet. secs. 33 and 34, hereinbefore described.</p> <p>From this cor. point, the 1/4 sec. cor. of secs. 33 and 34 bears N. 0°08' E., 10.85 chs. dist., hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p style="text-align: center;">In section 34</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From AP 1, sec. 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>From this cor. point, the stan. cor. of secs. 34 and 35 bears S. 89°59' E., 34.46 chs. dist., hereinbefore described.</p> <p>N. 61°33' W., on line 1-2, on the northeasterly right-of-way of the Burlington Northern and Santa Fe Railway.</p> <p>In and along a 4-strand barbed wire fence.</p> <p>Point selected for a witness point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.</p> |
|---|---|

Metes-and-Bounds Survey of the Right-of-Way
of the Burlington Northern and Santa Fe Railway,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | W P T 21 N R 12 E S 34  2014 |
| 51.89 | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. AP 2, sec. 34, identical with AP 13, sec. 33, on the line bet. secs. 33 and 34, hereinbefore described. |
| | <hr/> From AP 3, sec. 34, identical with AP 15, sec. 33, on the line bet. secs. 33 and 34, hereinbefore described. N. 28°26'30" E., on line 3-4, on the southeasterly boundary of Canyon Diablo Station of the Burlington Northern and Santa Fe Railway. |
| 3.36 | Dirt road, 13 lks. wide, bears S. 20° E. and N. 20° W. |
| 3.81 | Point for AP 4, sec. 34, identical with the NE corner of Canyon Diablo Station of the Burlington Northern and Santa Fe Railway. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, 2 1/2 ft. diam., with brass cap mkd. |
| | T 21 N R 12 E  AP 4 S 34 2014 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | <hr/> N. 61°33'30" W., on line 4-5, on the northeasterly boundary of Canyon Diablo Station of the Burlington Northern and Santa Fe Railway. |
| 0.55 | Dirt road, 9 ft. wide, bears S. 20° E. and N. 20° W. |
| 2.05 | AP 5, sec. 34, identical with AP 1, sec. 33, on the line bet. secs. 33 and 34, hereinbefore described. |
| | <hr/> From AP 6, sec. 34, identical with AP 12, sec. 33, on the line bet. secs. 33 and 34, hereinbefore described. |

Metes-and-Bounds Survey of the Right-of-Way
of the Burlington Northern and Santa Fe Railway,
T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>S. 61°33' E., on line 6-7, on the southwesterly right-of-way of the Burlington Northern and Santa Fe Railway.</p> <p>In and along a 4-strand barbed wire fence.</p> |
| 4.41 | Dirt road, 17 ft. wide, bears N. 21° E. and S. 21° W. |
| 22.33 | <p>Point selected for a witness point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 9 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>W P</p> <p>T 21 N R 12 E</p>  <p>S 34</p> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> |
| 44.66 | <p>AP 7, sec. 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 34 bears S. 89°59' E., 0.76 chs. dist., hereinbefore described.</p> <hr style="width: 60%; margin-left: 0;"/> |

T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | GENERAL DESCRIPTION |
|--------|--|
| | <hr/> <p data-bbox="386 373 1421 432">This survey is located on the Navajo Indian Reservation, about 10 miles SW of the village of Leupp, Arizona.</p> <p data-bbox="386 468 1421 611">Most of the township consists of nearly level to gently rolling terrain, cut by Canyon Diablo, Padre Canyon and Yellow Jacket Canyon. The area is extremely rocky, with vegetation consisting of native grasses, greasewood, Mormon Tea, yucca, and prickly pear, with scattering juniper timber.</p> <p data-bbox="386 646 1421 764">BIA Route 6910 traverses the westerly portion of the township in a northerly and southerly direction. BIA Route 6930 traverses the easterly portion of the township in a northeasterly and southwesterly direction.</p> <p data-bbox="386 800 1421 917">The mean magnetic declination of $10 \frac{3}{4}^{\circ}$ was derived from the NOAA National Geophysical Data Center magnetic field calculator program, utilizing the World Magnetic Model for Epoch 2010 for the dates of the survey.</p> <hr/> |

CERTIFICATE OF SURVEY

I, Wayne S. Hancock, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 22nd day of January, 2014, I have dependently resurveyed a portion of the Fifth Standard Parallel North (south boundary) and west boundary, surveyed the east boundary and the subdivisional lines, and conducted metes-and-bounds survey, T. 21 N., R. 12 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Surveying Instructions for the Survey of the Public Lands of the United States, 2009, and in specific manner described in the foregoing field notes.

7/29/2014
(Date)

Wayne S. Hancock
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the Fifth Standard Parallel North (south boundary) and west boundary, the survey of the east boundary and subdivisional lines, and metes-and-bounds survey, T. 21 N., R. 12 E., Gila and Salt River Meridian, in the State of Arizona, executed by Wayne S. Hancock, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

8/7/2014
(Date)

[Signature]
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 21 N., R. 12 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____~~
~~(Date)~~

~~_____~~
~~(Chief Cadastral Surveyor of Arizona)~~