

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
A PORTION OF THE SUBDIVISIONAL LINES,
PORTIONS OF MINERAL SURVEY NUMBERS 4376 AND 4377
AND
THE SUBDIVISION OF SECTIONS 31 and 32
TOWNSHIP 23 SOUTH, RANGE 21 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Gordon R. Bubel, Cadastral Surveyor

Under Special Instructions dated February 25, 2013, approved February 25, 2013 which provided for the surveys included under Group No. 1112, and assignment instructions dated February 25, 2013.

Survey commenced March 27, 2013

Survey completed November 22, 2013

INDEX DIAGRAM

TOWNSHIP 23 SOUTH RANGE 21 EAST
 GILA & SALT RIVER MERIDIAN, ARIZONA

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30 15	29 11	28	27	26	25
31	9 32 4	7 33	34	35	36

Mineral Survey number 4376 and 4377..... Pages 16-18
 Subdivision of Section 31 Pages 18-19
 Subdivision of Section 32 Pages 20-28

T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the south boundary, a portion of the subdivisional lines, portions of Mineral Survey number's 4376 and 4377, and the subdivision of sections 31 and 32, Township 23 South, Range 21 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

In 1901, Philip Contzen surveyed the east 5 miles of the south boundary and portions of the subdivisional lines. In 1916, Sidney E. Blout retraced and resurveyed the east 5 miles of the south boundary and surveyed the mile between sections 6 and 31, on the south boundary of the township. Robert Lenon in 1954, surveyed Mineral Survey number 4376 and in 1954-55, Lenon surveyed Mineral Survey number 4377. In 1970, Louise D. Gilbert remonumented the 1/4 section corner of sections 31 and 32 and the section corner of sections 29, 30, 31 and 32. In 1976, Harry K. Smith resurveyed portions of the subdivisional lines.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions dated February 25, 2013, for Group Number 1112, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation model R8 receiver, at the base stations and Trimble Navigation model 5700 receiver at the rover stations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS), AZCO COCHISE COUNTY 2 CORS ARP, AZAM SOPORI ELEM SCH CORS ARP and AZBR KBC LIBRARY CORS ARP.

The NAD 83(2011)(EPOCH:2010.0000), geographic position of the following two corners:

The section corner of sections 4, 5, 32, and 33, on the south boundary of the township is:

Latitude: 31°22'47.973" N.

Longitude: 110°13'26.511" W.

T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS

The quarter section corner of 30 and 31 is:

Latitude: 31°23'40.521" N. Longitude: 110°14'57.274" W.

The mean magnetic declination is 10° E.

**Dependent Resurvey of a Portion of the South Boundary,
T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona**

Restoring the resurvey executed by
Sidney E. Blout, in 1916

Beginning at the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., reestablished by Thomas F. Luckow, Arizona R.L.S., No. 4080, in 1990, as recorded in Cochise County Recorder's Office in Book 5, Records of Surveys at page 21. Monumented with an iron rod, 19 ins. long, 7/8 in. diam., set 8 ins. below the surface of Stone Ridge Road, this is accepted as a careful and faithful reestablishment of the original cor.

from which a reference monument established by Kevin P. Gilbert, Arizona, No. 14181, in 1994.

A rebar, 1/2 in. diam., projecting 1 in. above ground, bears S. 88°17' W., 20.0 ft. dist. with attached plastic cap mkd. RLS 14181.

and a new reference monument

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground for a reference monument, bears N. 89°57' W., 33.0 ft. dist. with brass cap mkd. T23S R21E S32 33.0 FT TO COR. T24S R21E S5 2013 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

N. 89°57' W., bet. secs. 5 and 32, on the S. bdy. of the Tp.

In and along, barbed wire fence, through burnt oak timber.

- | | |
|------|---|
| 0.28 | West edge of Stone Ridge Road, graveled and graded, 22 ft. wide, bears N. and S. |
| 3.74 | Fence cor., with barbed wire fences bearing, N., E., and W. |
| 5.46 | Fence cor., with barbed wire fences bearing, N., E., and W. |
| 9.84 | From this point, a fence cor. with barbed wire fences bearing, N., E., and W., bears N., 2 lks. dist. |

Dependent Resurvey of a Portion of the South Boundary,
T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
15.27	Rebar, 1/2 in. diam., firmly set, projecting 30 ins. above ground, with attached plastic cap mkd. RLS 14181.
20.00	<p>The E. 1/16 sec. cor. of sec. 5, only T. 24 S., R. 21 E., established by Kevin P. Gilbert, Arizona R.L.S. No. 14181, date unknown, monumented with a rebar 1/2 in. diam., firmly set, projecting 1 in. above ground with attached plastic cap stamped RLS 14181. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>Cor. is located 38 lks. S. of a barbed wire fence, bears irregularly E. and W., across flood damaged area.</p>
29.65	Fence cor., with barbed wire fences bearing, N., E., and W.
29.85	<p>Cor. 1, M.S. No. 4376, Trader lode, identical with the SW cor. of the Prince placer (patented), monumented with a marble stone, 10 x 4 ins., firmly set, projecting 10 ins. above ground, mkd 4376 on the NW face.</p> <p>A 1 1/2 in. diam., iron pipe, firmly set, projecting 4 ins. above ground, with attached 2 x 2 1/2 ins. bronze plate, is set alongside the marble stone. The bronze plate is mkd. SOUTH EAST CORNER TRADER NO-1. Cor. is located in a barbed wire fence, bears E. and W.</p> <p>A mound of stone, 3 ft. base, 1 1/2 ft. high, is alongside and W. of the marble stone.</p> <p>An aluminum post, with USFS sign # 54-2, is set alongside the cor.</p> <p>Continuing measurement, identical with line 1-4, M.S. No. 4376, Trader lode.</p>
34.10	Fence cor., with barbed wire fences bearing, N., E., and W.
39.64	<p>The 1/4 sec. cor. of sec. 32 only, T. 23 S., R. 21 E., monumented with a fractured granite stone, 18 x 12 x 6 ins., firmly set, 11 ins. in the ground, mkd. 4 S32 on the N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 23 S R 21 E 1/4 S 32 —</p> <p style="text-align: center;">T 24 S R 21 E</p> <p style="text-align: center;">2013</p>

Dependent Resurvey of a Portion of the South Boundary,
T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <p>Cor. is located in a barbed wire fence, bears E. and W.</p> <p>An aluminum post, with USFS signs #'s 54-2 and 54-9, is set alongside the cor.</p> <p>Continuing measurement</p>
40.01	<p>The 1/4 sec. cor. of sec. 5 only, T. 24 S., R. 21 E., monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. 1/4 S5 1916. Add the marks T23S R21E to the N. portion of brass cap and the marks T24S R21E 2013 to the S. portion of brass cap.</p> <p>from which</p> <p style="padding-left: 40px;">An oak snag, 12 ins. diam., bears S. 73 3/4° E., 50 lks. dist., no marks visible. (Record: S. 72 1/4° E.)</p> <p>Cor. is located in a barbed wire fence, bears E. and W.</p> <p>An aluminum post, with USFS signs #'s 54-2 and 54-9, is set alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/>
12.57	<p>N. 89°57' W., beginning new measurement.</p> <p>Cor. 4, M.S. No. 4376, Trader lode, monumented with a masonry nail with a brass washer, set in a rhyolite boulder, 18 x 10 x 6 ins. high, scribed T-4-4376.</p> <p>from which</p> <p style="padding-left: 40px;">An oak snag, 10 ins. diam., bears S. 21° E., 15.5 ft. dist., no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T23S R21E S32 MS4376 TRADER C4 S5 T24S R21E 2013</p>

**Dependent Resurvey of a Portion of the South Boundary,
T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Incorporate the scribed rhyolite boulder, within the mound of stone.</p> <p>A 1 1/2 in. diam., iron pipe, firmly set, projecting 7 ins. above ground, with attached 2 x 2 1/2 ins. bronze plate, is set alongside the stainless steel post. The bronze plate is mkd. SOUTH WEST TRADER NO-4.</p> <p>Cor. is located at the corner of a downed, barbed wire fences, bearing N. and E.</p> <p>An aluminum post, with burnt USFS signs #'s 54-2 and 54-9, is alongside the cor. Remove old post and signs, replace with new.</p> <p>Continuing measurement, across N. facing slope, through burnt oak timber.</p> <p>39.27 The cor. of secs. 31 and 32, T. 23 S., R. 21 E., monumented with a granite stone, 11 x 9 ins. firmly set, projecting 12 ins. above ground, with 5 grooves on the E. face and 1 groove on the W. face.</p> <p>Continuing measurement.</p> <p>40.07 The cor. of secs. 5 and 6, T. 24 S., R. 21 E., monumented with an iron post, 2 ins. diam., firmly set, projecting 20 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. S6 S5 T24S R21E 1916.</p> <hr/> <p align="center">Dependent Resurvey of a Portion of the Subdivisional Lines, T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p align="center">Restoring the survey executed by Philip Contzen, in 1901</p> <hr/> <p>From the 1/4 sec. cor. of secs. 32 and 33, perpetuated by Thomas F. Luckow, Arizona R.L.S. No. 4080, in 1990, recorded in Cochise County Recorder's Office in Book 5, Records of Survey at page 21. Monumented with an aluminum rod, 3/4 in. diam., firmly set, projecting 4 ins. above ground, encircled with a collar of stone, with aluminum cap mkd. USFS 1/4 S32 S33 RLS 4080 1990. This is accepted as a careful and faithful perpetuation of the cor. position.</p> <p>from which the orig. bearing trees</p> <p align="center">An oak, 40 ins. diam., bears S. 57 1/4° E., 114 lks. dist., with a healed blaze. (Record: N. 56° E.)</p>
--------	---

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>10.03</p>	<p>A spike, in the center of a rotted oak stump, bears S. 5° W., 85 lks. dist.</p> <p>and a bearing tree of unknown origin.</p> <p>An oak, 16 ins. diam., bears S. 10° W., 76 lks. dist., with a healed blaze.</p> <p>Cor. is located 30 lks. E. of a woven wire fence, bears N. and S.</p> <p>From this cor., an open end iron pipe, 4 ins. diam., projecting 33 ins. above ground, bears S. 51°18' W., 30 lks. dist., origin unknown. This monument was utilized in the subdivision of sec. 32, by R. Gregg Dotson, Arizona R.L.S. No. 13056, in 1987, as recorded in Cochise County Recorder's Office in Book 4, Records of Survey at page 20.</p> <p>N. 0°19' E., bet. secs. 32 and 33.</p> <p>Across patented lands, over rolling grass lands, with scattered oak timber.</p> <p>The S-N 1/64 sec. cor. of secs. 32 and 33, established by Kevin P. Gilbert, Arizona R.L.S. No. 14181, in 1992, recorded in Cochise County Recorder's Office in Book 6, Records of Surveys at page 80. Monumented with a rebar 18 ins. long, 1/2 in. diam., firmly set, 14 ins. in the ground, with attached plastic cap stamped RLS 14181. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T23S R21E S-N 1/64</p> <p style="text-align: center;">S32 S33</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, insert the rebar inside the stainless steel post.</p> <p>Set an aluminum post, with USFS signs #'s 54-2 and 54-9, attached alongside the cor.</p> <p>Cor. is located 25 lks. E. of a barbed wire fence, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/>
----------------------------	--

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°19' E., beginning new measurement.
3.03	Rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with attached plastic cap mkd. RLS 14181.
30.10	<p>The cor. of secs. 28, 29, 32, and 33, perpetuated by George W. McKay, Arizona R.L.S. No. 20369, in 1987, according to USFS FORM 7100-52, obtained from Coronado National Forest Supervisor's Office, Tucson, AZ. Monumented with an aluminum rod, 3/4 in. diam., firmly set, projecting 8 ins. above ground, with aluminum cap mkd. USFS T23S R21E S29 S28 S32 S33 LS 20639 1987. This is accepted as a careful and faithful perpetuation of the cor. position.</p> <p>from which an original bearing tree</p> <p style="padding-left: 40px;">A forked oak, 36 ins. diam. at base, bears S. 21 1/2° E., 328 lks. dist., with an open blaze, on a 16 ins. diam., limb.(Record: 322 lks. dist.)</p> <p>An aluminum post, with USFS signs #'s 54-2 and 54-9, is set alongside the cor.</p> <p>Cor. is locate 1 lk. NW of a fence cor., with barbed wire fences bearing E., S., and W.</p> <hr/> <p>From the cor. of secs. 31 and 32 only, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°04' W., bet. secs. 31 and 32.</p> <p>Descending, over N. facing slope, through burnt oak timber.</p>
14.30	From this point, cor. of fences bears E., 3 lks. dist., with dilapidated barbed wire fences, bearing N. and E.
15.015	<p>The N-S-S 1/256 sec. cor. of secs. 31 and 32, identical with the SW cor. of patented placer claim Hutch, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, projecting 5 ins. above ground, with attached, burnt plastic cap, origin unknown. This is accepted as a careful and faithful determination of the cor. point.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T23S R21E N-S-S 1/256 S 31 S 32 2013</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, insert the rebar inside the stainless steel post.</p>
	<p>Set an aluminum post, with USFS sign # 54-2, attached alongside the cor.</p>
	<p>Cor. is located 1.5 lks. W. of a dilapidated barbed wire fence, bears N. and S.</p>
	<p>From this cor., an open end iron pipe, 1 in. diam., projecting 8 ins. above ground, bears N. 2°48' E., 25 lks. dist.</p>
	<p style="text-align: center;">—————</p> <p>N. 0°04' W., beginning new measurement.</p>
19.50	<p>Ash Canyon Road, graded, 15 ft. wide, bears N. 75° E. and S. 75° W.</p>
20.01	<p>A rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground, with attached aluminum cap, mkd. COCHISE COUNTY R/W 1992 LS 14181 PUBLIC WORKS</p>
20.03	<p>The N-N-S 1/256 sec. cor. of secs. 31 and 32, identical with the NW cor. of patented placer claim Hutch, established by Kevin P. Gilbert, Arizona R.L.S. No. 14181, in 1992, recorded in Cochise County Recorder's Office in Book 6, Records of Surveys at page 22. Monumented with a rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground, with attached aluminum cap mkd. COCHISE COUNTY N-N-S 1/256 S32 1992 PUBLIC WORKS. This is accepted as a careful and faithful determination of the cor. point.</p>
	<p>Set an aluminum post, with USFS sign # 54-2, attached alongside the cor.</p>
23.45	<p>Graded road, 16 ft. wide, bears N. 75° E. and S. 75° W.</p>
25.04	<p>The 1/4 sec. cor. of secs. 31 and 32, remonumented in 1970, with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. T23S R21E 1/4 S31 S32 1970. Add the marks 2013 to the brass cap.</p>
	<p>from which an original bearing tree</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A sycamore, 24 ins. diam., bears N. 36° E., 189 lks. dist., no marks visible.</p> <p>An aluminum post, with burnt USFS signs #'s 54-2 and 54-9, is alongside the cor. Remove old post and signs, replace with new.</p> <p>Cor. is located, 8 lks. S. of a downed barbed wire fence, bears E. and W.</p> <hr/> <p>N. 0°03' E., beginning new measurement.</p> <p>Over patented lands.</p>
20.185	<p>Point for the N. 1/16 sec. cor. of secs. 31 and 32, not monumented.</p>
40.37	<p>The cor. of secs. 29, 30, 31, and 32, remonumented in 1970, with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, in a collar of stone, with brass cap mkd. T23S R21E S30 S29 S31 S32 1970. Add the marks 2013 to the brass cap.</p> <p>Cor. is located on the S. side of a fence cor., with barbed wire fences bearing S. and W.</p> <hr/> <p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>N. 89°57' W., bet. secs. 29 and 32.</p> <p>Over rolling grass lands, with scattered oak timber, in and along a barbed wire fence.</p>
11.03	<p>From this point, a rebar 1/2 in. diam., firmly set, projecting 1 in. above ground, with attached plastic cap mkd. RLS 14181, bears N., 4 lks. dist.</p> <p>The rebar is located 9 lks. S. of a barbed wire fence, bears E. and W.</p>
21.62	<p>From this point, a rebar 1/2 in. diam., firmly set, projecting 1 in. above ground, with attached plastic cap mkd. RLS 14181, bears N., 7 lks. dist.</p> <p>The rebar is located 15 lks. S. of a barbed wire fence, bears E. and W.</p>
27.04	<p>From this point, a rebar 1/2 in. diam., firmly set, projecting 1 in. above ground, bears N., 9 lks. dist.</p> <p>The rebar is located 16 lks. S. of a barbed wire fence, bears E. and W.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
30.26	<p>From this point, a rebar 1/2 in. diam., firmly set, projecting 1 in. above ground, with attached brass wafer, mkd. RLS 23379, bears N., 9 lks. dist.</p> <p>The rebar is located 17 lks. S. of a barbed wire fence, bears E. and W.</p>
37.50	<p>Old barbed wire fence bearing E. and newer barbed wire fence bearing W.</p>
39.84	<p>Entrance fence to Wild Horse Subdivision, brick, 3 3/4 ft. high, 1 ft. wide, bears N. and bears S., for 11 lks. to intersection with E. and W. bearing, barbed wire fence.</p>
40.09	<p>The 1/4 sec. cor. of secs 29 and 32, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, projecting 3 ins. above ground, origin unknown. This is accepted as the best available evidence of the orig. cor.</p> <p>from which an original bearing tree</p> <p style="padding-left: 40px;">An forked oak snag, 25 ins. diam., at base, bears N. 7° W., 288 lks. dist., no marks visible. (Record: 292 lks.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 12 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, seated in concrete, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T 23 S R 21 E</p> <p style="margin-left: 100px;">S 29</p> <p style="margin-left: 100px;">1/4 ———</p> <p style="margin-left: 100px;">S 32</p> <p style="margin-left: 100px;">2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, bury the rebar alongside the stainless steel post.</p> <p>Set an aluminum post, with USFS signs #'s 54-2 and 54-9, attached alongside the cor.</p> <p>Cor. is located in a common area of Wild Horse subdivision, 11 lks. N. of a barbed wire fence, bears E. and W.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor., an aluminum rod, 3/4 in. diam., firmly set, projecting 6 ins. above ground, with attached aluminum cap mkd. USFS LS 4080 1/4 S29 S32 1990, bears S. 62°19' E., 24.5 lks. dist. The origin of this monument, established by Thomas F. Luckow, Arizona R.L.S. No. 4080, in 1990, is recorded in Cochise County Recorder's Office in Book 5, Records of Survey at page 21. This monument was utilized in the subdivision of sec. 32, by Kevin P. Gilbert, Arizona R.L.S. No. 14181, in 1993, as recorded in Cochise County Recorder's Office in Book 6, Records of Survey at page 80.</p>
	<p>Aluminum rod is located in a barbed wire fence, bearing E. and W.</p>
	<p>From this same cor., a rebar 1/2 in. diam., firmly set, projecting 6 ins. above ground, bears N. 56°05' E., 7.1 lks. dist. This monument was utilized in the subdivision of sec. 32, by R. Gregg Dotson, Arizona R.L.S. No. 13056, in 1987, as recorded in Cochise County Recorder's Office in Book 4, Records of Survey at page 20.</p>
	<p>_____</p> <p>N. 89°56' W., beginning new measurement.</p>
	<p>Across landscaped, common area of Wild Horse subdivision, 11 lks. N., of barbed wire fence, bearing E. and W.</p>
6.29	<p>From this point, a plastic telecommunication junction box, 1 x 1 x 3 ft. high, bears S., 6 lks. dist.</p>
11.19	<p>North Easterly right-of-way of Arizona State Highway No. 92, monumented with a bronze disk, 3 ins. diam., set in a 6 ins. diam., concrete cylinder, projecting 2 ins. above ground, with top mkd. ARIZONA HIGHWAY DEPT. P.O.T. 763 + 97.41 1970. Recorded with Arizona Dept. of Transportation, project No. F-012-1-822, Drawing No. D-2-T-428, Sheet 19 of 24.</p> <p>From this cor., an iron rod, 1 in. diam., firmly set, with 3 ins. diam., aluminum cap mkd. ADOT ROW 2008 1238 764 + 04.03 LS 38862 S577801, bears S. 45°21' E., 11.5 lks. dist. Recorded with Arizona Dept. of Transportation, project No. 092 CH 328 H4596 01R, Drawing No. D-2-T-484, Sheet MS-5.</p>
	<p>From this same cor., a fence cor., bears S. 45°51' E., 21.5 lks. dist., with barbed wire fences bearing E. and S. 45° E.</p>
12.79	<p>North Easterly edge of pavement, Arizona State Highway No. 92, bears NW and SE.</p>
13.97	<p>South Westerly edge of same.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
15.61	<p>South Westerly right-of-way of Arizona State Highway No. 92, monumented with a bronze disk, 3 ins. diam., set in a 6 ins. diam., concrete cylinder, projecting 3 ins. above ground, with top mkd. ARIZONA HIGHWAY DEPT. 19. Recorded with Arizona Dept. of Transportation, project No. F-012-1-822, Drawing No. D-2-T 428, Sheet 19 of 24. Cor. is located at fence cor. with barbed wire fences bearing, SE, W. and NW.</p> <p>From this cor., an iron rod, 1 in. diam., firmly set, with 3 ins. diam., aluminum cap mkd. ADOT ROW 2008 1238 761 + 91.02 LS 38862 S577801, bears S. 48°59' E., 9 lks. dist. Recorded with Arizona Dept. of Transportation, project No. 092 CH 328 H4596 01R, Drawing No. D-2-T-484, Sheet MS-5.</p>
19.84	<p>The W 1/16 sec. cor. of secs. 29 and 32, established by Clarence S. Wilcox Arizona P.E. No. 1270, date unknown, monumented with an iron rod, 10 ins. long, 1/4 in. diam., set 7 ins. below ground, with attached brass wafer mkd. PE 1270. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 S R 21 E</p> <p>S 29</p> <p>W 1/16 ———</p> <p>S 32</p> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and the iron pin inside the stainless steel post.</p> <p>Set an aluminum post, with USFS sign # 54-2, attached alongside the cor.</p> <p>Cor. is located 1.5 lks. S., a fence cor., with woven wire fence bearing S. and W. and barbed wire fence bearing E.</p> <p>From this cor., a rebar, 1/2 in. diam., set, 3 ins. below ground, with attached plastic cap mkd. RLS 14181, bears S. 55°49' E., 10 lks. dist. The origin of this monument, established by Kevin P. Gilbert, Arizona R.L.S. No. 14181, in 1993, is recorded in Cochise County Recorder's Office in Book 6, Records of Survey at page 67.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°55' W., beginning new measurement.</p> <p>Over patented lands.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
19.90	The cor. of secs. 29, 30, 31, and 32.
	<hr/> <p style="text-align: center;">Restoring the resurvey executed by Harry K. Smith, in 1976</p> <hr/> <p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>S. 89°57' W., bet. secs. 30 and 31.</p> <p>Ascending, over foot hills of Huachuca Mts., in and along a barbed wire fence, through burnt oak timber.</p>
19.96	<p>The E. 1/16 sec. cor. of secs. 30 and 31, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T23S R21E E 1/16 S30 S31 1976. Add the marks 2013 to the brass cap.</p> <p>A mound of stone, 2 1/2 ft. base, 1 ft. high, is N. of cor.</p> <p>Cor. is located N. 30° E., 1.5 lks. dist., from a fence cor., with barbed wire fences bearing N. and W., and smooth wire fence bearing S. and E.</p> <p>Set an aluminum post, with USFS sign # 54-2, attached alongside the cor.</p> <p>From this cor., a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above ground, with attached brass tag stamped PE 1270, bears E., 4 lks. dist.</p> <p>From this same cor., a rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground, bears E., 6 lks. dist.</p> <hr/> <p>S. 89°57' W., beginning new measurement.</p>
9.20	Stump Canyon Road, graded 12 ft. wide, bears N. 10° E. and S. 10° W.
19.98	<p>The 1/4 sec. cor. of secs. 30 and 31, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T23S R21E 1/4 S30 S31 1976. Add the marks 2013 to the brass cap.</p> <p>from which an orig. bearing tree</p> <p style="padding-left: 40px;">An oak snag, 14 ins. diam., bears S. 26 1/4° E., 34 lks. dist., no marks visible.</p> <p>and a 1976 bearing tree</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS

A juniper snag, 11 ins. diam., bears N. 54 1/4° W.,
205.5 lks. dist., with a burnt blaze. (Record:
N. 54 1/2° W.)

A mound of stone, 3 ft. base, 2 ft. high, is N. of cor.

An aluminum post, with burnt USFS signs #'s 54-2 and 54-9, is
alongside the cor. Remove old post and signs, replace with new.

Cor. is located in a barbed wire fence, bears E. and W., 6 lks.
W., of intersection with fence, bearing S.

**Dependent Resurvey of Portions of M.S. No. 4376,
Trader lode and M.S. No. 4377, Trader Fraction lode,
T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona**

Restoring the Trader lode survey, executed by
Robert Lenon, in 1953 and the Trader Fraction
lode survey, executed by Robert Lenon in 1953-54.

From Cor. 4, M.S. No. 4376, Trader lode, on the S. bdy. of sec.
32, hereinbefore described.

N. 0°32' W., on line 4-3, M.S. No.4376, Trader lode.

Descending, through burnt oak timber, in and along dilapidated
barbed wire fence.

8.00 Cor. 3, M.S. No. 4376, Trader lode, monumented with a rhyolite
stone, 24 x 12 x 10 ins., firmly set, 17 ins. in the ground,
mkd. T3 4376 on a face and C3 on the opposite face.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
18 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to
top, with brass cap mkd.

T 23 S R 21 E

S32 C3
M.S. 4376
TRADER

2013

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post, bury the rhyolite stone alongside the
stainless steel post.

Dependent Resurvey of Portions of M.S. No. 4376,
 Trader lode and M.S. No. 4377, Trader Fraction lode,
 T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p>A 1 1/2 in. diam., iron pipe, firmly set, projecting 1 ins. above ground, with attached 2 x 2 1/2 ins. bronze plate, is set alongside the stainless steel post. The bronze plate is mkd. NORTH WEST C-TRADER NO-3.</p> <p>Set an aluminum post, with USFS sign # 54-2, attached alongside the cor.</p> <p>Cor. is located within a dilapidated barbed wire fence, bears N. and S.</p> <hr/> <p>N. 84°01' E., on line 3-2, M.S. No. 4376, Trader lode.</p> <p>0.06 Cor. 2, M.S. No. 4377, Trader Fraction lode, monumented with a rhyolite stone, 20 x 6 x 6 ins., firmly set, 14 ins. in the ground, mkd. TF 4377 on top face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 S R 21 E S32 M.S. 4377 TR. FRAC. C2</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>An iron pipe, 14 ins. long, 1 1/2 ins. diam., loosely set, projecting 9 ins. above ground, with attached 2 x 2 1/2 ins. bronze plate, is set alongside the stainless steel post. The bronze plate is mkd. SOUTH WEST CORNER TRADER-F NO-2. Bury the iron pipe and rhyolite stone, alongside the stainless steel post.</p> <p>Set an aluminum post, with USFS sign # 54-2, attached alongside the cor.</p> <p>Cor. is located within a dilapidated barbed wire fence, bears N. and S.</p> <hr/> <p>N. 0°34' W., on line 2-3, M.S. No. 4377, Trader Fraction lode.</p> <p>6.79 Cor. 3, M.S. No. 4377, Trader Fraction lode, monumented with a limestone, 28 x 9 x 5 ins., firmly set, 14 ins. in the ground, mkd. 3 TF 4377 on the E. face.</p>
---------------	---

Dependent Resurvey of Portions of M.S. No. 4376,
 Trader lode and M.S. No. 4377, Trader Fraction lode,
 T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to
 top, with brass cap mkd.

T 23 S R 21 E
 S32 C3
 M.S. 4377
 TR. FRAC.
 2013

Deposit a magnet, in a white plastic case, at the base of the
 stainless steel post.

An iron pipe, 15 ins. long, 1 1/2 ins. diam., loosely set,
 projecting 5 ins. above ground, with attached 2 x 2 1/2 ins.
 bronze plate, is set alongside the stainless steel post. The
 bronze plate is mkd. NORTH WEST CORNER TRADER-F NO-3. Bury the
 iron pipe and limestone, alongside the stainless steel post.

Set an aluminum post, with USFS sign # 54-2, attached alongside
 the cor.

Cor. is located 5 lks. S. of the S. edge of pavement, of an
 asphalt surfaced road, 11 ft. wide, bearing E. and W. and
 50 lks. S. of a barbed wire fence, bears E. and W.

From this cor., cor. 4, M.S. No. 4377, Trader Fraction lode,
 identical with the C-N-SE-SW 1/256 sec. cor. of sec. 32,
 identical with the SE corner of the patented placer claim
 Lassie, bears N. 89°52' E., 2.63 chs. dist., monumented with a
 rebar, 1/2 in. diam., set 5 ins. below the surface, of Twin Oaks
 Road, origin unknown. This is accepted as a careful and
 faithful reestablishment of the cor. position.

**Subdivision of Section 31,
 T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona**

Note: The following is a retracement of the survey executed by
 George W. McKay, Arizona R.L.S. No. 20369, in 1989, recorded in
 Cochise County Recorder's Office in Book 5, Records of Survey at
 page 6.

From the 1/4 sec. cor. of secs. 31 and 32, hereinbefore
 described.

S. 89°56' W., on the E. and W. center line of sec. 31.

Ascending over S. and E. facing slopes, through burnt oak
 timber.

Subdivision of Section 31,
T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
18.96	Fence cor., with barbed wire fences, bearing N., E. and W.
19.97	<p>The C-E 1/16 sec. cor. of sec. 31, monumented with a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with attached, melted plastic cap, origin unknown. This is accepted as a careful and faithful determination of the cor. point.</p> <p>The rebar is located on the west terminus of a barbed wire fence, bears E.</p> <p>Set an aluminum post, with USFS sign # 54-2, attached alongside the cor.</p>
39.94	<p>The center 1/4 sec. cor. of sec. 31, monumented with an aluminum rod, 3/4 in. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 2 1/2 ft. base, to top, with aluminum cap mkd. S31 C 1/4 LS 20369 1987. This is accepted as a careful and faithful determination of the cor. point.</p> <p>from which McKay's bearing object</p> <p style="padding-left: 40px;">A limestone outcropping, 10 x 6 x 5 ft. high, bears N. 59 3/4° E., 32.5 lks. dist., chiseled X BO on the exposed W. face.</p> <p>An aluminum post, with USFS signs #'s 54-2 and 54-9, attached is set alongside the cor.</p> <p>Cor. located on a steep, rocky W. facing slope.</p> <hr/> <p>N. 0°03' E., on the N. and S. center line of sec. 31.</p> <p>Descending, over foot hills of Huachuca Mts., across burnt oak timber.</p>
3.70	Barbed wire fence on ridge top, both bear S. 80° E. and N. 80° W.
22.60	Graded road, 12 ft. wide, bears N. 60° E. and S. 60° W.
34.02	<p>A rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with attached aluminum cap mkd. RLS 44133 2010 ALS INC.</p> <p>Rebar is located 15 lks. W., of a downed barbed wire fence, bears N. and S. and 1.5 lks. W. of a rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground.</p>
40.38	The 1/4 sec. cor. of secs. 30 and 31, hereinbefore described.

Subdivision of Section 32,
T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of sec. 32 only, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°04' E., on the N. and S. center line of sec. 32.</p> <p>Over patented lands.</p>
40.16	<p>Point for the center 1/4 sec. cor. of sec. 32, at intersection with the E. and W. center line of sec. 32, not monumented.</p> <p>From this point, a rebar 1/2 in. diam., firmly set, projecting 1 ins. above ground, with attached aluminum cap, mkd. C 1/4 S32 1992 LS 14181, bears N. 83°12' E., 11 lks. dist. The origin of this monument, established by Kevin P. Gilbert, Arizona R.L.S. No. 14181, in 1993, is recorded in Cochise County Recorder's Office in Book 6, Records of Survey at page 80.</p> <p>From this same cor. point, a rebar 1/2 diam., firmly set, projecting 5 ins. above ground, with attached metal wafer, mkd. RLS 10698, bears S. 36°54' E., 5 lks. dist. The origin of this monument, established by R. Gregg Dotson, Arizona R.L.S. No. 10698, in 1987, is recorded in Cochise County Recorder's Office in Book 4, Records of Survey at page 20.</p>
50.225	<p>Point for the C-S-N 1/64 sec. cor. of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T23S R21E S 32 C-S-N 1/64</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set an aluminum post, with USFS sign # 54-2, attached alongside the cor.</p> <p>From this cor., a rebar 1/2 in. diam., firmly set, projecting 1 in. above ground, with attached melted plastic cap, bears S. 83°15' E., 14 lks. dist. The origin of this monument, established by Kevin P. Gilbert, Arizona R.L.S. No. 14181, in 1993, is recorded in Cochise County Recorder's Office in Book 6, Records of Survey at page 87.</p>
60.29	Point for the center N. 1/16 sec. cor., not monumented.
80.42	The 1/4 sec. cor. of secs. 29 and 32, hereinbefore described.

Subdivision of Section 32,
T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 32 and 33, hereinbefore described.</p> <p>S. 89°52' W., on the E. and W. center line of sec. 32.</p> <p>Over patented lands.</p>
39.91	The point for the center 1/4 sec. cor. of sec. 32.
49.82	Point for the C-E-W 1/64 sec. cor. of sec. 32, not monumented.
59.73	<p>The center W. 1/16 sec. cor. of sec. 32, monumented with a rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground, with attached aluminum cap, mkd. SURVEY PT RLS 10698, origin unknown. The number listed on the aluminum cap, is not recognized in the State of Arizona registry. This is accepted as a careful and faithful determination of the cor. point.</p> <p>Cor. is located at the S. terminus of a woven wire fence, bears N.</p> <p>From this cor., a rebar 1/2 in. diam., firmly set, projecting 2 ins. above ground, with attached aluminum cap mkd. COCHISE COUNTY C-W 1/16 RLS 13056 PUBLIC WORKS, bears S. 58°55' W., 3 lks. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°58' W., beginning new measurement.</p>
19.91	<p>The 1/4 sec. cor. of secs. 31 and 32, hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p style="text-align: center;">NE 1/4 Sec. 32.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the S-N 1/64 sec. cor. of secs. 32 and 33, hereinbefore described.</p> <p>S. 89°55' W., on the E. and W., center line of the SE 1/4 of the NE 1/4 and the E. and W. center line of the SW 1/4 of the NE 1/4 of sec. 32, identical with a portion of the N. bdy. of a parcel of land, conveyed from the U.S. via patent number 02-90-0005 in 1989.</p> <p>Over rolling grass lands, with scattered oak timber.</p>
0.25	Barbed wire fence, bears N. and S.
0.45	A rebar, 1/2 in. diam., firmly set, projecting 4 ins. above ground, with attached plastic cap mkd. RLS 14181.
3.61	A rebar, 1/2 in. diam., firmly set, projecting 1 ins. above ground, with attached plastic cap mkd. RLS 14181.

**Subdivision of Section 32,
T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
16.46	From this point, a rebar, 1/2 in. diam., firmly set, projecting 4 ins. above ground, with attached aluminum cap mkd. G.P.S. SURVEY 1999 RLS 28737, bears N., 1 lk. dist.
25.16	Easterly right-of-way fence, Arizona State Highway No. 92, barbed wire, bears S. 38° E. and N. 38° W. A rebar 1/2 in. diam., firmly set, projecting 1 in. above ground, with burnt plastic cap, bears S. 38° E., 1.5 lks. dist. thence across Arizona State Highway No. 92 and utility corridor.
29.01	Westerly right-of-way, Arizona State Highway No. 92. From this point., a rebar 1/2 in. diam., firmly set, projecting 3 in. above ground, with attached brass wafer, mkd. RLS 36913, bears S. 38° E., 2.5 lks. dist. located at intersection of fences, with barbed wire bearing S. 38° E. and plastic plank fence, bearing W.
30.17	From this point., a rebar 1/2 in. diam., firmly set, projecting 4 in. above ground, with attached brass wafer, mkd. RLS 36913, bears S., 1.5 lks. dist. located 1 lk. N. of intersection of fences, with plastic plank fence, bearing E. and S. 75° W.
31.80	Ash Canyon Road, graded, 22 ft. wide, bears N. 75° E. and S. 75° W.
33.15	From this point., a rebar 1/2 in. diam., firmly set, projecting 1 in. above ground, with attached plastic cap mkd. 14181, bears S., 1 lks. dist.
39.96	The C-S-N 1/64 sec. cor. of sec. 32.
<hr/> SW 1/4 Sec. 32. <hr/>	
	From the C-N-SE-SW 1/256 sec. cor. of sec. 32, identical with the SE corner of the patented placer claim Lassie, identical with cor. 4, M.S. no. 4377, Trader Fraction lode, hereinbefore described. N. 89°31' W., on the E. and W. center line of the NW 1/4 of the SE 1/4 of the SW 1/4, sec. 32 and the E. and W. center line of the NE 1/4 of the SW 1/4 of the SW 1/4, sec. 32 and the E. and W. center line of the NW 1/4 of the SW 1/4 of the SW 1/4, sec. 32, identical with the S. boundaries of patented placer claims Lassie and Hutch. Over, asphalt surfaced road, 11 ft. wide.
2.63	From this point, cor. 3, M.S. No. 4377, Trader Fraction lode, bears S., 3 lks. dist., hereinbefore described.

Subdivision of Section 32,
T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
9.30	From this point, a rebar 5/8 in. diam., firmly set, projecting 2 ins. above ground, bears S. 10 lks. dist.
12.35	West edge asphalt surfaced road, 11 ft. wide, SW cor. of pavement, bears S., 12.5 lks. dist.
18.85	W. end of track road, bearing E.
19.23	From this point, a fence cor., bears S., 29 lks. dist., with dilapidated barbed wire fences, bearing N. and W.
19.33	From this point, a rebar, 1/2 in. diam., firmly set, projecting 4 ins. above ground, with attached melted plastic cap, bears N., 9 lks. dist.
24.29	From this point, a rebar, 1/2 in. diam., firmly set, projecting 4 ins. above ground, with attached melted plastic cap, bears N., 4.5 lks. dist.
29.25	The N-S-S 1/256 sec. cor. of secs. 31 and 32, hereinbefore described.
<hr/>	
NW 1/4 Sec. 32.	
<hr/>	
	From the center W. 1/16 sec. cor. of sec. 32, hereinbefore described.
	N. 0°02' E., on the N. and S. center line of the NW 1/4 of sec. 32.
	Along woven wire fence, over patented lands.
10.09	Point for the C-S-NW 1/64 sec. cor. of sec. 32, not monumented.
20.175	Point for the NW 1/16 sec. cor. at intersection with the E. and W. center line of the NW 1/4 of sec. 32, not monumented.
23.325	Point for an angle point, at the NW cor. of a parcel of land, conveyed from the U.S. via patent number 02-90-0012 in 1990.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.
T 23 S R 21 E	
S32 AP	
2013	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Subdivision of Section 32,
T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an aluminum post, with USFS sign # 54-2, attached alongside the cor.</p> <p>Cor. is located on the E. side of a woven wire fence, and 11 lks. W., of the W. edge of Turkey Track Road (graded, 20 ft. wide), both extend N. and S.</p> <p>From this cor., a rebar 5/8 in. diam., firmly set, projecting 3 ins. above ground, bears S. 55°41' E., 5.5 lks. dist. The origin of this monument, established by Hector A. Rochin, Arizona P.E. No. 2472, in 1993, is recorded in Cochise County Recorder's Office in Book 6, Records of Survey at page 84.</p>
27.00	Fence cor., barbed wire fence bears N., woven wire fence bears S. and W.
30.34	Fence cor., woven wire fences bearing N., S. and W.
32.835	Rebar, 1/2 in. diam., firmly set, projecting 4 ins. above ground, located in barbed wire fence, bears N. and S.
32.840	Open end iron pipe, 2 ins. diam., firmly set, projecting 2 ins. above ground, located in barbed wire fence, bears N. and S.
35.33	Fence cor., woven wire fences bearing N. and W.
40.33	The W. 1/16 sec. cor. of secs. 29 and 32, hereinbefore described.
	<hr/> <p>From the point for the center N. 1/16 sec. cor. of sec. 32, hereinbefore described.</p> <p>West, on the E. and W. center line of the NW 1/4 of sec. 32.</p>
9.915	Point for the C-E-NW 1/64 sec. cor., on the E. bdy. of a parcel of land, conveyed from the U.S. via patent number 02-90-0012 in 1990, not monumented; thence over patented lands.
19.83	Point for the NW 1/16 sec. cor. of sec. 32.
	<hr/> <p style="text-align: center;">SE 1/4, NW 1/4 Section 32.</p> <hr/> <p>From the point for the C-E-W 1/64 sec. cor. of sec. 32, hereinbefore described.</p> <p>N. 0°03' E., on the N. and S. center line of the SE 1/4 of the NW 1/4 of sec. 32.</p> <p>Over patented lands</p>

**Subdivision of Section 32,
T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
10.075	<p>Point for the SE-NW 1/64 sec. cor. of sec. 32, identical with the SE cor. of a parcel of land, conveyed from the U.S. via patent number 02-90-0024 in 1990, at intersection with the E. and W. center line of the SE 1/4 of the NW 1/4 of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 S R 21 E S 32 SE-NW 1/64 2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set an aluminum post, with USFS sign # 54-2, attached alongside the cor.</p> <p>From this cor., a rebar 1/2 in. diam., firmly set, projecting 1 in. above ground, with attached plastic cap, mkd RLS 14181, bears S. 84°25' E., 8.5 lks. dist.</p>
14.16	Rebar, 1/2 diam., set in concrete, projecting 2 ins. above ground.
15.58	From this point, a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with attached melted plastic cap, bears E., 9.5 lks. dist.
18.06	<p>Point for an angle point, identical with the NE cor. of a parcel of land, conveyed from the U.S. via patent number 02-90-0024 in 1990, identical with the SE cor. of a parcel of land, conveyed from the U.S. via patent number 02-90-0012 in 1990, not monumented.</p> <p>From this cor., a rebar 1/2 in. diam., firmly set, projecting 1 in. above ground, with melted plastic cap, bears N. 46°02' E., 14 lks. dist.</p>
20.15	<p>Point for the C-E-NW 1/64 sec. cor. of sec. 32.</p> <hr/> <p>From the C-S-N 1/64 sec. cor. of sec. 32.</p> <p>S. 89°56' W., on the E. and W. center line of the SE 1/4 of the NW 1/4 of sec. 32, identical with a portion of the S. bdy. of a parcel of land, conveyed from the U.S. via patent number 02-90-0005 in 1989.</p>
9.915	The SE-NW 1/64 sec. cor.; thence continuing measurement over patented lands.
19.83	<p>Point for the C-S-NW 1/64 sec. cor.</p> <hr/>

Subdivision of Section 32,
T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>NE 1/4, NW 1/4 Section 32.</p> <hr/>
	<p>From the point for the C-E-NW 1/64 sec. cor.</p> <p>N. 0°03' E., on the computed N. and S. center line of the NE 1/4 of the NW 1/4 of sec. 32, identical with a portion of the E. bdy. of a parcel of land, conveyed from the U.S. via patent number 02-90-0012 in 1990.</p>
0.70	<p>From this point, a fence cor. bears W., 20 lks. dist., with woven wire fences, bearing N. 7° E. and S. 50° W.</p>
2.42	<p>Woven wire fence, bears N. 7° E. and S. 7° W.</p>
3.08	<p>Woven wire fence, bears W. and bears E., for 8 lks. to fence cor., with woven wire fence bearing S. 7° W.</p>
3.15	<p>Point for an angle point, at the NE cor. of a parcel of land, conveyed from the U.S. via patent number 02-90-0012 in 1990.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 S R 21 E</p> <p style="text-align: center;">AP</p> <p style="text-align: center;">S32</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/>
	<p>West, on the N. bdy. of a parcel of land, conveyed from the U.S. via patent number 02-90-0012 in 1990.</p>
9.37	<p>From this point, a fence cor. bears S., 5 lks. dist., with woven wire fences, bearing E. and S.</p>
9.80	<p>Turkey Track Road, graded, 20 ft. wide, bears N. and S.</p>
9.92	<p>The angle point, on the NE cor. of a parcel if land, conveyed from the U.S. via patent number 02-90-0012 in 1990, on the N. and S. center line of the NW 1/4 of sec. 32.</p> <hr/>

Subdivision of Section 32,
T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The land encompassed in this survey lies in the southwesterly foothills of the Huachuca Mountains. Elevations range from 5000 to 6000 ft. above sea level.

Grass species with scattered oaks and mesquite is the dominant vegetation. The 2011 monument fire, burned most of the oaks, oak snags with root regrowth is common.

Access is by way of State Highway No. 92, Ash Canyon Road and numerous graded roads.

The mean magnetic declination of 10° E. was derived from the National Oceanic and Atmospheric Administration, National Geophysical Data Center, on line Magnetic Field Calculator, utilizing the World Magnetic Model for Epoch 2010 for the dates of survey.

CERTIFICATE OF SURVEY

I, Gordon R. Bubel, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 25th day of February, 2013, I have dependently resurveyed a portion of the south boundary, a portion of the subdivisional lines, portions of Mineral Survey numbers 4376 and 4377 and subdivided sections 31 and 32, Township 23 South, Range 21 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Surveying Instructions, (2009), and in specific manner described in the foregoing field notes.

APRIL 23, 2015

(Date)

Gordon R. Bubel

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependently resurveyed a portion of the south boundary, a portion of the subdivisional lines, portions of Mineral survey numbers 4376 and 4377 and the subdivision of sections 31 and 32, Township 23 South, Range 21 East, Gila and Salt River Meridian, in the State of Arizona, executed by Gordon R. Bubel, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

5/13/2015

(Date)

[Signature]

(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 23 S., R. 21 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~