Form 9600-9 (December 1979) (formerly 9180-6)

# UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

ORIGINAL

### FIELD NOTES

of the	
Dependent Resurvey	
of a Portion of the	
Subdivisional Lines	
and	
Certain Mining Claims	
and	
the Survey of	
the	
Subdivisions of Section 9	
and the	
Metes-and-Bounds Survey of	
Lot 1, Section 9	
in	
Township 8 North, Range 2 East	
Of the Gila and Salt River Meridia	an,
n the State of Arizona	
EXECUTED BY	
Dennis K. McKay, Cadastral Surveyor	
Inder special instructions dated February 11, 1982_, approved February 11, 1982	
, which provided for the surveys included under U.S. Survey/Gro	oup
Tumber630, and assignment instructions dated February 11, 19 <u>82</u>	<u>.</u> .
Survey commenced February 23 , 19 82	
Survey completed February 24, 1983	

### INDEX DIAGRAM

Townsh	ip <u>8 Nor</u>	rth	, Range	2 East	,
6	8	<b>4</b> 9 7	8	2	1
7	8	7 10 10 1 6 9 5	5 10 3	11	12
18	17	16	15	14	18
19	20	21	22	28	24
30	29	28	27	26	25
31	32	33	84	85	36

Mineral Survey No. 3512 -----pp. 11 - 12 Mineral Survey No. 3743 -----pp. 12 - 20 Survey of Lot 1, Sec. 9 -----pp. 20 - 21 T 8 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, the survey of subdivisions of section 9, the metes—and—bounds survey of Lot 1 in sec. 9, and the retracement and restoration of certain mining claims in Township 8 North, Range 2 East, Gila and Salt River Meridian, Arizona.

The north boundary of section 9 was surveyed in 1910 by Alfred N. Oliver, U.S. Deputy Surveyor. The east, south and west boundaries of section 9 were surveyed in 1917 by George F. Rigby, U.S. Surveyor. The lodes of Marietta and the Southeast Extension of Marietta were surveyed under Mineral Survey No. 3512, in 1918 by Richard T. Belcher, U.S. Mineral Surveyor. The lodes of April, April No. 1, April No. 2, Skiddoo Fraction, Harriet and Diorite were surveyed under Mineral Survey No. 3743, in 1921 by Edward L. Haff, U.S. Mineral Surveyor.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 630, Arizona, dated February 11, 1982.

The directions of all lines were determined by observations on a U.S.C.&G.S. triangulation network, confirmed by altitude observations on the sun, and refer to the true meridian. Distances and angles were measured with a Zeiss SM 4 Total Station instrument.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given within.

The geographic position of the southeast corner of section 9, as determined from a tie made to U.S.C.&G.S triangulation station "ROCK", located in the SW quarter of section 10, is as follows:

The mean magnetic declination is 14° E.

Dependent Resurvey, a Portion of the Subdivisional Lines T 8 N, R 2 E, Gila and Salt River Mer., Arizona

(Reestablishment of the Survey Executed by George F. Rigby, U.S. Surveyor, in 1917)

Beginning at the cor. of secs. 9, 10, 15 and 16, monumented with an iron post, 2 ins. diam., projecting 13 ins. above ground, in a mound of stone, 2½ ft. base, 6 ins. high, with brass cap mkd.

T8N R2E <u>S 9 | S10</u> <u>S16 | S15</u> 1917

CHAINS	Cor. is located 2 lks. S of a barbed wire fence, extends S 80° E and N 80° W.
	From this point U.S.C.&G.S. triangulation station "ROCK", bears N 76°32'21" E, 23.405 chs. dist., monumented with a stan. bronze tablet, firmly cemented into bedrock, with top mkd. ROCK 1924, and a triangle.
	N 0°04' W, bet. secs. 9 and 10.
	Over rolling land, through medium undergrowth.
0.30	Wash, drains E.
34.96	Intersect a private survey cor., monumented with a rebar, in. diam., projecting 4 ins. above ground, with plastic cap attached and mkd. COLLINS LS 7335. This monument was set by Gary B. Collins, L.S. No. 7335, AZ., as shown on a plat on Page 25 of Book 1 of Land Surveys on file with the Records of Yavapai County, Prescott, Arizona, and is not utilized in the course of this survey.
	Monument is located in a fence line, extends S 80° E and N 70° W.
37•27	Cor. of chain link, fence bears East, .6 lk. dist., fence extends N and E.
39.88	The ¼ sec. cor. of secs. 9 and 10, monumented with an iron post, 1 in. diam., projecting 12 ins. above ground, with brass cap mkd.
	S 9   S10 1917
	from which
	A cor. fence post, bears South, 0.5 lks. dist., chain link fence extends E and S.
	A cor. fence post, bears North, 8.3 lks. dist., barbed wire fence extends N, S 15° W and S 60° W.
	A mound of stone, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, is W of cor.
	N 0°08' W, beginning new measurement.
	Over rolling land, through medium undergrowth.
19.96	Point for the N 1/16 sec. cor. of secs. 9 and 10.
	Set an aluminum post, 28 ins. long, 1 in. diam., 14 ins. in the ground, in a mound of stone, 3½ ft. base, to top, with brass cap mkd.
	T8N R2E N 1/16 S 9   S10 1982
	Cor. is located on a NE slope.

Barbed wire fence, bears E and N 85° W.

29.91

CHAINS	
29.94	Point for the N N 1/64 sec. cor. of secs. 9 and 10.
	Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	N N 1/64 S 9   S10 1982
	from which
	A nail in the base of a gate post, 10 ins. diam., bears S $81\frac{1}{2}$ ° E, 26.7 lks. dist.
	A nail in the SW cor. of a post support, 8 x 6 ins., bears S 50° W, 3.5 lks. dist.
	Cor. is located 14 lks. W of a track road, bears N 10° E and S 10° W.
39•92	Cor. of secs. 3, 4, 9 and 10, monumented with a malapais stone, 19 x 10 x 8 ins., projecting 1 in. above ground, mkd. with 3 notches on the E edge, 5 notches on the S edge, and X on top.
	from which an original bearing tree
	A mesquite, 5 ins. diam., bears S 63° W, 152 lks. dist., with faint illegible scribe marks. (Record: S 60½° W)
	At the cor. point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T8N R2E <u>S 4   S 3</u> S 9   S10 1982
	Deposit original stone in mound.
	Drove steel fence post alongside the cor.
	From the cor. of secs. 9, 10, 15 and 16, heretofore described.
	N 89°44' W, bet. secs. 9 and 16.
	Over rolling land, through medium undergrowth.
0.30	Wash, drains N 45° E.
39.81	The $\frac{1}{4}$ sec. cor. of secs. 9 and 16, monumented with an iron post, 1 in. diam., projecting $2\frac{1}{2}$ ft. above ground, in a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, with brass cap mkd.
	1917
1	<u> </u>

_		
	CHAINS	A mound of stone, 4 ft. base, 3 ft. high, is W of cor.
		N 89°43' W, beginning new measurement.
	0.85	Ridge, bears N 10° E and S 10° W.
	6.80	Center of Agua Fria River, 40 lks. wide, course S.
	40.21	The cor. of secs. 8, 9, 16 and 17, monumented with an iron post, 2 ins. diam., projecting 14 ins. above ground, with brass cap mkd.
		T8N R2E S 8   S 9 S17   S16 1917
		Cor. is located on a steep S 72° E slope.
		N 0°02' W, bet. secs. 8 and 9.
		Over rolling land, through medium undergrowth.
	39•94	The 4 sec. cor. of secs. 8 and 9, monumented with an iron post, 1 in. diam., projecting 10 ins. above ground, with brass cap mkd.
		S 8   S 9 1917
		A mound of stone, 3 ft. base, 2 ft. high, is W of cor.
		Cor. is located on a steep E slope.
		N 0°08' W, beginning new measurement.
	39•58	The cor. of secs. 4 and 9 only, originally established by Alfred N. Oliver in 1910 as the cor. of secs. 4, 5, 8 and 9, and altered by George F. Rigby in 1917 to refer to secs. 4 and 9 only, monumented with a slate stone, 20 x 11 x 8 ins., projecting 6 ins. above ground, mkd. with 5 grooves on the S face and 4 grooves on the E face.
		from which bearing trees mkd. by Alfred N. Oliver in 1910
		The base of a fallen palo verde stump, 4 ins. diam., bears N 24° E, 79 lks. dist., no marks visible in a rotted blaze.
-		An ironwood, 5 ins. diam., bears S 224° W, 80 lks. dist.
		An ironwood stump, 8 ft. high, 8 ins. diam., bears N 34° W, 102 lks. dist., with blaze mkd. T8N R2E S5 BT. (Record: 105 lks. dist.)
		A mound of stone, 2 ft. base, 2 ft. high, is W of cor.
		At the cor. point
-		

CHAINS

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 16 ins. in the ground, in a mound of stone,  $3\frac{1}{2}$  ft. base, to top, with brass cap mkd.

Deposit the original stone in the mound of stone.

Cor. is located on a SW slope.

From this point the cor. of secs. 5 and 8 only, set by George F. Rigby, in 1917, bears N 1°12' W, 44 lks. dist., monumented with an iron post, 2 ins. diam., projecting 12 ins. above ground, with brass cap mkd.

T8N S5 | S8 | R2E 1917

Brass cap was remarked to read

T8N R2E 55 | S<sup>1</sup> 1982 1917

n diga kachambi makasabisabi, bi mai mili akam ili gasakabiy kacha kan ka ka

Reestablishment of the Survey Executed by Alfred N. Oliver, U.S. Deputy Surveyor, in 1910

From the cor. of secs. 3, 4, 9 and 10, heretofore described.

N 89°57' W, bet. secs. 4 and 9.

Over rolling land, through medium to dense undergrowth.

7.06

Cor. No. 1, M.S. No. 3743 April lode, monumented with a granite stone,  $22 \times 11 \times 8$  ins., projecting 10 ins. above ground, mkd. A-1-3743 on W face, and X on top. This cor. is now also designated as Cor. 2, Lot 1, sec. 9.

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.

Deposit the original stone in mound.

Drove steel fence post alongside the cor.

_	<del></del>	
	CHAINS	
	11.63	The North End Center of M.S. 3743 April lode, monumented with a granite stone, 12 x 8 x 12 ins. above ground, mkd. N END C A-3743 with a mound of stone, 4 ft. base, 1 ft. high, NW.
	12.01	A private survey cor., monumented with a rebar, \( \frac{5}{8} \) in. diam., with plastic cap mkd. COLLINS L S 7335, this monument is not utilized in the course of this survey.
	16.19	Cor. No. 4, M.S. 3743 April lode, identical with Cor. No. 4, April No. 1 lode of the same survey, monumented with a granite stone, 14 x 12 x 12 ins. above ground, mkd. A-4-3743 on the E face, A 1-4-3743 on W face, and an X on top.
		from which
		A power pole, bears N 20° E, 7.5 lks. dist., lines extend S and N 30° W.
		A cor. fence post, an open end iron pipe, 4 ins. diam., 8 ft. high, bears S 30° W, 2.1 lks. dist., fence extends S and W.
		Cor. is located on a spur, slopes NW.
	20.02	The E 1/16 sec. cor. of secs. 4 and 9, identical with Cor. No. 3, M.S. 3743 April No. 1 lode, monumented with a granite stone, 24 x 14 x 8 ins., projecting 10 ins. above ground, in a mound of stone, 2 ft. base, 10 ins. high, mkd. A 1-3 3743 on W face, ½ on E face, and X on top. A scattered mound of stone, bears NW, 6 lks. dist. from the cor. This position is accepted as a careful and faithful determination of the position of the cor.
		At the cor. point
		Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.
		T8N R2E M S   E 1/16 3743   S4 A NO 1 S9 COR 3 1982
		from which
		A cor. fence post, an open end iron pipe, 4 ins. diam., 7 ft. high, bears N 85° E, 1.8 lks. dist. Fence extends E and N.
		Deposit original stone alongside aluminum post.
		Cor. is located on a NW slope.
		N 89°57' W, beginning new measurement.
	15.30	Center of Agua Fria River, 1 ch. wide, course S 20° W.
	20.02	The $\frac{1}{4}$ sec. cor. of secs. 4 and 9, monumented with a quartz stone, 20 x 12 x 8 ins., firmly set and projecting 8 ins. above ground, mkd. $\frac{1}{4}$ on N face.
		l I

CHAINS	At the cor. point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap mkd.
	T8N R2E
	Deposit the original stone alongside the cor.
	Cor. is located on a steep E slope.
	N 89°54' W, beginning new measurement.
1.83	Intersect line 4-1, M.S. 3512 Marietta lode, at a point from which Cor. No. 1 bears S 0°11' E, 1.59 chs. dist., hereinafter described.
36.60	Power line, bears N 24° E and S 24° W.
39•94	The cor. of secs. 4 and 9 only.
	Subdivision of Section 9, T 8 N, R 2 E, Gila and Salt River Mer., Arizona
	From the 1 sec. cor. of secs. 9 and 16.
	N 0°16' W, on the N and S center line of sec. 9.
36.70	Center of the Agua Fria River, 20 lks. wide, course S 60° W.
39•93	Point for the center 4 sec. cor. of sec. 9, at intersection with the E and W center line of sec. 9, is located below the high water level of the Agua Fria River and is impracticable to monument.
	from which
	An iron post, 28 ins. long, 2½ ins. diam., set 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, for a reference monument, bears N 70¾° W, 57.9 lks. dist., with brass cap mkd. T8N R2E RM 38.2 FT C ¼ S9 1982, and an arrow pointing to the cor. point.
	An aluminum post, 28 ins. long, 1 in. diam., set 18 ins. in the ground, in a mound of stone, 2½ ft. base, to top, for a reference monument, bears N 1¾° W, 105.8 lks. dist., with cap mkd. T8N R2E RM 69.8 FT C ¼ S9 1982, and an arrow pointing to the cor. point.
56.20	Intersect line 2-3, M.S. 3743 Diorite lode, at a point from which the witness cor. to Cor. No. 2 bears N 89°58' W, 0.30 chs. dist., hereinafter described.
59•79	Point for the center N 1/16 sec. cor. of sec. 9.

### Subdivision of Section 9, T 8 N, R 2 E, Gila and Salt River Mer., Arizona

_		
	CHAINS	Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, with cap mkd.
		T8N R2E
		C N 1/16   S9
		Ċ 1982
		Raise a mound of stone, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, to W.
		Drove a steel fence post alongside the cor.
		Cor. is located on an E slope.
	78.06	Intersect line 4-1, M.S. 3743 Diorite lode, common with line 1-2, M.S. 3512 Marietta lode, at a point from which Cor. No. 1 of Marietta lode bears N 89°56' W, 1.83 chs. dist.
	79•65	The ‡ cor. of secs. 4 and 9.
		From the $\frac{1}{4}$ sec. cor. of secs. 9 and 10.
		N 89°41' W, on the E and W center line of sec. 9.
	11.99	Intersect line 4-1, M.S. 3743 April No. 2 lode, at a point from which Cor. No. 1 bears S 20°48' E, 0.61 chs. dist., hereinafter described.
	19.80	Wash, drains N.
	19.97	Point for the center E 1/16 sec. cor. of sec. 9.
		Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. in the ground, in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with cap mkd.
		T8N R2E C E 1/16 C S9 1982
		Drove a steel fence post alongside the cor.
		Cor. is located on a spur, slopes N 70° E.
	31.46	Intersect line 2-3, M.S. 3743 Harriet lode, at a point from which Cor. No. 2 bears S 22°01' E, 2.76 chs. dist., hereinafter described.
	36.80	Center of Agua Fria River, 25 lks. wide, course S 20° W.
	39•94	The center 1/4 sec. cor. of sec. 9.
	79•98	The 4 sec. cor. of secs. 8 and 9.
	·	NE 4 of Section 9
		From the center E 1/16 sec. cor. of sec. 9.
		N 0°12' W, on the N and S center line of the NE $^1_{\pi}$ of sec. 9.

### Subdivision of Section 9, T 8 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS	
19.91	Point for the NE 1/16 sec. cor. of sec. 9, at intersection with the E and W center line of the NE4 of sec. 9.
	Set an aluminum post, 28 ins. long, 1 in. diam., 12 ins. in the ground, in a mound of stone, 4 ft. base, to top, with cap mkd.
	T8N R2E NE 1/16 S9 1982
	Cor. is located on a W slope.
39•82	The E 1/16 sec. cor. of secs. 4 and 9.
	From the N 1/16 sec. cor. of secs. 9 and 10.
	N 89°49' W, on the E and W center line of the NE <sup>1</sup> 4 of sec.
5.18	Intersect line 1-2, M.S. 3743 April lode, at a point from which Cor. No. 2 bears S 5°31' E, 2.40 chs. dist., hereinafter described.
20.00	The NE 1/16 sec. cor. of sec. 9.
38.10	Center of Agua Fria River, 1 ch. wide, course S.
40.00	The center N 1/16 sec. cor. of sec. 9.
	Dependent Resurvey of Certain Boundaries of Mineral Surveys in T 8 N, R 2 E, Gila and Salt River Mer., Az.
	Mineral Survey No. 3512  Marietta Lode
	From Cor. No. 4, M.S. 3512 Marietta lode, identical with Cor. No. 3 Buckeye lode, of the same survey, monumented with an open end pipe, 1 <sup>1</sup> / <sub>4</sub> ins. diam., firmly set in solid schist, projecting 10 ins. above ground.
	from which an original bearing tree
	A mesquite stump, 3 ft. high, 3 ins. diam., bears N 15°38' W, 47.3 lks. dist., no marks visible.
	Cor. is located in a wash, 20 lks. wide, drains S 30° E.
	Cor. was not remonumented.
	S 0°11' E, on line 4-1, M.S. 3512 Marietta lode.
21.14	Intersect the line bet. secs. 4 and 9, at a point from which the ‡ sec. cor. of secs. 4 and 9 bears S 89°54' E, 1.83 chs. dist., thence in sec. 9.
22.73	Cor. No. 1, M.S. 3512 Marietta lode, on line 4-1, M.S. 3743 Diorite lode, monumented with a wood post, 4 ft. long, 4 ins. sq., set in a mound of stone, 4 ft. base, 15 ins. high.

CHAINS	At the cor. point
	Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. in the ground, in a mound of stone, 4 ft. base, to top, with cap mkd.
	M-COR 1 M S 3512
	Deposit the wood post alongside mound of stone.
	Drove steel fence post alongside the cor.
	Cor. is located on a N 80° E slope.
	er kaj gija in likerko er er sil erkiĝas relato er astrojas. Transporta
	Thence
	S 89°56' E, on line 1-2, M.S. 3512 Marietta lode, common with a portion of line 4-1, M.S. 3743 Diorite lode.
1.83	Intersect the N and S center line of sec. 9, at a point from which the $\frac{1}{4}$ sec. cor. of secs. 4 and 9 bears N 0°16' W, 1.59 chs. dist.
2.49	Point for Cor. No. 1, M.S. 3743 Diorite lode, at proportionate distance; there is no remaining evidence of the original cor. Cor. was not remonumented.
9.09	Point for Cor. No. 2, M.S. 3512 Marietta lode, determined from an original bearing rock
	A stone, 24 X 14 X 8 ins. above ground, mkd. BR 2-ML 3512 X on S face, bears N 26°31' W, 43.5 lks. dist.
	Cor. point falls on mine tailings and is impracticable to monument.
	Mineral Survey No. 3743
	Diorite Lode
	From the point for Cor. No. 1, M.S. 3743 Diorite lode, hereinbefore described.
	N 89°56' W, on line 1-4, M.S. 3743 Diorite lode, identical with a portion of line 2-1, M.S. 3512 Marietta lode.
0.66	Intersect the N and S center line of sec. 9, at a point from which the 4 sec. cor. of secs. 4 and 9, bears N 0°16' W, 1.59 chs. dist.
2.49	Cor. No. 1, M.S. 3512 Marietta lode, hereinbefore described.
	S 89°57' W, beginning new measurement.
2.02	The North End Center of M.S. 3743 Diorite lode, monumented with a mound of stone, 3 ft. base, 1 ft. high, with post hole in center.

CHAINS	At the cor. point
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.
	S9 D-N END CEN M S 3743 1982
	Cor. is located 8 lks. S of a small wash, drains N 50° E.
	S 89°57' W, beginning new measurement.
3.70	Dirt road, 18 lks. wide, bears N 20° E and S 22° W.
4.57	Cor. No. 4, M.S. 3743 Diorite lode, monumented with a mound of stone, 3 ft. base, 10 ins. high.
	At the cor. point
	Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. in the ground, in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with cap mkd.
	S9 D-COR 4 M S 3743 1982
	Drove steel fence post alongside the cor.
	Cor. is located on a N 45° E slope.
	Thence
	S 5°33' E, on line 4-3, M.S. 3743 Diorite lode.
21.96	Point for Cor. No. 3, M.S. 3743 Diorite lode, determined from the original bearing trees
	A mesquite stump, 6 ft. high, 8 ins. diam., bears N 54° E, 39.0 lks. dist., mkd. 3743 and other faint scribing.
	A mesquite, 6 ins. diam., bears S 15° E, 67.5 lks. dist., mkd. X BT-D-3-3743.
	Cor. point is located in a wash, 48 lks. wide, drains S 32°E, and is impracticable to monument.
	from which
	An aluminum post, 28 ins. long, 1 in. diam., set 20 ins. in the ground, for a reference monument, bears S 73° W, 34.2 lks. dist., with cap mkd. D. COR 3 M.S. 3743 RM 22.55 FT 1982, and an arrow pointing to the cor.

CHAINS	An aluminum post, 28 ins. long, 1 in. diam., set 22 ins. into a rock crack, for a reference monument, bears N 5° W, 57.6 lks. dist., with cap mkd. D.3 COR 3 M.S. 3743 RM 38.01 FT 1982, and an arrow pointing to the cor.
	Thence
	S 89°58' E, on line 3-2, M.S. 3743 Diorite lode.
6.10	Point selected for the witness cor. to Cor. No. 2, M.S. 3743 Diorite lode.
	Set an aluminum post, 28 ins. long, 1 in. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.
	W C D - COR 2 M S 3743
	Drove a steel fence post alongside the cor.
	Cor. is located on a spur, slopes S 45° E.
6.18	Point for the original witness cor. to No. 2, M.S. 3743 Diorite lode, at proportionate dist., there is no remaining evidence of the original cor. Cor. point falls on a steep rock slide where it is impracticable to monument.
6.40	Intersect the N and S center line of sec. 9, at a point from which the center N 1/16 sec. cor. bears N 0°16' W, 3.59 chs. dist.
8.37	Intersect line 2-3, M.S. 3743 Harriet lode, at a point from which the true point for Cor. No. 3, M.S. 3743 Harriet lode, bears N 22°01' W, 2.38 chs. dist., hereinafter described.
9.09	Point for Cor. No. 2, M.S. 3743 Diorite lode, at proportionate dist., falls in the flood plain of the Agua Fria River, impracticable to monument.
	Thence
	N 5°35' W, on line 2-1, M.S. 3743 Diorite lode.
	Intersect the true point for Cor. No. 4, M.S. 3512 Southeast Extension of Marietta lode, not monumented, on line 3-4, M.S. 3743 Harriet lode, at a point from which the witness cor. to Cor. No. 3, bears N 84°16' E, 2.19 chs. dist., hereinafter described.
	Continue distance on a line common with line 4-1, M.S. 3512 Southeast Extension of Marietta lode.
21.96	Cor. No. 1, M.S. 3743 Diorite lode, and place of begin- ning.


CHAINS

#### Mineral Survey No. 3743 Harriet Lode

From Cor. No. 4, M.S. 3743 Harriet lode, identical with Cor. No. 3, M.S. 3743 April No. 2 lode, on line 3-4, M.S. 3512 Southeast Extension of Marietta Lode, monumented with a mound of stone,  $2\frac{1}{2}$  ft. base, 8 ins. high.

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.



Drove a steel fence post alongside the cor.

Cor. is located on a slight W slope.

S 84°16' W, on line 4-3, M.S. 3743 Harriet lode, common with a portion of line 3-4, M.S. 3512 Southeast Extension of Marietta lode.

The North End Center of M.S. 3743 Harriet lode, monumented with a granite stone, 10 x 7 x 12 ins. above ground, in a mound of stone, 2 ft. base, 10 ins. high, mkd. N END C H-3743 on S face, and X on top, and with another mound of stone, 3 ft. base, 3 ft. high, N of cor.

Cor. was not remonumented.

S 84°16' W, beginning new measurement.

1.14 The witness cor. to Cor. No. 3, M.S. 3743 Harriet lode, identical with the witness cor. to Cor. No. 4, M.S. 3512 Southeast Extension of Marietta lode, monumented with a mound of stone, 3 ft. base, 15 ins. high.

from which the original bearing rock

A schist outcropping, 5 x 3 x 5 ft. above ground, bears S 80° E, 23.1 lks. dist., mkd. BR W C 4 SE-E-M X 3512 on N face.

from which the original bearing tree

A mesquite stump, 12 ins. diam., 3 ft. high, bears N 53°13' W, 13.6 lks. dist., with blaze, no scribing visible.

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, 4 ft. base, to top, with cap mkd.

	CHAINS	W C SE E M M S 3512 COR 4			
		М S 3743 1982			
		Cor. is located at the base of the left outer bank of the Agua Fria River.			
	3•33	True point for Cor. No. 4, M.S. 3512 Southeast Extension of Marietta lode, on line 1-2, M.S. 3743 Diorite lode, at proportionate dist., in the flood plain of the Agua Fria River, impracticable to monument.			
at record dist., on a projection from 3743 Harriet lode, through the witness		Point for cor. No. 3, M.S. 3743 Harriet lode, determined at record dist., on a projection from Cor. No. 4, M.S. 3743 Harriet lode, through the witness cor. to this corpoint, falls in the flood plain of the Agua Fria River, impracticable to monument.			
		Thence			
		S 22°01' E, on line 3-2, M.S. 3743 Harriet lode.			
	2.38	Intersect line 2-3, M.S. 3743 Diorite lode, at a point from which the point for Cor. No. 2, M.S. 3743 Diorite lode, bears S 89°58' E, 0.72 chs. dist.			
	19•98	Intersect the E and W center line of sec. 9, at a point from which the center ½ sec. cor. of sec. 9, bears N 89°41' W, 8.48 chs. dist.			
	22.74 Cor. No. 2, M.S. 3743 Harriet lode, monumented with a diorite stone, 11 x 8 x 10 ins. above ground, in a mon of stone, 3 ft. base, 3 ft. high, mkd. H 2- on SE face 3743 on NE face, and X on top.				
		Cor. is located on a spur, slopes N 20° E.			
	Cor. was not remonumented.				
		Thence			
N 84°14' E, on line 2-1, M		N 84°14' E, on line 2-1, M.S. 3743 Harriet lode.			
	4.73	The South End Center of M.S. 3743 Harriet lode, monumented with a quartzite stone, $12 \times 10 \times 5$ ins. above ground, mkd. H. SE 3743, and with a mound of stone, $2\frac{1}{2}$ ft. base, 3 ft. high, S of cor.			
		Cor. was not remonumented.			
		N 84°14' E, beginning new measurement.			
	4.74	Cor. No. 1, M.S. 3743 Harriet lode, identical with Cor. No. 2, M.S. 3743 April No. 2 lode, monumented with a faint mound of earth and stone.			

CHAINS

Set an aluminum post, 28 ins. long, 1 in. diam., 15 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.

Drove a steel fence post alongside the cor.

Cor. is located on a ridge, bears E and N 50° W.

#### Mineral Survey No. 3743 April No. 2 Lode

From Cor. No. 2, M.S. 3743 April No. 2 lode, identical with Cor. No. 1, M.S. 3743 Harriet lode, hereinbefore described.

N 84°14' E, on line 2-1, M.S. 3743 April No. 2 lode.

4.74 The South End Center of M.S. 3743 April No. 2 lode, monumented with a diorite stone, 17 x 9 x 14 ins. above ground, mkd. S END C A NO 2-3743 on N face, and X on top, and with a scattered mound of stone S of cor.

Cor. was not remonumented.

N 84°14' E, beginning new measurement.

4.54 Cor. No. 1, M.S. 3743 April No. 2 lode, monumented with a diorite stone, 18 x 10 x 20 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, mkd. A NO 2 1-3743 on W face, and X on top, with another mound of stone, 3 ft. base, 1½ ft. high, SE of cor.

Cor. is located on a S slope.

Cor. was not remonumented.

Thence

N 20°48' W, on line 1-4, M.S. 3743 April No. 2 lode.

STATE OF STATE OF STATE

- O.61 Intersect the E and W center line of sec. 9, at a point from which the center E 1/16 sec. cor. of sec. 9, bears N 89°41' W, 7.98 chs. dist.
- 21.82 Intersect line 5-6, M.S. 3743 April No. 1 lode, at a point from which the South End Center, M.S. 3743 April No. 1 lode, bears N 89°04' E, 0.63 chs. dist., hereinafter described.
- Intersect the E and W center line of the NE<sup>1</sup> of sec. 9, at a point from which the NE 1/16 sec. cor. of sec. 9 bears N 89°49' W, 0.44 chs. dist., hereinbefore described.

CHAINS					
22.60	Cor. No. 4, M.S. 3743 April No. 2 lode, monumented with a granite stone, 16 x 14 x 18 ins. above ground, mkd. A No. 2-4-3743 on W face, and X on top, with a wood post, 4 x 4 ins. wide, 4 ft. long, in a mound of stone, 2½ ft. base, 12 ins. high, alongside, and another mound of stone, 3 ft. base, 4 ft. high, bears S 45° E, 7.6 lks. dist. from the cor.				
	Cor. is located on a W slope.				
	Cor. was not remonumented.				
	Mineral Survey No. 3743 April No. 1 Lode				
From Cor. No. 6, M.S. 3743 April No. 1 lode, ident with Cor. No. 3, M.S. 3743 Skiddoo Fraction lode, mented with a rotted wood post, projecting 2 ins. ground, in a mound of stone, 2½ ft. base, 10 ins.					
	At the cor. point				
	Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with cap mkd.				
	M S 3743 S F \ A NO 1 COR 3 \ COR 6 S 9 1982				
Drove a steel fence post alongside the cor.					
	Cor. is located on a S 70° W slope.				
	N 89°04' E, on line 6-5, M.S. 3743 April No. 1 lode.				
3.40	Intersect the N and S center line of the NE <sup>1</sup> <sub>4</sub> of sec. 9, at a point from which the NE 1/16 sec. cor. bears N 0°12' W, 0.23 chs. dist., hereinbefore described.				
3•92	Intersect line 4-1, M.S. 3743 April No. 2 lode, at a point from which Cor. 4 bears N 20°48' W, .78 chs. dist., hereinbefore described.				
4•55	The South End Center of M.S. 3743 April No. 1 lode, monumented with a stone, 11 x 6 x 11 ins. above ground, mkd. S END C APR No. 1 on the E face, 3743 on the W face, and X on top, with a mound of stone, 3 ft. base, 3 ft. high, 6 lks. S of cor.				
	Cor. is located on a spur, slopes S 70° W.				
	Cor. was not remonumented.				
	N 89°04' E, beginning new measurement.				
4.53	Cor. No. 5, M.S. 3743 April No. 1 lode, and on line 4-3, M.S. 3743 April lode, monumented with a stone, 15 x 9 x 10 ins. above ground, mkd. A No. 1-5 3743 on the W face, and X on top. A 4 x 4 in. wood stump, in a mound of stone, 3½ ft. base, 18 ins. high, is W of cor.				

CHAINS Cor. is located on a steep S 20° E slope, and 2½ lks. E of a fence line, extends N and S. Cor. is not remonumented. Mineral Survey No. 3743 April Iode From Cor. No. 5, M.S. 3743 April No. 1 lode, and on line 4-3, M.S. 3743 April lode, hereinbefore described. S 5°30' E, on line 4-3, M.S. 3743 April lode. 2.41 Cor. No. 3, M.S. 3743 April lode, monumented with a stone, 14 x 6 x 5 ins. above ground, mkd. A-3-3743 on the E face, and X on top, with a mound of stone, 3 ft. base, 2½ ft. high, N of cor. from which A fence cor, iron pipe, 7 ft. high, 4 ins. diam., bears N, 6.1 lks. dist., barbed wire fence extends E and N. Cor. is located on a S 45° W slope. Cor. was not remonumented. Thence S 89°59' E, on line 3-2, M.S. 3743 April lode. The South End Center of M.S. 3743 April lode, monumented 4.57 with a granite stone, 11 x 7 x 8 ins. above ground, mkd. S END C-A-3743 on N face, and X on top, in a mound of stone, 2 ft. base, 5 ins. high. Cor. is located in a barbed wire fence line, extends E and W. Cor. was not remonumented. S 89°59' E, beginning new measurement. Cor. No. 2, M.S. 3743 April lode, monumented with a granite stone, 8 x 7 x 4 ins. above ground, mkd. A-2-3743 on the W face, and X on top. A wood post, 4 x 4 ins.,  $3\frac{1}{2}$ 4.57 ft. high, in a mound of stone, 3 ft. base, 1½ ft. high, bears S 40° E, 6 lks. from the cor. Another mound of stone, 3 ft. base, 2½ ft. high, bears N 50° E, 5 lks. from the cor. from which A cor. fence post, an iron pipe, 7 ft. high, 4 ins. diam., bears N 58° E, 1.2 lks. dist., barbed wire fence extends W and N 2° W. Cor. is located near the top of a flat knoll. Cor. was not remonumented.

<b>-</b>				
CHAINS	Thence			
	N 5°31' W, on line 2-1, M.S. 3743 April lode.			
2.40	Intersect the E and W center line of the NE4 of sec. 9, at a point from which the N 1/16 sec. cor. of secs. 9 and 10, bears S 89°49' E, 5.18 chs. dist., hereinbefore described.			
12.41	Cor. 3, lot 1, sec. 9, at intersection with the E and W center line of the NE <sup>1</sup> <sub>4</sub> of the NE <sup>1</sup> <sub>4</sub> of sec. 9, hereinafter described.			
22.43	Cor. No. 1, M.S. 3743 April lode, identical with cor. lot 1, sec. 9, and on the line bet. secs. 4 and 9, her inbefore described.			
Survey of Lot 1 in Section 9, T 8 N, R 2 E, Gila and Salt River Mer., Arizona				
	From cor. 1, lot 1, sec. 9, identical with the cor. of secs. 3, 4, 9 and 10, hereinbefore described.			
	N 89°57' W, on line 1-2, lot 1, sec. 9, identical with a portion of the line bet. secs. 4 and 9.			
7.06 Cor. 2, lot 1, sec. 9, identical with Cor. No. 1, M.S. 3743 April lode, hereinbefore described.				
	S 5°31' E, on line 2-3, lot 1, sec. 9, identical with a portion of line 1-2, M.S. 3743 April lode.			
10.02	Cor. 3, lot 1, sec. 9, at intersection with the calculated E and W center line of the NE4 of the NE4 of sec. 9.			
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top with brass cap mkd.				
	T8N R2E  MS			
	from which			
A cor. fence post, an open end iron pipe, 7 ft. high, 4 ins. diam., bears South, 7 lks. dist., 4 strand barbed wire fence extends S 84° E and S.				
	endagnaga kanguna dipenah dibengan pendagan kanguna mengangan dibengan kanggan pendagan penda			
	S 89°53' E, on line 3-4, lot 1, sec. 9, identical with a portion of the E and W center line of the NE <sup>1</sup> of the NE <sup>1</sup> of sec. 9.			
0.50	Wash, 5 lks. wide, drains N.			
6.12	Cor. 4, lot 1, sec. 9, identical with the N N 1/64 sec. cor. of secs. 9 and 10, hereinbefore described.			
	N 0°08' W, on line 4-1, lot 1, sec. 9, identical with a portion of the line bet. secs. 9 and 10.			

## Survey of Lot 1 in Section 9, T 8 N, R 2 E, Gila and Salt River Mer., Arizona

T		
9.98	Cor. 1, lot 1, sec. 9, identical with the cor. of secs. 3, 4, 9 and 10, and the place of beginning, hereinbefore	
	described.	
	er andrese en de antitente de andrestant propuertan en que reconstrue que en que que en expanse que no espa-	
	GENERAL DESCRIPTION	
	The land encompassed in this survey is located immediately west of Rock Springs, Arizona. The elevation ranges between 1900 to 2400 ft. above sea level.	
	The terrain is rugged and contains palo verde, creosote, mesquite and various cacti.	
	The Agua Fria River winds southerly through the center of the sec. Seasonal tributaries in the sec. drain into the river. Mining activity has occurred throughout the sec.	
	The mean magnetic declination is 14° E.	
	entendentale esta nel parase entende a un troper a respectar entende estalas entendente, se un como per conse	

Form 9600-11 (August 1979)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

#### FIELD ASSISTANTS

NAMES	CAPACITY
Kevin L. Miller	Surveying Technician
Neil A. Hemminger	Surveying Technician

#### CERTIFICATE OF SURVEY

(I) (₩¥), Dennis K. McKay, Cadastral Surveyor

. HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 11th day

of February , 1982 , (I)XWA) have dependently resurveyed a portion of the subdivisional lines and certain mining claims and have surveyed the subdivisions of section 9 and the metes-and-bounds survey of lot 1, section 9, in Township 8 North, Range 2 East,

of the Gila and Salt River Meridian, in the State of Arizona , which are represented in the foregoing field notes as having been executed by (me), (me) and under (my) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

(Date)

DEC 0 9 1983

(Cadastral Surveyor)

(Cadastral Surveyor)

#### CERTIFICATE OF APPROVAL

The foregoing field notes of the dependent resurvey of a portion of the sub-divisional lines and certain mining claims and have surveyed the sub-divisions of section 9 and the metes-and-bounds survey of lot 1, section 9, in Township 8 North, Range 2 East, of the Gila and Salt River Meridian, Arizona

executed by Dennis K. McKay, Cadastral Surveyor

(Date)

having been critically examined and found correct, are hereby approved.

DEC 1 2 1983

(Date)

(Date)

(Date)

(Chief Cadastral Surveyor of Arizona

CERTIFICATE OF TRANSCRIPT

(CERTIFY That the foregoing transcript of the field notes of the above-described surveys in

T. 8 N., R. 2 E., G&SRM, Arizona , is a true copy of the original field notes.