ORIGINAL

1

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF			
THE SIXTH STANDARD PARALLEL NORTH THROUGH RANGE 19 WEST,			
A PORTION OF THE FIFTH GUIDE MERIDIAN WEST THROUGH TOWNSHIP 24 NORTH			
AND A PORTION OF THE SUBDIVISIONAL LINES,			
AND			
THE METES-AND-BOUNDS SURVEY			
OF THE MOUNT TIPTON WILDERNESS AREA BOUNDARY,			
IN TOWNSHIP 24 NORTH, RANGE 19 WEST			
Of the Gila and Salt River Meridian,			
In the State of Arizona			
EXECUTED BY			
Joe R. Salazar, Cadastral Surveyor			

Under Special Instructions dated <u>April 8, 1994</u>, and approved <u>April 8, 1994</u>, which provided for the surveys included under Group Number $\overline{770}$ and assignment instructions dated <u>January 11, 1995</u>

Survey commenced <u>January 19, 1995</u> Survey completed <u>February 2, 1995</u>

INDEX DIAGRAM

TOWNSHIP	24 NORTH	. RANGE	19 WEST ,

					4
6	5	4	3	2 7	7 1 5
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Metes-and-Bounds Survey of MTWA

pp. 9-14

T. 24 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the Sixth Standard Parallel North through Range 19 West, a portion of the Fifth Guide Meridian West through Township 24 North and a portion of the subdivisional lines, and the metesand-bounds survey of the Mount Tipton Wilderness Area Boundary, in Township 24 North, Range 19 West, Gila and Salt River Meridian, Arizona.

The Sixth Standard Parallel North and the Fifth Guide Meridian West were surveyed by C. Burton Foster in 1874. The Sixth Standard Parallel North was independently resurveyed by H.G. Bardsley and Royston C. Durnford in 1915. The Fifth Guide Meridian West was resurveyed by Hugo Price in 1916. The subdivisional lines were surveyed by Guy H. Richardson and Hugo Price in 1916.

The survey was executed in accordance with the specifications as set forth in the <u>Manual of Surveying Instructions</u>, 1973, and the Special Instructions dated April 8, 1994, for Group No. 770, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of all lines were determined by direct hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with a Lietz Set 2A total station instrument.

The geographic position of the 1/4 sec. cor. of sec. 12 only, on the E. bdy. of the Tp., as determined from a tie made to U.S. Geological Survey triangulation station "Putman 1958", is as follows:

Latitude: 35°29'02.96" N. Longitude: 114°15'12.79" W. NAD27

The mean magnetic declination, as taken from the 1985 magnetic declination map published by U.S. Geological Survey, is 15° E.

Dependent Resurvey of a Portion of the 6th. Stan. Par. N. through R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	Restoring the resurvey executed by H. G. Bardsley and Royston C. Durnford, in 1915
	Beginning at the stan. cor. of Tps. 25 N., Rs. 18 and 19 W., monumented with an iron post, 3 ins. diam., firmly set, projecting 16 ins. above ground, with a mound of stone to the N., 4 ft. base, 3 ft. high, with brass cap mkd. T25N R19W R18W S36 S31 SC 1995 1915, as described in the field notes of the dependent resurvey of a portion of the 6th Stan. Par. N. through R. 18 W., T. 25 N., R. 18 W., executed concurrently under this same group.
	S. 89°53' W., on the S. bdy. of sec. 36, T. 25 N., R. 19 W., on the 6th Stan. Par. N., along the Mount Tipton Wilderness Area Bdy.
	Over broken terrain.
31.72	Point for the 1/4 sec. cor. of sec. 1 only, T. 24 N., R. 19 W., hereinafter described.
39.97	The stan. 1/4 sec. cor. of sec. 36, T. 25 N., R. 19 W., monumented with an iron post, 1 in. diam., firmly set, projecting 17 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, N. of cor., with brass cap mkd. SC 1/4 S36 1915.
	Add marks T25N R19W 1995 to the brass cap.
	S. 89°57′ W., beginning new measurement.
	Over broken terrain.
31.76	Point for the closing cor. of secs. 1 and 2, hereinafter described.
	Leave the Mount Tipton Wilderness Area Bdy.
39.95	The stan. cor. of secs. 35 and 36, T. 25 N., R. 18 W., monumented with an iron post, 3 ins. diam, firmly set, projecting 11 ins. above ground, with a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, to the N., with brass cap mkd. SC T25N R19W S35 S36 1915.
	Add the marks 1995 to the brass cap.

Dependent Resurvey of a Portion of the 5th Guide Mer. W. through T. 24 N., Gila and Salt River Meridian, Arizona ${\sf Constant}$

CHAINS	
	Restoring the resurvey executed by Hugo Price, in 1916
	From the 1/4 sec. cor. of sec. 12 only, on the E. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, with a mound of stone, 3 ft. base, 3 ft. high, to the W., with brass cap mkd. S12 1/4 S7 1916.
	Add the marks 1995 to the brass cap.
	From this cor. point, U. S. Geological Survey triangulation station "PUTNAM 1958", with published latitude of 35°28′50.155" N. and longitude of 114°15′42.626" W., NAD 27, bears S. 62°19′ W., 42.23 chs. dist., monumented with a standard brass disk, 4 ins. diam., firmly set in drill hole on rock outcrop, 12x9x3 ins. above ground, with brass disk mkd. PUTNAM 1958 and a triangle.
	N. 0°02' E., on the E. bdy. of sec. 12.
	Descend, over N. slope of ridge.
6.50	End descent, enter nearly level ground.
37.71	The closing cor. of secs. 6 and 7, T. 24 N., R. 18 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 15 ins. above ground, with a mound of stone, 2 1/2 ft. base, 1/2 ft. high, to the E., with brass cap mkd. T24N R19W R18W S1 S6 S12 S7 1916.
	Add the marks 1995 to the brass cap.
	Thence along the Mount Tipton Wilderness Area Bdy.
40.28	The cor. of secs. 1 and 12 only, on the E. bdy. of the Tp., monumented with an iron post, 3 ins. diam, firmly set, projecting 14 ins. above the ground, with a mound of stone, 2 ft. base, 2 ft. high, to the N., with brass cap mkd. T24N R19W S1 S12 1916.
ļ	Add the marks 1995 to the brass cap.
	Leave the Mount Tipton Wilderness Area Bdy.
	N. O°O2' E., on the E. bdy. of sec. 1.
	Over nearly level ground.
28.37	Point for AP 7, sec. 1, on the Mount Tipton Wilderness Area Bdy., hereinafter described.
	Display 1097) USDI DI M

Dependent Resurvey of a Portion of the 5th Guide Mer. W. through T. 24 N., Gila and Salt River Meridian, Arizona

CHAINS		
29.41	Point for AP 6, sec. 1, on the Mount Tipton Wilderness Area Bdy., hereinafter described.	
39.99	The 1/4 sec. cor. of sec. 1 only, monumented with an iron post, 1 in. diam., firmly set, projecting 21 ins. above ground, with brass cap mkd. T24N R19W S1 1/4 1916, with a mound of stone 2 1/2 ft. base, 1/2 ft. high W. of cor.	
	Add the marks 1995 to the brass cap.	
	N. O°O5' W., beginning new measurement.	
22.04	Intersect the 6th Stan. Par. N., point for the closing cor. of Tps. 24 N., Rs. 18 and 19 W.	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.	
	T25N R18W S31	
	S1 S6 R19W R18W CC T24N 1995	
	Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.	
	From this cor. point, the 1916 closing cor. of Tps. 24 N., Rs. 18 and 19 W., monumented with an iron post 3 ins. diam., firmly set, projecting 13 ins. above ground, in a mound of stone 5 ft. base to top, with brass cap mkd. T25N R18W S31 S36 CC S1 S6 R19W R18W 1916, bears, N. 0°05′ W., O.O3 ch. dist.	
	Add the marks AM and 1995 to the brass cap and bury the iron post 6 ins. below the ground.	
	From this same cor. point, the stan. cor. of Tps. 25 N., Rs. 18 and 19 W., hereinbefore described, bears, N. 89°46′ W., 8.29 chs. dist.	

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 24 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	Restoring the survey executed by Guy P. Richardson and Hugo Price, in 1916 ———————————————————————————————————
	From the cor. of secs. 1 and 12 only, on the E. bdy. of Tp., hereinbefore described.
	N. 89°51' W., bet. secs. 1 and 12, along the Mount Tipton Wilderness Area Bdy.
	Over nearly level ground,
28.23	Point for AP 13, sec. 1, on the Mount Tipton Wilderness Area Bdy., hereinafter described.
	Leave the Mount Tipton Wilderness Area Bdy.
29.38	Point for AP 1, sec. 1, on the Mount Tipton Wilderness Area Bdy., hereinafter described.
	Thence along the Mount Tipton Wilderness Area Bdy.
40.04	The 1/4 sec. cor. of secs. 1 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above ground, with a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, to the W., with brass cap mkd. S1 1/4 S12 1916.
	Add the marks T24N R19W 1995 to the brass cap.
	N. 89°54′ W., beginning new measurement.
39.98	The cor. of secs. 1, 2, 11 and 12, monumented with an iron post, 2 ins. diam., firmly set, projecting 23 ins. above ground, in a mound of stone, 3 ft. base, 1 1/2 ft. high, with brass cap mkd. T24N R19W S2 S1 S11 S12 1916.
	Add the marks 1995 to the brass cap.
	Cor. is located in fence, bears. N. and S.
	N. O°O1' W., bet. secs. 1 and 2, along the Mount Tipton Wilderness Area Bdy.
	Over broken terrain
39.99	The 1/4 sec. cor. of secs. 1 and 2, monumented with an iron post, 1 in. diam., firmly set, projecting 23 ins. above ground, with brass cap mkd. S2 1/4 S1 1916.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 24 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS

Add the marks T24N R19W 1995 to the brass cap.

Cor. is located in fence, bears N. and S.

N. 0°03' W., beginning new measurement.

Over broken terrain

21.80


The original closing cor. of secs. 1 and 2, monumented with an iron post, 2 ins. diam., firmly set, projecting 26 ins. above ground, in a mound of stone, 5 ft. base to top, with brass cap mkd. T25N R19W S36 S35 CC S2 S1 T24N R19W 1916.

Add the marks AM and 1995 to the brass cap and bury the iron post 6 ins. below the ground.

21.82

Intersect the 6th Stan. Par. N., point for the closing cor. of secs. 1 and 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

From this cor. point, the stan. cor. of secs. 35 and 36, T. 25 N., R. 19 W., hereinbefore described, bears S. 89°57′ W., 8.19 chs. dist.

The point for the 1/4 sec. cor. of sec. 1 only, T. 24 N., R. 19 W., is at midpoint on the N. bdy. of sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T25N R19W

1/4 S 1 T24N R19W 1995 Dependent Resurvey of a Portion of the Subdivisional Lines, T. 24 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS

Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 25 N., R. 19 W., hereinbefore described, bears S. 89°53′ W., 8.25 chs. dist.

Metes-and-Bounds Survey of the
Mount Tipton Wilderness Area Boundary,
T. 24 N., R. 19 W., Gila and Salt River Meridian, Arizona

In Section 1

From the point for AP 1, sec. 1, on the line bet. secs. 1 and 12.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 40 ft. W. of track road, bears ENE and WSW.

From this cor. point, the 1/4 sec. cor. of secs. 1 and 12, hereinbefore described, bears N. 89°51′ W., 10.66 chs. dist.

N. 31°45' E., on line 1-2.

5.10 | Point for AP 2, sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS

Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.


Cor. is located 50 ft. N. of track road, bears ENE and WSW.

N. 37°13′ E., on line 2-3.

8.78 P

Point for AP 3, sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.


Cor. is located 40 ft. N. of track road, bears NE and SW.

N. 38°53' E., on line 3-4.

7.40

Point for AP 4, sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 35 ft. N. of track road, bears NE and SW.


N. 48°36' E., on line 4-5.

9.28

Point for AP 5, sec. 1.

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.




Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 45 ft. N. of track road, bears NE and SW.

N. 58°06' E., on line 5-6.

Point for AP 6, sec. 1, on the line bet. secs. 1 and 6, on the E. bdy. of the Tp.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor is located 38 ft. N. of track road, bears NE and SW.

From this cor. point, the 1/4 sec. cor. of sec. 1 only, hereinbefore described, bears N. 0° 02' E., 10.58 chs. dist.

From the point for AP 7, sec. 1, on the line bet. secs. 1 and 6, on the E. bdy. of the Tp.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS

T24N R19W R18W S1 S6 AP7 MTWA 1995

Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.


Cor. is located 30 ft. S. of track road, bears ENE and WSW.

From this cor. point, the cor. of secs. 1 and 12 only, hereinbefore described, bears S. 0° 02′ W., 28.37 chs. dist.

S. 43°46′ W., on line 7-8.

3.01 | Point for AP 8, sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.




Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 37 ft. S. of track road, bears ENE and WSW.

S. 66°25′ W., on line 8-9.

6.10 | Point for AP 9, sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

CHAINS


Cor. is located 36 ft. S. of track road, bears ENE and WSW.

S. 50°24' W., on line 9-10.

8.52

Point for AP 10, sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.


Cor. is located 30 ft. S. of track road, bears ENE and WSW.

S. 40°50′ W., on line 10-11.

9.48

Point for AP 11, sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 40 ft. S. of track road, bears NE and SW.


S. 37°49′ W., on line 11-12.

9.36

Point for AP 12, sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS



Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 35 ft. S. of track road, bears NE and SSW.

S. 29°26' W., on line 12-13.

4.22 | Point for AP 13, sec. 1, on the line bet. secs. 1 and 12.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 45 ft. N. of track road, bears NE and SW.

From this cor. point, the cor. of secs. 1 and 12 only, on the E. bdy. of the Tp., hereinbefore described, bears S. 89° 51′ E., 28.23 chs. dist.

GENERAL DESCRIPTION

This survey is located about 40 miles west of Kingman, Arizona, and 2 miles east of State Highway 93. Access is provided by dirt road off of State Highway 93 at about mile post 44.

T. 24 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS

The elevation ranges from 4500 to 4800 feet above sea level. The terrain consists of low broken ridges, with washes draining predominately westerly, covered with a moderate growth of scrub oak and catclaw brush. The soil is largely sand and gravel.

Description of the Mount Tipton Wilderness Area Bdy., T. 24 N., R. 17 W., Gila and Salt River Meridian, Arizona

The following description is for informational purposes only.

Beginning at the stan. cor. of Tps. 25 N., Rs. 18 and 19 W.

thence S. 89°53′ W., 39.97 chs. dist., on the S. bdy. of sec. 36, T. 25 N., R. 19 W., to the stan. 1/4 sec. cor. of sec. 36; thence S. 89°57′ W., 31.76 chs. dist., on the S. bdy. of sec. 36,

T. 25 N., R. 19 W., to the closing cor. of secs. 1 and 2, T. 24 N., R. 19 W.;

thence S. 0°03' E., 21.82 chs. dist., on the line bet. secs. 1 and 2, to the 1/4 sec. cor. of secs. 1 and 2;

thence S. 0°01' E., 39.99 chs. dist., on the line bet. secs. 1 and 2, to the cor. of secs. 1, 2, 11 and 12;

thence S. 89°54' E., 39.98 chs. dist., on the line bet. secs. 1 and 12, to the 1/4 sec. cor. of secs. 1 and 12;

thence S. 89°51' E., 10.66 chs. dist., on the line bet. secs. 1 and 2, to Angle Point 1, sec. 1;

thence N. 31°45' E., 5.10 chs. dist., to Angle Point 2, sec. 1; thence N. 37°13' E., 8.78 chs. dist., to Angle Point 3, sec. 1;

thence N. $38^{\circ}53'$ E., 7.40 chs. dist., to Angle Point 4, sec. 1;

thence N. 48°36' E., 9.28 chs. dist., to Angle Point 5, sec. 1; thence N. 58°06' E., 11.54 chs. dist., to Angle Point 6, sec. 1,

on the line bet. secs. 1 and 6, on the E. bdy. of the Tp.;

From Angle Point 7, sec. 1, on the line bet. secs. 1 and 6, on the E. bdy. of the Tp.

thence S. 43°46' W., 3.01 chs. dist., to Angle Point 8, sec. 1;

thence S. 66°25' W., 6.10 chs. dist., to Angle Point 9, sec. 1;

thence S. $50^{\circ}24'$ W., 8.52 chs. dist., to Angle Point 10, sec. 1; thence S. $40^{\circ}50'$ W., 9.48 chs. dist., to Angle Point 11, sec. 1;

thence S. 37°49' W., 9.36 chs. dist., to Angle Point 12, sec. 1;

thence S. 29°26′ W., 4.22 chs. dist., to Angle Point 13, sec. 1, on the line bet. secs. 1 and 12.

thence S. 89°51' E., 28.23 chs. dist., on the line bet. secs. 1 and 12, to the cor. of secs. 1 and 12 only, on the E. bdy. of the Tp.

thence S. 0°02' W., 2.57 chs. dist., on the E. bdy. of sec. 12, to the closing cor. of secs. 6 and 7, T. 24 N., R. 18 W.

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Robert J. Lyle	Surveying Technician
Geoffrey A. Graham	Surveying Technician

CERTIFICATE OF SURVEY

I, Joe R. Salazar, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 8th day of April, 1994, I have dependently resurveyed a portion of the Sixth Standard Parallel North through Range 19 West, a portion of the Fifth Guide Meridian West through Township 24 North and a portion of the subdivisional lines, and performed a metes-and-bounds survey of the Mount Tipton Wilderness Area Boundary, in Township 24 North, Range 19 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

BUREAU OF LAND MANAGEMENT Arizona State Office Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the Sixth Standard Parallel North through Range 19 West, a portion of the Fifth Guide Meridian West through Township 24 North and a portion of the subdivisional lines, and the metes-and-bounds survey of the Mount Tipton Wilderness Area Boundary, in Township 24 North, Range 19 East, Gila and Salt River Meridian, Arizona, executed by Joe R. Salazar, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

CERTIFICATE OF APPROVAL

7/28/97

(Date)

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 24 N., R. 19 W., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.

(Date)

(Chief Cadastral Surveyor of Arizona)