ORIGINAL

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE

	DEPENDENT RESURVEY OF
	A PORTION OF THE SUBDIVISIONAL LINES
	AND
	THE METES-AND-BOUNDS SURVEY OF
	THE TABLE TOP WILDERNESS AREA BOUNDARY,
	TOWNSHIP 8 SOUTH, RANGE 3 EAST
Of the	Gila and Salt River Meridian,
In the State of	
-	
	EXECUTED BY
Joe R. Salazar	Cadastral Surveyor

Under Special Instructions dated <u>April 8, 1996</u>, approved <u>April 8, 1996</u>, which provided for the surveys included under Group Number <u>797</u>, and assignment instructions dated <u>January 8, 1997</u>.

Survey Commenced <u>February 19, 1998</u> Survey Completed <u>April 15, 1998</u>

INDEX DIAGRAM

TOWNSHIP 8 SOUTH, RANGE 3 EAST,

		,			
6	5	4	3	2	1
7	6 8	9	10	11	12
18 !	5 17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Metes-and-Bounds Survey of TTWA

Tract 38 Section 17 Section 8 Tract 37 Section 5

pp. 7-13

pp. 13-16

pp. 16-19, 28-33 pp. 19-28

pp. 33-49

T. 8 S., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the subdivisional lines and the metes-and-bounds survey of the Table Top Wilderness Area Boundary, Township 8 South, Range 3 East, Gila and Salt River Meridian, Arizona.

A portion of the north boundary, the south boundary and a portion of the subdivisional lines were surveyed by W. H. Thorn and W. K. Kierulff, in 1915. A portion of the west boundary and a portion of the subdivisional lines were surveyed by Francis E. Joy, in 1934.

The survey was executed in accordance with the specifications as set forth in the <u>Manual of Surveying Instructions</u>, 1973, and the Special Instructions dated April 8, 1996, for Group No. 797, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The distances and directions of all lines were determined by using the Trimble 4400 real time kinematic survey system, and refer to the true meridian.

The geographic position of the cor. of secs. 17, 18, 19 and 20, was determined by NAVSTAR GPS, using the technique of real time kinematic positioning. U.S. Coast and Geodetic Survey triangulation station "TULE 1960", was used as the control station. The coordinates refer to the top of the monument.

Latitude: 32°43′27.54" N. Longitude: 112°05′02.04" W. NAD83 (1992)

The mean magnetic declination of 12 $1/4^{\circ}$ E. was derived from U.S. Geological Survey computer program MAGPOINT, utilizing the Regional Magnetic Field Model for Epoch 1995 for the dates of the survey.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 8 S., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS

Restoring the Survey executed by Francis E. Joy, in 1934

Beginning at the cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 ins. diam, firmly set, projecting 15 ins. above the ground, with brass cap mkd. T8S R3E S18 S17 S19 S20 1915.

Cor. is located in 5 strand barbed wire fence, bears E. and W.

Add the marks 1998 to the brass cap.

From this cor. point, U.S. Coast and Geodetic Survey triangulation station "TULE 1960", with published latitude of 32°49′56.87447" N. and longitude of 112°03′59.09841" W., NAD83 (1992), bears N. 7°46′21" E. (forward bearing), 601.79 chs. dist., monumented with a standard brass disk, 3 ins. diam., incased in concrete, 12 ins. square, 8 ins. high and rounded on top, with top of disk mkd. TULE 1960 and a triangle.

S. 89°59′ W, bet. secs. 18 and 19, along the northerly bdy. of the Papago Indian Reservation.

Over rolling and rocky land, through creosote and cacti.

Along 5 strand barbed wire fence.

14.90 Point for AP 1, Tract 38, on the metes and bounds survey of the Table Top Wilderness Area Bdy.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 14 ins. in the ground to bedrock, in a supporting mound of stone, 2 1/2 ft. base, to top, with aluminum cap mkd.



Cor. is located in 5 strand barbed wire fence, bears E. and W.

Thence along the Table Top Wilderness Area Bdy.

40.04 True point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate dist.

The witness cor. for the 1/4 sec. cor. of secs. 18 and 19, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. WC S18 1/4 S19 1934.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 8 S., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	1. 6 S., R. 3 E., Gila and Sait River Meridian, Arizona
	Add the marks T8S R3E 1998 to the brass cap.
	Restoring the Survey executed by W. H. Thorn and W. K. Kierulff, in 1915
	From the cor. of secs. 17, 18, 19 and 20.
	N. 0°02' E., bet. secs. 17 and 18.
	Over rolling and rocky land, through creosote and cacti.
40.00	The 1/4 sec. cor of secs. 17 and 18, monumented with an iron post, 1 in diam., firmly set, projecting 4 ins above the ground, with the brass cap mkd. 1/4 S18 S17 1915.
	Add the marks T8S R3E 1998 to the brass cap.
	Cor is located 25 ft. N. of wash, drains ESE.
	N. 0°03' W., beginning new measurement.
	Over rolling and rocky land, through creosote and cacti.
25.28	Point for AP 18, Tract 38, identical with AP 1, sec. 17, of the metes-and-bounds survey of the Table Top Wilderness Area Bdy., not monumented.
40.02	The cor. of secs. 7, 8, 17 and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 23 ins. above the ground, in a scattered mound of stone, with brass cap mkd. T8S R3E S7 S8 S18 S17 1915.
	Add the marks 1998 to the brass cap.
	Rebuilt the supporting mound of stone, 2 1/2 ft. base, to top.
	From the 1/4 sec. cor. of secs. 8 and 17, monumented with an iron post, 1 in. diam., firmly set, projecting 25 ins. above the ground, in a supporting mound of stone, 2 1/2 ft. base to top, with brass cap mkd. S8 1/4 S17 1915.
	Add the marks T8S R3E 1998 to the brass cap.
	S. 89°54′ W., bet. secs. 8 and 17.
	Over rolling and rocky land, through creosote and cacti.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 8 S., R. 3 E., Gila and Salt River Meridian, Arizona

	1. 0 S., R. 3 E., Gila and Sait River Meridian, Arizona
CHAINS	
19.95	Point for AP 8, sec. 17, identical with AP 1, sec. 8, of the metes-and-bounds survey of the Table Top Wilderness Area Bdy., not monumented.
40.05	The cor. of secs. 7, 8, 17 and 18.
	N. 0°02' W., bet. secs. 7 and 8.
	Over rolling and rocky land, through creosote and cacti.
27.88	Point for AP 19, Tract 37, identical with AP 11, sec. 8, of the metes-and-bounds survey of the Table Top Wilderness Area Bdy., not monumented.
28.30	Two track road, bears E. and W.
28.81	Point for AP 43, Tract 37, identical with AP 12, sec. 8, of the metes-and-bounds survey of the Table Top Wilderness Area Bdy., not monumented.
40.01	The 1/4 sec. cor. of secs. 7 and 8, monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above the ground, in a scattered mound of stone, with brass cap mkd. S7 1/4 S8 1915.
<u>:</u>	Add the marks T8S R3E 1998 to the brass cap.
	Rebuilt the supporting mound of stone, 2 1/2 ft. base, to top.
	N. 0°01' W., beginning new measurement.
	Over rolling and rocky land, through creosote and cacti.
40.26	The true point for the cor. of secs. 5, 6, 7 and 12, determined at record bearing and dist. from the original witness cor.
	From this point, the witness cor. for the cor. of secs. 5, 6, 7 and 8, bears N. O°O3' W., O.59 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. WC T8S R3E S6 S5 S7 S8 1915.
	Add the marks 1998 to the brass cap.
	From the 1/4 sec. cor. of secs. 5 and 8, monumented with an iron post, 1 in diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. S5 1/4 S8 1915.
	Add the marks T8S R3E 1998 to the brass cap.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 8 S., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	The strike of th
Chains	
	N. 89°47′ W., bet. secs. 5 and 8.
	Over rolling and rocky land, through creosote and cacti.
3.97	Point for AP 1, sec. 5 identical with AP 26, sec. 8, of the metes-and-bounds survey of the Table Top Wilderness Area Bdy., not monumented.
40.03	The true point for the cor. of secs. 5, 6, 7 and 8.
	Metes-and-Bounds Survey of the Table Top Wilderness Area Bdy., T. 8 S., R. 3 E., Gila and Salt River Meridian, Arizona
	Tract 38
	From AP 1, Tract 38, on the line bet. secs. 18 and 19, hereinbefore described.
	From this cor. point, the cor. of sec. 17, 18, 19 and 20, bears N. 89°59' E., 14.90 chs. dist., hereinbefore described.
	N. 20°49' E., on line 1-2, Tract 38, of the metes-and-bounds survey of the Table Top Wilderness Area Bdy.
	Over rolling and rocky lands, through creosote and cacti.
6.75	Point for AP 2, Tract 38.
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd.
	T8S R3E
	AP2
	TTWA
	1998
	Cor. is located in 3 strand barbed wire fence, bears NNE. and SSW.
	N. 58°51' E., on line 2-3, Tract 38.
	Over rolling and rocky lands, through creosote and cacti.
6.26	Point for AP 3, Tract 38.

CHAINS

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd.

T8S R3E
TTWA
AP3
1998

Cor. is located 30 ft. westerly of two track road.

N. 22°31' E., on line 3-4, Tract 38.

Over rolling and rocky lands, through creosote and cacti.

4.42 | Point for AP 4, Tract 38.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd.

T8S R3E TTWA AP4 1998

Cor. is located 30 ft. westerly of two track road.

N. 0°25' W., on line 4-5, Tract 38.

Over rolling and rocky lands, through creosote and cacti.

7.53 | Point for AP 5, Tract 38.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd.

T8S R3E TTWA / AP5 / 1998

Cor. is located 30 ft. westerly of two track road.

N. 9°07' E., on line 5-6, Tract 38.

CHAINS Over rolling and rocky lands, through creosote and cacti. 2.71 Point for AP 6, Tract 38. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd. T8S ,R3E TTWA \ AP6 1998 Cor. is located 30 ft. westerly of two track road. N. 18°04' W., on line 6-7, Tract 38. Over rolling and rocky lands, through creosote and cacti. 2.42 Point for AP 7, Tract 38. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd. T8S R3E TTWA Cor. is located 30 ft. westerly of two track road. N. 9°12' E., on line 7-8, Tract 38. Over rolling and rocky lands, through creosote and cacti. 2.90 Point for AP 8, Tract 38. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd. **T8S R3E** TTWA 1998 Cor. is located 30 ft. westerly of two track road.

CHAINS

N. 0°07' E., on line 8-9, Tract 38.

Over rolling and rocky lands, through creosote and cacti.

8.68 Point for AP 9, Tract 38.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd.



Cor. is located 30 ft. westerly of two track road.

N. 32°25' E., on line 9-10, Tract 38.

Over rolling and rocky lands, through creosote and cacti.

3.82 | Point for AP 10, Tract 38.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.



Cor. is located 30 ft. westerly of two track road.

N. 6°12′ W., on line 10-11, Tract 38.

Over rolling and rocky lands, through creosote and cacti.

- 6.90 Wash, 20 lks. wide, drains E.
- 7.26 | Point for AP 11, Tract 38.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, in a supporting mound of stone, 2 1/2 ft. base, to top, with aluminum cap mkd.

CHAINS

T8S R3E TTWA AP11

Cor. is located 30 ft. westerly of two track road.

N. 11°35′ W., on line 11-12, Tract 38.

Over rolling and rocky lands, through creosote and cacti.

6.22 | Point for AP 12, Tract 38.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, in a supporting mound of stone, 2 ft. base, to top, with aluminum cap mkd.



Cor. is located 30 ft. westerly of two track road.

N. 54°42′ W., on line 12-13, Tract 38.

Over rolling and rocky lands, through creosote and cacti.

2.23 | Point for AP 13, Tract 38.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, in a supporting mound of stone, 2 ft. base, to top, with aluminum cap mkd.



Cor. is located 30 ft. westerly of two track road.

N. 34°23′ W., on line 13-14, Tract 38.

Over rolling and rocky lands, through creosote and cacti.

CHAINS Point for AP 14, Tract 38. 2.33 Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd. T8S R3E TTWA AP14 Cor. is located 30 ft. westerly of two track road. N. 16°28' E., on line 14-15, Tract 38. Over rolling and rocky lands, through creosote and cacti. 5.66 Point for AP 15, Tract 38. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd. **T8S R3E** TTWA Cor. is located 30 ft. westerly of two track road. N. 42°47' E., on line 15-16, Tract 38. Over rolling and rocky lands, through creosote and cacti. Point for AP 16, Tract 38. 3.69 Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd. T8S R3E TTWA AP16 1998 Cor. is located 30 ft. northwesterly of two track road. S. 82°57' E., on line 16-17, Tract 38.

CHAINS Over rolling and rocky lands, through creosote and cacti. Point for AP 17, Tract 38. 3.88 Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd. T8S R3E TTWA AP17 1998 Cor. is located 30 ft. northerly of two track road. N. 67°51' E., on line 17-18, Tract 38. Over rolling and rocky lands, through creosote and cacti. 0.56 The point for AP 18, Tract 38, identical with AP 1, sec. 17, on the line bet. secs. 17 and 18, hereinbefore described. From this point, the cor of sec. 7, 8, 17 and 18, bears N. 0°03' W., 14.74 chs. dist., hereinbefore described In Section 17 From the point for AP 1, sec. 17, identical with AP 18, Tract 38, on the line bet. secs. 17 and 18. N. 67°51' E., on line 1-2, sec. 17, of the metes-and-bounds survey of the Table Top Wilderness Area Bdy. Over rolling and rocky lands, through creosote and cacti. 2.56 Point for AP 2, sec. 17. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd. T8S R3E **TTWA** AP2 S17 1998

CHAINS	
	Cor. is located 30 ft. northerly of two track road.
	S. 79°29' E., on line 2-3, sec. 17.
	Over rolling and rocky lands, through creosote and cacti.
2.95	Point for AP 3, sec. 17.
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, with aluminum cap mkd.
	T8S R3E
	TTWA AP3
	S17 1998
	Cor. is located 30 ft. northerly of two track road.
	N. 69°30' E., on line 3-4, sec. 17.
	Over rolling and rocky lands, through creosote and cacti.
10.45	Point for AP 4, sec. 17.
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.
	T8S R3E
	TTWA AP4
	\$17
	1998
	Cor. is located 30 ft. northerly of two track road.
	N. 89°32' E., on line 4-5, sec. 17.
	Over rolling and rocky lands, through creosote and cacti.
2.35	Point for AP 5, sec. 17.
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 29 ins. in the ground, with aluminum cap mkd.
2.35	Point for AP 5, sec. 17. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 29 ins. in the

	T. 8 S., R. 3 E., Gila and Salt River Meridian, Arizona
CHAINS	
	T8S R3E TTWA AP5 S17
	1998
	Cor. is located 30 ft. northwesterly of two track road.
	N. 12°59' E., on line 5-6, sec. 17.
	Over rolling and rocky lands, through creosote and cacti.
2.08	Point for AP 6, sec. 17.
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 27 ins. in the ground, with aluminum cap mkd.
	T8S R3E TTWA AP6 S17
	1998
	Cor. is located 30 ft. westerly of two track road.
	N. 24°50' E., on line 6-7, sec. 17.
	Over rolling and rocky lands, through creosote and cacti.
5.51	Point for AP 7, sec. 17.
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd.
	T8S R3E TTWA AP7 S17
	1998
	Cor. is located 30 ft. westerly of two track road.
	N. 1°31′ W., on line 7-8, sec. 17.
	Over rolling and rocky lands, through creosote and cacti.

The point for AP 8, sec. 17, identical with AP 1, sec. 8, on the

line bet. secs. 8 and 17, hereinbefore described.

3.64

CHAINS

From this point, the 1/4 sec. cor. of secs. 8 and 17, bears N. 89°54′ E., 19.95 chs. dist., hereinbefore described

In Section 8

From the point for AP 1, sec. 8, identical with AP 8, sec. 17, on the line bet. secs. 8 and 17.

N. 1°31' W., on line 1-2, sec. 8, of the metes-and-bounds survey of the Table Top Wilderness Area Bdy.

Over rolling and rocky lands, through creosote and cacti.

11.80 | Point for AP 2, sec. 8.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, with aluminum cap mkd.

Cor. is located 30 ft. easterly of two track road.

N. 2°05' W., on line 2-3, sec. 8.

Over rolling and rocky lands, through creosote and cacti.

5.46 | Point for AP 3, sec. 8.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, with aluminum cap mkd.

Cor. is located 30 ft. easterly of two track road.

N. 23°10' E., on line 3-4, sec. 8.

Over rolling and rocky lands, through creosote and cacti.

T. 8 S., R. 3 E., Gila and Salt River Meridian, Arizona **CHAINS** Point for AP 4, sec. 8. 8.15 Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd. **T8S R3E** TTWA AP4 Cor. is located 30 ft. easterly of two track road. N. 17°38' E., on line 4-5, sec. 8. Over rolling and rocky lands, through creosote and cacti. 4.37 Point for AP 5, sec. 8. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd. T8S R3E 1998 Cor. is located 30 ft. southeasterly of two track road. N. 68°03' W., on line 5-6, sec. 8. Over rolling and rocky lands, through creosote and cacti. 2.54 Point for AP 6, sec. 8. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd. T8S R3E **S8** AP6 **TTWA** 1998 Cor. is located 30 ft. southerly of two track road.

CHAINS

S. 80°04' W., on line 6-7, sec. 8.

Over rolling and rocky lands, through creosote and cacti.

9.11 | Point for AP 7, sec. 8.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd.




Cor. is located 30 ft. southerly of two track road.

S. 65°22′ W., on line 7-8, sec. 8.

Over rolling and rocky lands, through creosote and cacti.

5.37 | Point for AP 8, sec. 8.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd.



Cor. is located 30 ft. southerly of two track road.

N. 56°46′ W., on line 8-9, sec. 8.

Over rolling and rocky lands, through creosote and cacti.

3.13 | Point for AP 9, sec. 8.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, to bedrock in a supporting mound of stone, 2 ft. base, to top, with aluminum cap mkd.

CHAINS

T8S R3E S8 AP9 TTWA 1998

Cor. is located 30 ft. southerly of two track road.

N. 83°01' W., on line 9-10, sec. 8.

Over rolling and rocky lands, through creosote and cacti.

3.46 | Point for AP 10, sec. 8.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.

AP10 TTWA 1998

Cor. is located 30 ft. southerly of two track road.

S. 79°53′ W., on line 10-11, sec. 8.

Over rolling and rocky lands, through creosote and cacti.

1.91 The point for AP 11, sec. 8, identical with AP 19, Tract 37, on the line bet. secs. 7 and 8, hereinbefore described.

From this point, the cor. of secs. 7, 8, 17 and 18, bears S. 0°02' E., 27.88 chs. dist., hereinbefore described.

Tract 37

From the point for AP 19, Tract 37, identical with AP 11, sec. 8, on the line bet. secs. 7 and 8.

S. 79°53′ W., on line 19-20, Tract 37, of the metes-and-bounds survey of the Table Top Wilderness Area Bdy.

Over rolling and rocky lands, through creosote and cacti.

CHAINS	
3.99	Point for AP 20, Tract 37.
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.
	T8S R3E
	AP20 TTWA 1998
	Cor. is located 30 ft. southerly of two track road.
	N. 84°44′ W., on line 20-21, Tract 37.
	Over rolling and rocky lands, through creosote and cacti.
4.35	Point for AP 21, Tract 37.
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.
	T8S R3E
	AP21 TTWA 1998
	Cor. is located 30 ft. southerly of two track road.
	N. 87°06′ W., on line 21-22, Tract 37.
	Over rolling and rocky lands, through creosote and cacti.
4.02	Point for AP 22, Tract 37.
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 29 ins. in the ground, with aluminum cap mkd.
	T8S R3E
	AP22 TTWA 1998
	Cor. is located 30 ft. southerly of two track road.
	N. 87°25′ W., on line 22-23, Tract 37.

CHAINS Over rolling and rocky lands, through creosote and cacti. 3.64 Point for AP 23, Tract 37. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd. T8S R3E TTWA 1998 Cor. is located 30 ft. southerly of two track road. N. 40°36' W., on line 23-24, Tract 37. Over rolling and rocky lands, through creosote and cacti. 3.03 Point for AP 24, Tract 37. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd. T8S R3E 1998 Cor. is located 30 ft. southerly of two track road. N. 54°06′ W., on line 24-25, Tract 37. Over rolling and rocky lands, through creosote and cacti. 4.26 Point for AP 25, Tract 37. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd. T8S R3E AP25 TTWA 1998 Cor. is located 30 ft. southwesterly of two track road.

CHAINS

N. 31°24′ W., on line 25-26, Tract 37.

Over rolling and rocky lands, through creosote and cacti.

5.66 | Point for AP 26, Tract 37.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.

T8S R3E AP26 TTWA 1998

Cor. is located 30 ft. southwesterly of two track road.

N. 52°14′ W., on line 26-27, Tract 37.

Over rolling and rocky lands, through creosote and cacti.

5.56 | Point for AP 27, Tract 37.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.



Cor. is located 30 ft. southwesterly of two track road.

N. 71°25' W., on line 27-28, Tract 37.

Over rolling and rocky lands, through creosote and cacti.

4.34 | Point for AP 28, Tract 37.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.



CHAINS Cor. is located 30 ft. southwesterly of two track road. N. 15°40' W., on line 28-29, Tract 37. Over rolling and rocky lands, through creosote and cacti. 2.18 Point for AP 29, Tract 37. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd. **T8S R3E** AP29 TTWA 1998 Cor. is located 30 ft. southwesterly of two track road. N. 72°20′ W., on line 29-30, Tract 37. Over rolling and rocky lands, through creosote and cacti. 3.17 Point for AP 30, Tract 37. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, with aluminum cap mkd. **T8S R3E** AP30 4 **TTWA** 1998 N. 28°32' E., on line 30-31, Tract 37. Over rolling and rocky lands, through creosote and cacti. 4.38 Point for AP 31, Tract 37. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, in a supporting mound of stone, 2 ft. base, to top, with aluminum cap mkd.

CHAINS

T8S R3E TTWA AP31 1998

Cor. is located 28 ft. NW of 5 strand barbed wire fence, bears SE and ESE.

S. 68°24' E., on line 31-32, Tract 37.

Over rolling and rocky lands, through creosote and cacti.

3.86 | Point for AP 32, Tract 37.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd.




Cor. is located 28 ft. NE of 5 strand barbed wire fence, bears SW and WNW.

S. 29°56′ W., on line 32-33, Tract 37.

Over rolling and rocky lands, through creosote and cacti.

2.46 Point for AP 33, Tract 37.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.



Cor. is located 20 ft. E of 5 strand barbed wire fence, bears NE and WNW.

S. 4°30′ W., on line 33-34, Tract 37.

CHAINS Over rolling and rocky lands, through creosote and cacti. 2.71 Point for AP 34, Tract 37. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd. **T8S R3E** AP34 **TTWA** 1998 Cor. is located 30 ft. northeasterly of two track road. S. 72°58' E., on line 34-35, Tract 37. Over rolling and rocky lands, through creosote and cacti. 4.07 Point for AP 35, Tract 37. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd. T8S R3E AP35 TTWA 1998 Cor. is located 30 ft. northerly of two track road. S. 51°13' E., on line 35-36, Tract 37. Over rolling and rocky lands, through creosote and cacti. 6.18 Point for AP 36, Tract 37. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd. T8S R3E AP36 **TTWA** Cor. is located 30 ft. northerly of two track road.

Metes-and-Bounds Survey of the Table Top Wilderness Area Bdy.,

T. 8 S., R. 3 E., Gila and Salt River Meridian, Arizona **CHAINS** S. 31°12′ E., on line 36-37, Tract 37. Over rolling and rocky lands, through creosote and cacti. 5.52 Point for AP 37, Tract 37. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd. T8S R3E AP37 TTWA Cor. is located 30 ft. northerly of two track road. S. 54°19' E., on line 37-38, Tract 37. Over rolling and rocky lands, through creosote and cacti. 4.12 Point for AP 38, Tract 37. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd. T8S R3E TTWA AP38 1998 Cor. is located 30 ft. northerly of two track road. S. 43°03' E., on line 38-39, Tract 37. Over rolling and rocky lands, through creosote and cacti. 2.90 Point for AP 39, Tract 37. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd. **T8S R3E** TTWA **AP39** 1998

	T. 0 5., R. 5 E., GITA AND SAIL RIVEL MELITANI, ALIZONA
CHAINS	
	Cor. is located 30 ft. northeasterly of two track road.
	2 20150/ 5 31 20 40 7 4 27
	S. 88°50' E., on line 39-40, Tract 37.
	Over rolling and rocky lands, through creosote and cacti.
3.36	Point for AP 40, Tract 37.
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd.
	T8S R3E AP40 TTWA
	1998
	Cor. is located 30 ft. northerly of two track road.
	·
	S. 87°20′ E., on line 40-41, Tract 37.
	Over rolling and rocky lands, through creosote and cacti.
3.90	Point for AP 41, Tract 37.
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.
	T8S R3E AP41 TTWA
	1998
	Cor. is located 30 ft. northerly of two track road.
	S. 83°12′ E., on line 41-42, Tract 37.
	Over rolling and rocky lands, through creosote and cacti.
3.95	Point for AP 42, Tract 37.
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.
	T8S R3E AP42 TTWA
	1998

GWANNE	T. 6 5., N. 5 E., Gila and Sait River Her Idian, Arizona
CHAINS	Cor. is located 30 ft. northerly of two track road.
	N. 78°36' E., on line 42-43, Tract 37.
	Over rolling and rocky lands, through creosote and cacti.
4.17	The point for AP 43, Tract 37, identical with AP 12, sec. 8, on the line bet. secs. 7 and 8, hereinbefore described.
	From this point, the 1/4 sec. cor. of secs. 7 and 8, bears N. 0°02' W., 11.20 chs. dist., hereinbefore described.
	In Section 8
	From the point for AP 12, sec. 8, identical with AP 43, Tract 37, on the line bet. secs. 7 and 8.
	N. 78°36' E., on line 12-13, sec. 8, of the metes-and-bounds survey of the Table Top Wilderness Area Bdy.
	Over rolling and rocky lands, through creosote and cacti.
1.55	Point for AP 13, sec. 8.
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd.
	T8S R3E
	TTWA
	AP13
	S8 1998
	Cor. is located 30 ft. northerly of two track road.
	S. 82°38' E., on line 13-14, sec. 8.
	Over rolling and rocky lands, through creosote and cacti.
4.14	Point for AP 14, sec. 8.
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 27 ins. in the ground, with aluminum cap mkd.

T8S R3E TTWA AP14 S8 1998


Cor. is located 30 ft. northerly of two track road.

S. 55°19' E., on line 14-15, sec. 8.

Over rolling and rocky lands, through creosote and cacti.

2.86 | Point for AP 15, sec. 8.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, in a supporting mound of stone, 2 ft. base, to top, with aluminum cap mkd.



Cor. is located 30 ft. northerly of two track road.

N. 63°24' E., on line 15-16, sec. 8.

Over rolling and rocky lands, through creosote and cacti.

5.14 | Point for AP 16, sec. 8.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 29 ins. in the ground, with aluminum cap mkd.

T8S R3E TTWA AP16 S8 1998

Cor. is located 30 ft. northerly of two track road.

N. 80°13' E., on line 16-17, sec. 8.

	T. 8 S., R. 3 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Over rolling and rocky lands, through creosote and cacti.
8.85	Point for AP 17, sec. 8.
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.
	T8S_R3E
	TTWA AP17
	1998
	Cor. is located 30 ft. northerly of two track road.
	S. 84°39′ E., on line 17-18, sec. 8.
	Over rolling and rocky lands, through creosote and cacti.
3.44	Point for AP 18, sec. 8.
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.
	T8S R3E TTWA AP18 S8
	1998
	Cor. is located 30 ft. northwesterly of two track road.
	N. 4°36' W., on line 18-19, sec. 8.
	Over rolling and rocky lands, through creosote and cacti.
4.17	Point for AP 19, sec. 8.
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.
	T8S R3E TTWA / AP19 S8
	1998

CHAINS

Cor. is located 30 ft. westerly of two track road.

N. 8°49' E., on line 19-20, sec. 8.

Over rolling and rocky lands, through creosote and cacti.

10.07 | Point for AP 20. sec. 8.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.

Cor. is located 30 ft. westerly of two track road.

N. 34°02' E., on line 20-21, sec. 8.

Over rolling and rocky lands, through creosote and cacti.

5.44 | Point for AP 21, sec. 8.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.

Cor. is located 30 ft. westerly of two track road.

N. 32°24′ W., on line 21-22, sec. 8.

Over rolling and rocky lands, through creosote and cacti.

5.19 | Point for AP 22, sec. 8

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 22 ins. in the ground, in a supporting mound of stone, 2 1/2 ft. base, to top, with aluminum cap mkd.

	1. 0 3., N. 3 L., dita and Saft River Her Idian, Al 120na
CHAINS	
	T8S R3E
	AP22 (S8
	TTWA \ 1998
	Cor. is located 30 ft. westerly of two track road.
	N. 11°00' E., on line 22-23, sec. 8.
	Over rolling and rocky lands, through creosote and cacti.
8.72	Point for AP 23, sec. 8.
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.
	T8S R3E
	AP23 S8
	TTWA / 1998
	Cor. is located 30 ft. westerly of two track road.
	N. 40°31′ E., on line 23-24, sec. 8.
	Over rolling and rocky lands, through creosote and cacti.
11.03	Point for AP 24, sec. 8.
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, with aluminum cap mkd.
	T8S R3E
	TTWA AP24 S8
	1998
	Cor. is located 30 ft. westerly of two track road.
	N. 8°10' E., on line 24-25, sec. 8.
	Over rolling and rocky lands, through creosote and cacti.
5.31	Point for AP 25, sec. 8.

CHAINS

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 15 ins. in the ground, in a supporting mound of stone, 2 1/2 ft. base, 12 ins. high, with aluminum cap mkd.

Cor. is located 30 ft. westerly of two track road.

N. 3°26' E., on line 25-26, sec. 8.

Over rolling and rocky lands, through creosote and cacti.

The point for AP 26, sec. 8, identical with AP 1, sec. 5, on the line bet. secs. 5 and 8, hereinbefore described.

From this point, the 1/4 sec. cor. of secs. 5 and 8, bears S. 89°47′ E., 3.97 chs. dist., hereinbefore described

In Section 5

From the point for AP 1, sec. 5, identical with AP 26, sec. 8, on the line bet. secs. 5 and 8.

N. 3°26' E., on line 1-2, sec. 5, of the metes-and-bounds survey of the Table Top Wilderness Area Bdy.

Over rolling and rocky lands, through creosote and cacti.

0.98 | Point for AP 2, sec. 5.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 19 ins. in the ground to bedrock, in a supporting mound of stone, 2 ft. base, 12 ins. high, with aluminum cap mkd.



Cor. is located 30 ft. westerly of two track road.

CHAINS

N. 36°38' E., on line 2-3, sec. 5.

Over rolling and rocky lands, through creosote and cacti.

2.82

Point for AP 3, sec. 5.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.



Cor. is located 30 ft. northwesterly of two track road.

N. 36°55' E., on line 3-4, sec. 5.

Over rolling and rocky lands, through creosote and cacti.

3.65 | Point for AP 4, sec. 5.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.



Cor. is located 30 ft. northwesterly of two track road.

N. 53°46' E., on line 4-5, sec. 5.

Over rolling and rocky lands, through creosote and cacti.

9.13 | Point for AP 5, sec. 5.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, with aluminum cap mkd.



CHAINS

Cor. is located 30 ft. northwesterly of two track road.

N. 63°08' E., on line 5-6, sec. 5.

Over rolling and rocky lands, through creosote and cacti.

4.95 | Point for AP 6, sec. 5.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.




Cor. is located 30 ft. northwesterly of two track road.

N. 50°43' E., on line 6-7, sec. 5.

Over rolling and rocky lands, through creosote and cacti.

3.49 | Point for AP 7, sec. 5.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.



Cor. is located 30 ft. northwesterly of two track road.

N. 58°28' E., on line 7-8, sec. 5.

Over rolling and rocky lands, through creosote and cacti.

8.42 | Point for AP 8, sec. 5.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.

CHAINS

T8S R3E TTWA S5

Cor. is located 30 ft. northwesterly of two track road.

N. 17°56' E., on line 8-9, sec. 5.

Over rolling and rocky lands, through creosote and cacti.

7.26 | Point for AP 9, sec. 5.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.




Cor. is located 30 ft. westerly of two track road.

N. 35°20' W., on line 9-10, sec. 5.

Over rolling and rocky lands, through creosote and cacti.

3.22 | Point for AP 10, sec. 5.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.



Cor. is located 30 ft. westerly of two track road.

N. 61°02′ W., on line 10-11, sec. 5.

Over rolling and rocky lands, through creosote and cacti.

3.22 | Point for AP 11, sec. 5.

CHAINS

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, with aluminum cap mkd.

T8S R3E TTWA AP11 S5


Cor. is located 30 ft. southwesterly of two track road.

N. 42°10′ W., on line 11-12, sec. 5.

Over rolling and rocky lands, through creosote and cacti.

3.42 Point for AP 12, sec. 5.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.



Cor. is located 30 ft. southwesterly of two track road.

N. 53°43′ W., on line 12-13, sec. 5.

Over rolling and rocky lands, through creosote and cacti.

3.80 | Point for AP 13, sec. 5.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.

T8S R3E S5 AP13 TTWA 1998

Cor. is located 30 ft. southerly of two track road.

N. 87°10′ W., on line 13-14, sec. 5.

CHAINS Over rolling and rocky lands, through creosote and cacti. 2.03 Point for AP 14, sec. 5. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd. T8S R3E AP14 **TTWA** 1998 Cor. is located 30 ft. southerly of two track road. N. 28°10′ W., on line 14-15, sec. 5. Over rolling and rocky lands, through creosote and cacti. 1.25 Point for AP 15, sec. 5. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 17 ins. in the ground to bedrock, in a supporting mound of stone, 2 1/2 ft. base, 12 ins. high, with aluminum cap mkd. T8S R3E TTWA AP15 1998 Cor. is located 30 ft. westerly of two track road. N. 15°58' E., on line 15-16, sec. 5. Over rolling and rocky lands, through creosote and cacti. 9.10 Point for AP 16, sec. 5. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd. **T8S R3E** S5 AP16 TTWA/ 1998

CHAINS						
	Cor. is located 30 ft. southwesterly and 30 ft. southeasterly of two track road.					
	S. 32°21′ W., on line 16-17, sec. 5.					
	Over rolling and rocky lands, through creosote and cacti.					
5.99	Point for AP 17, sec. 5.					
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.					
	T8S R3E S5					
	AP17					
	/ TTWA 1998					
	1990					
	Cor. is located 30 ft. easterly of two track road.					
	S. 27°46′ W., on line 17-18, sec. 5.					
	Over rolling and rocky lands, through creosote and cacti.					
3.50	Point for AP 18, sec. 5.					
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.					
	T8S R3E S5					
	AP18					
	TTWA 1998					
	Cor. is located 30 ft. southeasterly of two track road.					
	S. 55°54′ W., on line 18-19, sec. 5.					
	Over rolling and rocky lands, through creosote and cacti.					
5.64	Point for AP 19, sec. 5.					
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 29 ins. in the ground, with aluminum cap mkd.					
	growing, wrom aramitian out mar					

CHAINS

T8S R3E S5 AP19 TTWA 1998


Cor. is located 30 ft. southeasterly of two track road.

N. 86°09' W., on line 19-20, sec. 5.

Over rolling and rocky lands, through creosote and cacti.

3.89 | Point for AP 20, sec. 5.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.



Cor. is located 30 ft. southeasterly of two track road.

S. 23°58′ W., on line 20-21, sec. 5.

Over rolling and rocky lands, through creosote and cacti.

2.18 | Point for AP 21, sec. 5.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 25 ins. in the ground to bedrock, in a supporting mound of stone, 2 ft. base, to top, with aluminum cap mkd.



Cor. is located 30 ft. southeasterly of two track road.

S. 66°56′ W., on line 21-22, sec. 5.

	1. 8 S., R. 3 E., Gila and Sait River Meridian, Arizona			
CHAINS				
	Over rolling and rocky lands, through creosote and cacti.			
2.20	Point for AP 22, sec. 5.			
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.			
	T8S R3E S5 AP22 TTWA			
	1998			
	Cor. is located 30 ft. southerly of two track road.			
	S. 3°35′ E., on line 22-23, sec. 5.			
	Over rolling and rocky lands, through creosote and cacti.			
5.42	Point for AP 23, sec. 5.			
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.			
	T8S R3E S5 AP23 TTWA 1998			
	S. 68°28′ W., on line 23-24, sec. 5.			
	Over rolling and rocky lands, through creosote and cacti.			
3.35	Point for AP 24, sec. 5.			
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.			
	T8S R3E S5			
	AP24 TTWA 1998			

CHAINS N. 61°34′ W., on line 24-25, sec. 5. Over rolling and rocky lands, through creosote and cacti. 2.74 Point for AP 25, sec. 5. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 29 ins. in the ground, with aluminum cap mkd. T8S R3E S5 AP25 TTWA 1998 Cor. is located 35 ft. SE. of corner of 4 strand barbed wire fence, bears NE. and NW. N. 28°31′ W., on line 25-26, sec. 5. Over rolling and rocky lands, through creosote and cacti. Point for AP 26, sec. 5. 3.99 Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd. T8S R3E AP26 TTWA 1998 Cor. is located 35 ft. SW. of corner of 4 strand barbed wire fence, bears SE. and SW. N. 81°43′ W., on line 26-27, sec. 5. Over rolling and rocky lands, through creosote and cacti. 6.55 Point for AP 27, sec. 5. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 21 ins. in the ground to bedrock, in a supporting mound of stone, 2 ft. base, to top, with aluminum cap mkd.

CHAINS

T8S R3E TTWA _____ S5 AP27 ____ S5


Cor. is located 15 ft. SW. of corner of 4 strand barbed wire fence, bears NE. and ENE.

N. 7°41' E., on line 27-28, sec. 5.

Over rolling and rocky lands, through creosote and cacti.

4.22 | Point for AP 28, sec. 5.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 24 ins. in the ground to bedrock, in a supporting mound of stone, 2 ft. base, to top, with aluminum cap mkd.




N. 59°46' E., on line 28-29, sec. 5.

Over rolling and rocky lands, through creosote and cacti.

8.18 Point for AP 29, sec. 5.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.



Cor. is located 30 ft. westerly of two track road.

N. 32°36' E., on line 29-30, sec. 5.

Over rolling and rocky lands, through creosote and cacti.

CHAINS 1.49 Point for AP 30, sec. 5. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd. T8S R3E TTWA **AP30 S5** 1998 Cor. is located 30 ft. northerly of two track road. S. 64°05' E., on line 30-31, sec. 5. Over rolling and rocky lands, through creosote and cacti. 1.19 Point for AP 31, sec. 5. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd. T8S R3E TTWA AP31 1998 \ Cor. is located 30 ft. easterly of two track road. S. 17°36' E., on line 31-32, sec. 5. Over rolling and rocky lands, through creosote and cacti. 7.80 Point for AP 32, sec. 5. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd. T8S R3E **TTWA** AP32 **S5** 1998

CHAINS	
	Cor. is located 30 ft. easterly of two track road.
	N. 74°40' E., on line 32-33, sec. 5.
	Over rolling and rocky lands, through creosote and cacti.
3.11	Point for AP 33, sec. 5.
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.
	T8S R3E TTWA AP33
	S5 1998
	Cor. is located 30 ft. northerly of two track road.
	N. 31°23′ E., on line 33-34, sec. 5.
	Over rolling and rocky lands, through creosote and cacti.
2.24	Point for AP 34, sec. 5.
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.
	T8S R3E
	TTWA AP34
	S5
	1998
	Cor. is located 30 ft. northerly of two track road.
	S. 89°19' E., on line 34-35, sec. 5.
	Over rolling and rocky lands, through creosote and cacti.
4.01	Point for AP 35, sec. 5.
	Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd.

CHAINS T8S R3E TTWA AP35 **S5** 1998 Cor. is located 30 ft. northerly of two track road. N. 56°07' E., on line 35-36, sec. 5. Over rolling and rocky lands, through creosote and cacti. 5.29 Point for AP 36, sec. 5. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 25 ins. in the ground to bedrock, in a supporting mound of stone, 2 ft. base, to top, with aluminum cap mkd. T8S R3E TTWA AP36 **S5** 1998 Cor. is located 30 ft. northerly of two track road. N. 25°44' E., on line 36-37, sec. 5. Over rolling and rocky lands, through creosote and cacti. 3.37 Point for AP 37, sec. 5. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd. T8S R3E TTWA 1998 Cor. is located 30 ft. northerly of two track road. N. 32°05' E., on line 37-38, sec. 5. Over rolling and rocky lands, through creosote and cacti.

CHAINS

7.78 | Point for AP 38, sec. 5.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, with aluminum cap mkd.

Cor. is located 30 ft. westerly of two track road.

N. 9°26' W., on line 38-39, sec. 5.

Over rolling and rocky lands, through creosote and cacti.

5.18 | Point for AP 39, sec. 5.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd.


Cor. is located 30 ft. westerly of two track road.

N. 7°41' E., on line 39-40, sec. 5.

Over rolling and rocky lands, through creosote and cacti.

7.22 | Point for AP 40, sec. 5.

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, with aluminum cap mkd.



Cor. is located 30 ft. westerly of two track road.

N. 56°04' E., on line 40-41, sec. 5.

CHAINS Over rolling and rocky lands, through creosote and cacti. Point for AP 41, sec. 5. 2.96 Set an aluminum rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd. T8S R3E TTWA AP41 1998 Cor. is located 30 ft. westerly of two track road. N. 39°34' E., on line 41-42, sec. 5. Over rolling and rocky lands, through creosote and cacti. 3.77 Point for AP 42, sec. 5. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd. T8S R3E 1998 Cor. is located 30 ft. westerly of two track road. N. 25°34' E., on line 42-43, sec. 5. Over rolling and rocky lands, through creosote and cacti. 6.33 Point for AP 43, sec. 5. Set an aluminum rod, 36 ins. long, 3/4 in. diam., 12 ins. in the ground to bedrock, in a supporting mound of stone, 2 ft. base, 18 ins. high, with aluminum cap mkd. T8S R3E TTWA AP43 **S5** 1998

CHAINS

Cor. is located 30 ft. westerly of two track road.

N. 17°28' E., on line 43-44, sec. 5.

Over rolling and rocky lands, through creosote and cacti.

9.48

AP 44, sec. 5, identical with AP 1, Tract 38, T. 7 S., R. 3 E., monumented with an aluminum rod, 3/4 in. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. T7S R3E TTWA AP1 AP44 S5 TTWA T8S 1997 as described in the field notes of the dependent resurvey of a portion of the S. bdy., T. 7 S., R. 3 E., surveyed concurrently under this same group.

From this cor. point, the cor. of secs. 4, 5, 32 and 33, on the N. bdy. of Tp., bears S. 89°59′ E., 15.76 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above ground with brass cap mkd. T7S R3E S5 S4 S32 S33 T8S 1915 1997 as described in the field notes of the dependent resurvey of a portion of the S. bdy., T. 7 S., R. 3 E., surveyed concurrently under this same group.

General Description

Table Top Wilderness Area is located about 30 miles easterly of Gila Bend, Arizona. The land is rolling and rocky. Vegetation consists of creosote, palo verde, ironwood, and cacti.

Access is through Interstate 8.

Description of the Table Top Wilderness Area Bdy., T. 8 S., R. 3 E., Gila and Salt River Meridian, Arizona

The following is for informational purposes only.

Beginning at the cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the Tp.

thence N. 89°57' E., 38.70 chs. dist. on record course, bet. secs. 18 and 19, to the witness cor. to the 1/4 sec. cor. of secs. 18 and 19;

thence N. 89°59′ E., 25.14 chs. dist., bet. secs. 18 and 19, to Angle Point 1, Tract 38;

thence N. 20°49' E., 6.75 chs. dist., to Angle Point 2, Tract 38.;

T. 8 S., R. 3 E., Gila and Salt River Meridian, Arizona

```
CHAINS
        thence N. 58°51' E., 6.26 chs. dist., to Angle Point 3,
             Tract 38:
        thence N. 22°31' E., 4.42 chs. dist., to Angle Point 4,
             Tract 38;
        thence N. 0°25' W., 7.53 chs. dist., to Angle Point 5,
             Tract 38;
                  9°07' E., 2.71 chs. dist., to Angle Point 6,
        thence N.
             Tract 38:
        thence N. 18°04' W., 2.42 chs. dist., to Angle Point 7,
             Tract 38:
        thence N. 9°12' E., 2.90 chs. dist., to Angle Point 8,
             Tract 38;
        thence N. 0°07' E., 8.68 chs. dist., to Angle Point 9,
             Tract 38;
        thence N. 32°25' E., 3.82 chs. dist., to Angle Point 10,
             Tract 38;
        thence N. 6°12' W., 7.26 chs. dist., to Angle Point 11,
             Tract 38:
        thence N. 11°35' W., 6.22 chs. dist., to Angle Point 12,
             Tract 38;
        thence N. 54°42′ W., 2.23 chs. dist., to Angle Point 13,
             Tract 38;
        thence N. 34°23′ W., 2.33 chs. dist., to Angle Point 14,
             Tract 38:
        thence N. 16°28' E., 5.66 chs. dist., to Angle Point 15,
             Tract 38;
        thence N. 42°47' E., 3.69 chs. dist., to Angle Point 16,
             Tract 38;
        thence S. 82°57' E., 3.88 chs. dist., to Angle Point 17,
             Tract 38;
        thence N. 67°51' E., 0.56 chs. dist., to Angle Point 18,
             Tract 38, identical with Angle Point 1, sec. 17, on the line
             bet. secs. 17 and 18;
        thence N. 67°51' E., 2.56 chs. dist., to Angle Point 2, sec. 17;
        thence S. 79°29' E., 2.95 chs. dist., to Angle Point 3, sec. 17;
        thence N. 69°30' E., 10.45 chs. dist., to Angle Point 4, sec. 17;
        thence N. 89°32' E., 2.35 chs. dist., to Angle Point 5, sec. 17;
        thence N. 12°59' E., 2.08 chs. dist., to Angle Point 6, sec. 17;
        thence N. 24°50' E., 5.51 chs. dist., to Angle Point 7, sec. 17;
        thence N. 1°31' W., 3.64 chs. dist., to Angle Point 8, sec. 17,
             identical with Angle Point 1, sec. 8, on the line bet. secs.
             8 and 17;
                   1°31' W., 11.80 chs. dist., to Angle Point 2, sec. 8;
        thence N.
                   2°05′ W.,
                              5.46 chs. dist., to Angle Point 3, sec. 8;
        thence N.
                             8.15 chs. dist., to Angle Point 4, sec. 8;
        thence N. 23°10' E.,
        thence N. 17°38' E., 4.37 chs. dist., to Angle Point 5, sec. 8;
        thence N. 68°03' W., 2.54 chs. dist., to Angle Point 6, sec. 8;
        thence S. 80°04' W.,
                              9.11 chs. dist., to Angle Point 7, sec. 8;
        thence S. 65°22' W., 5.37 chs. dist., to Angle Point 8, sec. 8;
        thence N. 56°46′ W., 3.13 chs. dist., to Angle Point 9, sec. 8;
        thence N. 83°01' W., 3.46 chs. dist., to Angle Point 10, sec. 8;
```

T. 8 S., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	thence S. 79°53'	W	1.91 chs.	dist., to	Angle Point	11. sec. 8.
	identical w	ith Ar		-	37, on the 1	-
	secs. 7 and thence S. 79°53'	-	3.99 chs.	dist to	Angle Point	20.
	Tract 37;	,	3.33 031	u.501, 00	7g	,
	thence N. 84°44'	W.,	4.35 chs.	dist., to	Angle Point	21,
	Tract 37; thence N. 87°06′	W.,	4.02 chs.	dist., to	Angle Point	22,
	Tract 37;					
	thence N. 87°25′ Tract 37;	W.,	3.64 cns.	dist., to	Angle Point	23,
	thence N. 40°36′	W.,	3.03 chs.	dist., to	Angle Point	24,
	Tract 37; thence N. 54°06′	W	1 26 chs	dist to	Angle Point	25
	Tract 37;	w.,	4.20 0115.	urst., to	Angle Form	23,
	thence N. 31°24'	W.,	5.66 chs.	dist., to	Angle Point	26,
	Tract 37; thence N. 52°14′	W	5.56 chs.	dist to	Angle Point	27.
	Tract 37;					
	thence N. 71°25′ Tract 37;	W.,	4.34 chs.	dist., to	Angle Point	28,
	thence N. 15°40'	W.,	2.18 chs.	dist., to	Angle Point	29,
	Tract 37; thence N. 72°20′	W	3 17 chs	dist to	Angle Point	30
	Tract 37;	и.,	J.17 Clis.	uist., to	Angle Form.	50,
	thence N. 28°32'	Ε.,	4.38 chs.	dist., to	Angle Point	31,
	Tract 37; thence S. 68°24′	Ε.,	3.86 chs.	dist., to	Angle Point	32,
	Tract 37;				_	
	thence S. 29°56' Tract 37;	W.,	2.46 chs.	dist., to	Angle Point	33,
	thence S. 4°30′	W.,	2.71 chs.	dist., to	Angle Point	34,
	Tract 37; thence S. 72°58′	F	4.07 chs.	dist. to	Angle Point	35.
	Tract 37;	,	4.07 01131	u1301, 00	Ang ic To mic .	
	thence S. 51°13′	Ε.,	6.18 chs.	dist., to	Angle Point	36,
	Tract 37; thence S. 31°12′	Ε.,	5.52 chs.	dist., to	Angle Point	37,
	Tract 37;	_	4.40			
	thence S. 54°19' Tract 37;	Ł.,	4.12 cns.	aist., to	Angle Point .	38,
	thence S. 43°03'	Ε.,	2.90 chs.	dist., to	Angle Point	39,
	Tract 37; thence S. 88°50'	Ε	3.36 chs.	dist to	Angle Point	40.
	Tract 37;				_	
	thence S. 87°20' Tract 37;	Ε.,	3.90 chs.	dist., to	Angle Point	41,
	thence S. 83°12'	Ε.,	3.95 chs.	dist., to	Angle Point	42 ,
•	Tract 37;					

T. 8 S., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	+ h = n = = N	700267 5	4 17 aba	44.4	Amaila Dadas	42
					Angle Point	
		secs. 7 and		ng le Point	12, sec. 8,	on the line
			-	dist to	Angle Doint	13, sec. 8;
					Angle Point	
					Angle Point	
					Angle Point	
				-	_	•
					Angle Point	
					Angle Point	
					Angle Point	
					Angle Point	
					Angle Point	
						22, sec. 8;
						23, sec. 8;
					Angle Point	
						25, sec. 8;
,					Angle Point	
			ingle Point	1, sec. 5,	, on the line	e pet. secs.
	5 and		0 08 che	dist to	Angle Point	2 sec 5.
}					Angle Point	
		•		-	Angle Point	-
					Angle Point	
					Angle Point	
					Angle Point	
					Angle Point	
					Angle Point	
						10, sec. 5;
						10, sec. 5;
						12, sec. 5;
		53°43′ W.,				12, sec. 5;
						14, sec. 5;
						15, sec. 5;
		-		-	_	16, sec. 5;
						17, sec. 5;
					Angle Point	
		55°54′ W.,			Angle Point	
		86°09′ W.,			_	20, sec. 5;
		23°58′ W.,				21, sec. 5;
		66°56′ W.,				22, sec. 5;
		3°35′ E.,				23, sec. 5;
		68°28′ W.,		•	_	24, sec. 5;
		61°34′ W.,		-	_	25, sec. 5;
		28°31′ W.,		-	_	26, sec. 5;
1		81°43′ W.,			-	27, sec. 5;
		7°41′ E.,				28, sec. 5;
		59°46′ E.,				29, sec. 5;
}		32°36′ E.,		-	_	30, sec. 5;
		64°05′ E.,			_	31, sec. 5;
		17°36′ E.,			Angle Point	
					Angle Point	
					_	34, sec. 5;
		J. 25 L.,	L.LT 0113.	a.s.,	Aligne To file	J+, JCO: J,

T. 8 S., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	thence S. 89°19′ E., 4.01 chs. dist., to Angle Point 35, sec. 5; thence N. 56°07′ E., 5.29 chs. dist., to Angle Point 36, sec. 5; thence N. 25°44′ E., 3.37 chs. dist., to Angle Point 37, sec. 5; thence N. 32°05′ E., 7.78 chs. dist., to Angle Point 38, sec. 5; thence N. 9°26′ W., 5.18 chs. dist., to Angle Point 39, sec. 5; thence N. 7°41′ E., 7.22 chs. dist., to Angle Point 40, sec. 5; thence N. 56°04′ E., 2.96 chs. dist., to Angle Point 41, sec. 5; thence N. 39°34′ E., 3.77 chs. dist., to Angle Point 42, sec. 5; thence N. 25°34′ E., 6.33 chs. dist., to Angle Point 43, sec. 5;
	thence N. 17°28' E., 9.48 chs. dist., to Angle Point 44, sec. 5, identical with Angle Point 1, Tract 38, T. 7 S., R. 3 E., on the line bet. secs. 5 and 32, on the N. bdy. of the Tp.;

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
W. William Foster	Surveying Technician
Mark R. Searles	Surveying Technician

CERTIFICATE OF SURVEY

I, Joe R. Salazar, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 8th day of April, 1996, I have dependently resurveyed a portion of the subdivisional lines and executed the metesand-bounds survey of the Table Top Wilderness Area Boundary, Township 8 South, Range 3 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

10/19/99
(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Arizona State Office Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and the metes-and-bounds survey of the Table Top Wilderness Area Boundary, Township 8 South, Range 3 East, Gila and Salt River Meridian, Arizona, executed by Joe R. Salazar, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

(Chief Cadastral Surveyor of Arizona)

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 8 S., R. 3 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.

(Date)