**ORIGINAL** 

# UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES, AND A PORTION OF THE

SUBDIVISION OF SECTION LINES IN SECTION 25,

THE SUBDIVISION OF THE SW 1/4 OF SECTION 25,

AND A METES-AND-BOUNDS DESCRIPTION OF A PARCEL OF LAND ACQUIRED

BY THE SALT RIVER PIMA MARICOPA INDIAN COMMUNITY IN SECTION 25,

TOWNSHIP 3 NORTH, RANGE 5 EAST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA.

#### **EXECUTED BY**

### Gordon R. Bubel, Cadastral Surveyor

Under Special Instructions dated January 7, 2015, approved January 7, 2015 and Supplemental Special Instructions dated February 12, 2015, approved February 12, 2015, which provided for the surveys included under Group No. 1141, and assignment instructions dated January 7, 2015.

Survey commenced February 25, 2015

Survey completed March 11, 2015

### INDEX DIAGRAM

TOWNSHIP 3 NORTH RANGE 5 EAST GILA & SALT RIVER MERIDIAN, ARIZONA

	6	5	4	3	2	1
	7	8	9	10	11	12
	18	17	16	15	14	13
	19	20	21	22	23	24
	7					
4	30	6 <b>29</b>	28	27	26	25 4
	5					
		16	15	13	11	5
	31	32	33	34	35	36 4

#### T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the east boundary, a portion of the subdivisional lines, and a portion of the subdivision of section lines in section 25, the subdivision of the SW 1/4 of section 25 and a metes-and-bounds description of a parcel of land acquired by the Salt River Pima Maricopa Indian Community in section 25, Township 3 North, Range 5 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

The east boundary of section 25, was surveyed by Sydney E. Blout in 1914 and resurveyed by Ty White and Claude F. Warner in 1950. The south boundary of section 25, which was identical with the north boundary of the Salt River Indian Reservation, was surveyed by L.D. Chillson in 1888 and resurveyed by Robert A. Farmer in 1911. The east half the south boundary of section 25, was resurveyed by Ty White and Claude F. Warner in 1950. The west half of the south boundary of section 25 was resurveyed by Gordon R. Bubel in 2008. The N. and W. boundaries of section 25 were surveyed by Sydney E. Blout in 1914 and resurveyed by Ty White and Claude F. Warner in 1950. The NE, SE and NW 1/4 sections of section 25, were subdivided by Ty White and Claude F. Warner in 1950. In 1995, Public Law 104-102, "Saddleback Mountain Arizona Settlement Act of 1995", was enacted. This law allowed for the acquisition of portions of section 25, for the Salt River Pima Maricopa Indian Community. In 1995, Robert J. Pecha, Arizona R.L.S. No. 21080, in compliance with provisions within Public Law 104-102, executed a survey in section 25, identifying the Salt River Pima Maricopa Indian Community acquired land.

The survey was executed in accordance with the specifications as set forth in the <u>Manual of Surveying Instructions</u>, (2009), the Special Instructions dated January 7, 2015 and Supplemental Special Instructions dated February 12, 2015, for Group Number 1141, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation R8 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

### T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona

#### CHAINS

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) AZTP TEMPE CORS ARP, SRP1 SALT RIVER CORS ARP and AZPA PEORIA FIREST 195 CORS ARP.

The NAD 83 (2011) (EPOCH: 2010.0000), geographic position of the corner of sections 25, 30, 31, and 36, on the east boundary of the township is as follows:

Latitude: 33°34'04.42" N. Longitude: 111°47'14.54" W.

The NAD 83 (2011) (EPOCH: 2010.0000), geographic position of the southwest 1/16 section corner of section 25, is as follows:

Latitude: 33°34'17.52" N. Longitude: 111°48'01.32" W.

The mean magnetic declination is 10 1/2° E.

### Dependent Resurvey of a Portion of the East Boundary, T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona

Restoring the resurvey executed by Ty White and Claude F. Warner, in 1950

Beginning at the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. T3N R5E R6E S25 S30 R5E T3N R6E S36 S31 SRIR 1911 1950. Add the marks 2015 to the brass cap.

Cor. is located 42 lks. N. of a barbed wire fence, bears E. and W.

N. 0°03' W., bet. secs. 25 and 30, on the E. bdy. of the Tp.

Within the Salt River Pima Maricopa Indian Community, over nearly level land.

- 10.010 Point for the S-S 1/64 sec. cor. of secs. 25 and 30, at proportionate dist., there is no remaining evidence of the 1950 wood post, not monumented.
- The S. 1/16 sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. S 1/16 S25 S30 1950, with a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high to the W. Add the marks 2015 to the brass cap.

### Dependent Resurvey of a Portion of the Subdivisional Lines, T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona

	Restoring the resurvey executed by White and Warner in 1950 and the resurvey executed by Gordon R. Bubel in 2008.			
	From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of t Tp., hereinbefore described.			
	N. 89°59' W., bet. secs. 25 and 36.			
	Within the Salt River Pima Maricopa Indian Community, ov nearly level land.			
9.978	Point for the E-E 1/64 sec. cor. of secs. 25 and 36, proportionate dist., there is no remaining evidence of the 19 wood post, not monumented.			
14.966	Point accepted for the W-E-E 1/256 sec. cor. of secs. 25 and 36 monumented with a rebar, 1/2 in. diam., firmly set, flush wit the surface, origin unknown.			
	Cor. is located 43 lks. N. of a barbed wire fence, bears E. and W			
	N. 89°58' W., beginning new measurement.			
4.985	The E. 1/16 sec. cor. of secs. 25 and 36, monumented with iron post, 1 in. diam., firmly set, projecting 14 ins. about ground, with brass cap mkd.			
	N			
	S 25 1/16 ——			
	S 36 SRIR			
	1911			
	amend the brass cap to read:			
	T 3 N R 5 E			
	S 25 E 1/16 ——			
	S 36 SRIR			
	1911 2015			
	Build a mound of stone, 2 $1/2$ ft. base, to top, around the ir post.			

### Dependent Resurvey of a Portion of the Subdivisional Lines, T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona

	T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona						
CHAINS							
	N. 89°53' W., beginning new measurement.						
20.003	The 1/4 sec. cor. of secs. 25 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with a mound of stone 2 ft. base, 1 ft. high, to the N., brass cap mkd. S25 1/4 T3N R6E S36 SRIR 1911 2008.						
	Add the marks 2015 to the brass cap.						
	Cor. is located 46 lks. N. of a barbed wire fence, bears E. and W.						
	N. 89°58' W., beginning new measurement.						
10.382	A rebar, 1/2 in. diam., firmly set, flush with the surface.						
13.426	A witness point, on the SRPMIC bdy., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, in a mound of stone 2 1/2 ft. base, to top, with aluminum cap mkd. WP T3N R5E S25 S36 SRPMIC 2008.						
	Add the marks 2015 to the brass cap.						
	Cor. is located 46 lks. N. of a barbed wire fence, bears E. and W.						
	N. 89°58' W., beginning new measurement.						
	On the N. bdy. of the Salt River Pima Maricopa Indian Community.						
6.579	The W. 1/16 sec. cor. of secs. 25 and 36, monumented with an iron post, 1 ins, diam., firmly set, projecting 17 ins. above ground, encircled with a collar of stone with brass cap mkd. No 2 T3N R5E S25 1/16 SRIR S36 1911 2008.						
	Add the marks 2015 to the brass cap.						
	Cor. is located 44 lks. N. of a barbed wire fence, bears E. and W.						

## Dependent Resurvey of a Portion of the Subdivision of Section Lines in Section 25, T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona

CITA TATO	T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona					
CHAINS						
	Restoring the survey executed by Ty White and Claude F. Warner, in 1950					
	From the 1/4 sec. cor. of secs. 25 and 36, hereinbefore described.					
	N. 0°04' W., on the N. and S. center line of sec. 25.					
	Within the Salt River Pima Maricopa Indian Community, over nearly level land.					
10.001	Point accepted for the C-S-S 1/64 sec. cor. of sec. 25, monumented with a rebar, 1/2 in. diam., firmly set, 2 ins. below the surface, origin unknown.					
	N. 0°04' W., beginning new measurement.					
5.005	Point accepted for the C-N-S-S 1/256 sec. cor. of sec. 25, monumented with a rebar, 3/8 in. diam., firmly set, flush with the surface, origin unknown.					
	N. 0°04' W., beginning new measurement.					
4.992	The center S. 1/16 sec. cor. of sec. 25, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. C S 1/16 C S25 1950, with a steel fence post alongside.					
	Add the marks 2015 to the brass cap, raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W. of the cor.					
	N. 0°03' W., beginning new measurement.					
	On the Salt River Pima Maricopa Indian Community boundary.					
5.004	Point accepted for the C-S-N-S 1/256 sec. cor. of sec. 25, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, 17 ins. in the ground, origin unknown.					
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.					
	T 3 N R 6 E					
	C-S-N-S 1/256					
	SRPMIC S30 2015					

## Dependent Resurvey of a Portion of the Subdivision of Section Lines in Section 25, T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona

	1. 5 N., R. 5 E., GIIA AND SAIL RIVEL MELIDIAN, ALIZONA
CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post, insert the rebar within the stainless steel post.
	N. 0°03' W., beginning new measurement.
	Across private lands.
14.996	The center 1/4 sec. cor. of secs. 25, reestablished by Ted Frank Poole, Arizona R.L.S. No. 8607 in 1995, according to an unrecorded survey, obtained from the Maricopa County Department of Transportation. Monumented with a rebar, 1/2 in. diam., firmly set, 4 ins. below the surface, with an affixed, damaged and unreadable plastic cap. Accepted as a careful and faithful reestablishment of the orig. cor. position.
	From the S. 1/16 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., hereinbefore described.
	N. 89°59' W., on the E. and W. center line of the SE 1/4 of sec. 25, identical with the Salt River Pima Maricopa Indian Community boundary.
9.987	Point for the C-E-SE 1/64 sec. cor. of sec. 25, at proportionate dist., there is no remaining evidence of the 1950 wood post. Not remonumented.
19.974	The SE 1/16 sec. cor. of sec. 25, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SE 1/16 S25 1950. A mound of stone, 3 ft. base 1 1/2 ft. high, is alongside and W. of the cor.
	Add the marks 2015 to the brass cap.
	Cor. is located 23 lks. S. of an iron rail fence, bears E. and W.
	N. 89°56' W., beginning new measurement.
19.984	The center S. 1/16 sec. cor. of sec. 25.

### Subdivision of the SW 1/4 of Section 25, T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona

	T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona
CHAINS	
	From the W. $1/16$ sec. cor. of secs. 25 and 36, hereinbefore described.
	N. 0°02' W., on the N. and S. center line of the SW $1/4$ of sec. 25.
	Across a portion of Reach 12, Central Arizona Project, Granite Reef Aqueduct.
4.073	Point accepted for an angle point, on the boundary of the Salt River Pima Maricopa Indian Community. Monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, 15 ins. in the ground, with an attached, damaged and illegible aluminum tag. Established by Ronald Book, Arizona R.L.S. No. 18540, date unknown. Referenced in 1995 by Robert J. Pecha, Arizona R.L.S. No. 21080, in the survey recorded in Book 407, Page 48, Maricopa County Recorder's Office.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T 3 N R 5 E
	AP SRPMIC
	S25
	2015
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post, insert the rebar inside the stainless steel post.
	From this cor. point, the WP on the line bet. secs. 25 and 36, bears S. 58°14' E., 7.742 ch. dist., hereinbefore described.
	Cor. is located 27 lks. W. of a track road, bears N. and S.
	N. 0°05' W., beginning new measurement.
	On the Salt River Pima Maricopa Indian Community boundary.
5.933	Point accepted for the C-S-SW 1/64 sec. cor. of sec. 25, monumented with an open end iron pipe, 7/8 in. diam., firmly set, projecting 5 ins. above ground, origin unknown.
	Encircle the iron pipe with a collar of stone.

Subdivision of the SW 1/4 of Section 25, T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona

	T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona					
CHAINS						
	North, beginning new measurement.					
	On the Salt River Pima Maricopa Indian Community boundary.					
2.502	A rebar, 1/2 in. diam., firmly set, projecting 4 ins. above ground.					
4.347	A rebar, 5/8 in. diam., firmly set, projecting 3 ins. above ground, with attached 2 in. diam., aluminum cap mkd. CAWCD GR-12-74.6 RLS 18540.					
4.998	Point accepted for the C-N-S-SW 1/256 sec. cor. of sec. 25, monumented with an open end iron pipe, 7/8 in. diam., firmly set, projecting 18 ins. above ground, origin unknown.					
	Build a mound of stone, 3 ft. base, 1 ft. high, around the iron pipe.					
	From this cor., a rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground, with an attached, damaged and unreadable plastic cap bears N. 29°11' W., 0.8 lks. dist.					
	N. 0°09' W., beginning new measurement.					
	On the Salt River Pima Maricopa Indian Community boundary.					
2.948	A rebar, 1/2 in. diam., firmly set flush with the surface, attached 1 in. diam., plastic cap mkd. RLS 27749.					
4.999	Point accepted for the SW 1/16 sec. cor. of sec. 25, on the boundary of the Salt River Pima Maricopa Indian Community. Monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, 17 ins. in the ground. Established by Ronald Book, Arizona R.L.S. No. 18540, date unknown. Referenced in 1995 by Robert J. Pecha, Arizona R.L.S. No. 21080, in the survey recorded in Book 407, Page 48, Maricopa County Recorder's Office.					
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.					
	T3NR5E					
	SW 1/16 S 25					
	SRPMIC					
	2015					
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post, insert the rebar inside the stainless steel post.					

	Subdivision of the SW 1/4 of Section 25, T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona							
CHAINS								
	From this cor., a rebar, 1/2 in. diam., firmly set, projecting 1 ins. above ground, with attached, 1 in. diam. plastic cap, mkd. LS 24523, bears N. 9°59' E., 0.9 lks. dist.							
	From this same cor. point, a rebar 1/2 in. diam., firmly set, 3 ins. below the surface, bears N. 87°54' E., 11.0 lks. dist.							
	The center W. 1/16 sec. cor. of sec. 25 and the S. 1/16 sec. cor. of secs. 25 and 26, were searched for, nothing found.							
	Cor. is located, 20 lks. E. of an iron rail fence, bears E. and W.							
	From the center S. 1/16 sec. cor. of sec. 25, hereinbefore described.							
	S. 89°55' W., on the E. and W. center line of the SW 1/4 of sec. 25.							
	Within the Salt River Pima Maricopa Community.							
9.631	Point accepted for an angle point, on the boundary of the Salt River Pima Maricopa Indian Community. Monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, 18 ins. in the ground, with attached 1 in. diam., plastic cap mkd. RLS 32790. Established by Richard A. Klebieko, Arizona R.L.S. No. 32790, date unknown, not recorded.							
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.							
	T 3 N R 5 E							
	AP SRPMIC S25 2015							
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post, insert the rebar inside the stainless steel post.							
	Cor. is located on the east right-of-way of 131st St., City of Scottsdale.							
	S. 89°55' W., beginning new measurement.							
	On the Salt River Pima Maricopa Indian Community boundary.							
0.379	Point accepted for the C-E-SW 1/64 sec. cor. of sec. 25, monumented with a 3 ins. diam. aluminum disk, unmarked, set in concrete, flush with the pavement of 131st St., City of Scottsdale bears N and S							

Scottsdale bears N. and S.

### Subdivision of the SW 1/4 of Section 25, T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona

	T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona						
CHAINS							
	Mark the aluminum disk to read:						
	T 3 N R 5 E						
	S 25 C-E-SW						
	1/64						
	SRPMIC						
	2015						
	Cor. is located, 4.7 lks. W. of east edge of pavement, and 2.7 lks. N. of the south end of pavement, 131st St., City of Scottsdale.						
	N. 89°49' W., beginning new measurement.						
0.30	West edge of pavement 131st St., city of Scottsdale.						
2.726	A rebar, 1/2 in. diam., flush with the surface.						
5.074	A rebar, 1/2 in. diam., flush with the surface.						
6.478	From this point, a rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground, bears S., 4.4 lks. dist.						
6.516	From this point, an open end iron pipe, 7/8 in. diam., firmly set, projecting 15 ins. above ground, bears N., 1.4 lks. dist.						
7.726	A rebar, 1/2 in. diam., flush with the surface, with attached, broken and unreadable plastic cap.						
9.996	The SW 1/16 sec. cor. of sec. 25.						
	From the C-S-N-S 1/256 sec. cor. of sec. 25, hereinbefore described.						
	N. 89°57' W., on the E. and W. center line of the SE 1/4 of the NE 1/4 of the SW 1/4 of sec. 25.						
	On the Salt River Pima Maricopa Indian Community boundary.						
4.714	Intersect the easterly side of an asphalt parking area, bears S. 28°50' W., for 9.4 lks., thence S. 16°48' W., for 42.3 lks. dist., to the SE cor., located within the Salt River Pima Maricopa Community.						
5.440	Intersect the westerly side of an asphalt parking area, bears S. 3°56' W., for 36.8 lks., to the SW cor., located within the Salt River Pima Maricopa Community.						

### Subdivision of the SW 1/4 of Section 25, T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona

	1. J R., R. J B., GIIA and Baic RIVEL MILITAIN, ALIZONA						
CHAINS							
9.632	Point accepted for an angle point, on the boundary of the Siver Pima Maricopa Indian Community. Monumented with a relation land, 1/2 in. diam., firmly set, 18 ins. in the growith attached 1 in. diam., plastic cap mkd. RLS 327 Established by Richard A. Klebieko, Arizona R.L.S. No. 327 date unknown, not recorded.						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.						
	T3NR5E						
	AP						
	SRPMIC S25						
	2015						
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post, insert the rebar inside the stainless steel post.						
	Cor. is located on the east right-of-way of 131st St., City of Scottsdale.						
	From this cor. point, the angle point at the intersection of the east right-of-way of 131st., City of Scottsdale with the E. and W. center line of the SW 1/4 of sec. 25, bears S. 0°04' E., 5.027 ch. dist., hereinbefore described.						
	N. 89°57' W., beginning new measurement.						
	Over patented lands.						
0.379	Point accepted for the C-S-NE-SW 1/256 sec. cor. of sec. 25, monumented with a 3 ins. diam., brass disk, marked CITY OF SCOTTSDALE, set in concrete, flush with the pavement of 131st St., City of Scottsdale, bears N. and S						
	Cor. is located, 3.5 lks. W. of east edge of pavement, 131st St., City of Scottsdale.						
	S. 0°04' E., on a portion of the N. and S. center line of the NE $1/4$ of the SW $1/4$ of sec. 25.						
	Over patented lands, identical with the center line of 131st St., City of Scottsdale.						
5.028	The C-E-SW 1/64 sec. cor. of sec. 25, hereinbefore described.						

## Metes-and-Bounds Description in Section 25, T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona

	T. 3/N., R. 5 E., Gila and Salt River Meridian, Arizona
CHAINS	
	The following is a metes-and-bounds description of the lands acquired by the Salt River Pima Maricopa Indian Community, by way of Public Law 104-102.
	Beginning at the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.
	thence N. 0°03' W., bet. secs. 25 and 30, 20.02 chs. dist. to the S. 1/16 sec. cor. of secs. 25 and 30; thence N. 89°59' W., on the E. and W. center line of the SE 1/4 of sec. 25, 19.974 chs. dist., to the SE 1/16 sec. cor. of
	sec. 25; thence N. 89°56' W., continuing on the E. and W. center line of the SE 1/4 of sec. 25, 19.984 chs. dist., to the center S. 1/16 sec. cor. of sec. 25;
	thence N. 0°03' W., on the N. and S. center line of sec. 25, 5.004 chs. dist., to the C-S-N-S 1/256 sec. cor. of sec. 25; thence N. 89°57' W., on the SE 1/4 of the NE 1/4 of the SW 1/4 of sec. 25, 9.632 chs. dist., to an angle point on the
	east right-of-way of 136th St., City of Scottsdale; thence S. 0°04' E., on the east right-of-way of 136th St., City of Scottsdale, 5.027 chs. dist., to an angle point, on the E. and W. center line of the SW 1/4 of sec. 25;
	thence S. 89°55' W., on the E. and W. center line of the SW 1/4 of sec. 25, 0.379 chs. dist., to the C-E-SW 1/64 sec. cor. of sec. 25;
	thence N. 89°49' W., continuing on the E. and W. center of the SW 1/4 of sec. 25, 9.996 chs. dist., to the SW 1/16 sec. cor. of sec. 25;
	thence S. 0°09' E., on the N. and S. center line of the SW 1/4 of sec. 25, 4.999 chs. dist. to the C-N-S-SW 1/256 sec. cor. of sec. 25;
	thence South, continuing on the N. and S. center line of the SW 1/4 of sec. 25, 4.998 chs. dist. to the C-S-SW 1/64 sec. cor. of sec. 25;
	thence S. 0°05' E., continuing on the N. and S. center line of the SW 1/4 of sec. 25, 5.933 chs. dist., to an angle point at intersection with Reach 12, Granite Reef Aqueduct, Central Arizona Project;
	thence S. 58°14' E., on Reach 12, Granite Reef Aqueduct, Central Arizona Project, 7.742 chs. dist., to a witness point at intersection with the line bet. secs. 25 and 36; thence S. 89°58' E., on the line bet. secs. 25 and 36, 13.426
	chs. dist., to the 1/4 sec. cor. of secs. 25 and 36; thence S. 89°53' E., continuing on the line bet. secs. 25 and 36, 20.003 chs. dist., to the E. 1/16 sec. cor. of secs.
	25 and 36; thence S. 89°58' E., continuing on the line bet. secs. 25 and 36, 4.985 chs. dist., to the W-E-E 1/256 sec. cor. of secs. 25 and 36;
	thence S. 89°59' E., continuing on the line bet. secs. 25 and 36, 14.966 chs. dist., to the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp. and point of beginning.

### Metes-and-Bounds Description in Section 25, T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona

ri,	J 7	ŀΤ	M	C
L	1 <i>F</i>	$_{\perp}$	1/1	D

#### GENERAL DESCRIPTION

The survey is located adjacent to and within the City of Scottsdale, Arizona. Access is by way of Shea Boulevard and 136th Street.

The terrain is nearly level, timber consists of palo verde, ironwood and saguaro, with undergrowth of chola, creosote and brittlebush. The elevation ranges from 1500 ft. to 1560 ft. above sea level.

A residential paved parking area, occupying 1224 square feet +/- on the Salt River Pima Indian Maricopa Community, is located in the S 1/2 of the SE 1/4 of the NE 1/4 of the SW 1/4 of section 25.

The area of land acquired by the Salt River Pima Maricopa Indian Community via Public Law 104-102 in section 25, is 83.4 acres +/-.

The mean magnetic declination of  $10\ 1/2^\circ$  E. was derived from the National Oceanic and Atmospheric Administration, Magnetic Field Calculator, utilizing the World Magnetic Model for Epoch 2015 for the dates of survey.

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

### FIELD ASSISTANTS

TIELD ASSISTANTS	
NAMES	CAPACITY
Richard A. Klebieko	Land Surveyor, SRPMIC
Carlos A. Payan	Range Tech. (Fire), BLM
Keith Andrews	Survey Tech. SRPMIC

#### CERTIFICATE OF SURVEY

I, Gordon R. Bubel, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 7th day of January 2015, and the Supplemental Special Instructions bearing date of the 12th day of February 2015, I have dependently resurveyed a portion of the east boundary, a portion of the subdivisional lines and a portion of the subdivision of section lines in section 25, subdivided the southwest quarter of section 25, and described by metes-and-bounds the land acquired by the Salt River Pima Maricopa Indian Community in section 25, Township 3 North, Range 5 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Surveying Instructions, (2009), and in specific manner described in the foregoing field notes.

OCT. 13, 2015
(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the east boundary, a portion of the subdivisional lines, and a portion of the subdivision of section lines in section 25, the subdivision of the southwest quarter of section 25, and a metes-and-bounds description of lands acquired by the Salt River Pima Maricopa Indian Community in section 25, Township 3 North, Range 5 East, Gila and Salt River Meridian, in the State of Arizona, executed by Gordon R. Bubel, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

12/10/2015
(Date) (Chief Cadastral Surveyor of Arizona)

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above described surveys in T. 3 N., R. 5 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.

(Date) (Chief Cadastral Surveyor of Arizona)