

Converse County Oil and Gas Plan of Development

August 12, 2014



Prepared by



THIS PAGE INTENTIONALLY LEFT BLANK.

CONTENTS

SECTION 1 - Introduction	1
1.1 Project Location and Background	1
1.2 Overview of the Proposed Action	1
1.3 Purpose and Need	2
SECTION 2 - Project Description	5
2.1 Introduction	5
2.2 Description of the Project Area	5
2.3 Existing and Planned Oil and Gas Development in the Project Area	5
2.3.1 Introduction	5
2.3.2 Existing Oil and Gas Infrastructure	5
2.3.3 Planned (but not constructed) Oil and Gas Development in the Project Area	7
2.4 Converse County Project Proposed Action	10
2.4.1 Project Development	12
2.4.2 Project Workforce and Transportation	27
2.5 References	30

LIST OF TABLES

Table 2-1. Oil and Gas Well Type and Status.....	6
Table 2-2. Summary of Existing and Planned Surface Disturbance	8
Table 2-3. Proposed Action Summary of New Surface Disturbance	11
Table 2-4. Employment Estimates.....	28
Table 2-5. Daily Average Project Vehicle Traffic Trips per Well	29

LIST OF FIGURES

Figure 1-1. Converse County Oil and Gas Project Area	3
Figure 2-1. Example Drilling and Completion Horizontal Well Pad Layout (during drilling).....	16
Figure 2-2. Example Drilling and Completion Horizontal Well Pad Layout (during production)	17
Figure 2-3. Example Production Only Well Pad Layout	18

ACRONYMS AND ABBREVIATIONS

Anadarko	Anadarko Petroleum Company
APD	Application for Permit to Drill
AQD	Air Quality Department
BACT	Best Available Control Technology
BLM	Bureau of Land Management
CBNG	Coalbed Natural Gas
CFO	Casper Field Office
CFR	Code of Federal Regulations
Chesapeake	Chesapeake Energy Corporation
EA	Environmental Assessment
EIS	Environmental Impact Statement
EOG	EOG Resources, Inc.
EPA	Environmental Protection Agency
hp	horsepower
IM	Instruction Memorandum
MSDS	Material Safety Data Sheet
NEPA	National Environmental Policy Act of 1969
NOS	Notice of Staking
OG	Operator Group
POD	Plan of Development
RCRA	Resource Conservation and Recovery Act
RKI	RKI Exploration and Production, LLC
ROW	Right-of-Way
Samson	Samson Resources
SARA	Superfund Amendments and Reauthorization Act
SM	SM Energy
SPCC	Spill Prevention Control and Countermeasures
TBNG	Thunder Basin National Grassland
USFS	U.S. Forest Service
WDEQ	Wyoming Department of Environmental Quality
WOGCC	Wyoming Oil and Gas Conservation Commission

SECTION 1 - INTRODUCTION

1.1 Project Location and Background

This comprehensive Plan of Development (POD) presents the detailed information necessary to understand the full-field oil and natural gas development project proposed by the Operator Group (OG). The OG is comprised of Anadarko Petroleum Company (Anadarko), Chesapeake Energy Corporation (Chesapeake), EOG Resources, Inc., (EOG), RKI Exploration and Production (RKI), Samson Resources (Samson), and SM Energy (SM) as well as representing the interests of other operators within the project area.

The Converse County Project Area (“project area”) encompasses 1,501,707 acres, including 88,423 acres of public lands administered by the Bureau of Land Management (BLM) Casper Field Office (CFO), 100,966 acres of land administered by the State of Wyoming, 63,886 acres of Thunder Basin National Grasslands, 1,246,918 acres of private land, and 1,514 acres of land under water. The mineral estate in the project area is comprised of 964,525 acres of federal mineral estate and 537,182 acres of non-federal mineral estate of which approximately 345,000 is State-owned, and is generally located within Townships 32 through 40 North, Ranges 67 through 76 West, 6th Principal Meridian in Converse County, Wyoming (see **Figure 1**). The project area is located entirely in Converse County, Wyoming, with its northern boundary being the Campbell County line. As evidenced by the acreage numbers listed, the majority of the federal mineral estate (808,154 acres) is located below private surface lands, in what is called a “split-estate” situation.

1.2 Overview of the Proposed Action

The Proposed Action is to drill up to 5,000 oil and gas wells over 10 years. Although actual operations are subject to change as the project proceeds, the OG would drill wells at an average rate of approximately 500 wells per year for 10 years. To the greatest extent possible, the OG intends to conduct drilling and development operations within the project area on a year-round basis in order to maximize the use of horizontal development from multi-well pads. As part of this Plan of Development, the OG is seeking approval from the BLM to waive discretionary timing limitations on a programmatic basis (i.e., several wells at a time for extended periods of time). Without this waiver, the application of timing limitations would force members of the OG to move drilling rigs in and out of areas during portions of the year, which would increase operations costs, decrease efficiencies, and potentially increase impacts to wildlife and other sensitive resources.

Project construction would generally include well pads, roads, pipelines, power lines, compressor stations, and ancillary facilities. In addition, the OG could drill a limited number of vertical exploratory oil and gas wells; these vertical wells are captured in the 5,000 oil and gas well count and surface disturbance estimates and would not change the total number of wells or pads. The total number of wells drilled, as well as the annual drilling rate, would depend on factors largely outside the control of the OG such as new geologic information and associated successes, engineering technological development, economic factors, regulatory permitting, availability of equipment and a trained workforce, performance of commodity markets, contract lease, and unit stipulations and restrictions.

The anticipated initial drilling and completion pad size would be up to 12 acres; however, individual pad sizes may vary based on the number of wells per pad and constraints related to lease/landowner agreements, operational safety, and topography. The number of wells drilled from each pad would vary from 1 to 16. If productive, the portions of the well pad not needed for routine operations would be reclaimed to reduce surface disturbance to an average of 6 acres for the life of the wells on the pad. After the last well is plugged and abandoned, the pad would be fully reclaimed. Estimated initial (short-term) and post-interim reclamation (long-term) surface disturbances from the 1,500 proposed multi-well pads and all associated infrastructure are 53,495 acres and 21,288 acres respectively. The total estimated long-term surface disturbance for the Proposed Action would be approximately 1 percent of the project area.

Types of Surface Disturbance


Short-term: Initial (peak) disturbance during construction

Long-term: Disturbance that is not reclaimed following initial construction or after drilling/completion

1.3 Purpose and Need

The purpose of the Proposed Action is to allow the OG to conduct drilling and development operations on a year-round basis, produce, and market oil, natural gas, and associated hydrocarbon products, pursuant to their rights and obligations under existing oil and gas leases issued by the BLM, State of Wyoming, and private mineral owners. The BLM oil and gas leasing program encourages development of domestic oil and gas reserves, consistent with the BLM's multiple-use mission. The oil and gas resources produced from this project are needed to meet national domestic energy demand.

Figure 1-1. Converse County Oil and Gas Project Area



THIS PAGE INTENTIONALLY LEFT BLANK.

SECTION 2 - PROJECT DESCRIPTION

2.1 Introduction

This section defines the project area boundaries, describes the existing and planned oil and gas facilities present within the project area, and presents the OG's Proposed Action. It also includes standard development and production activities to facilitate understanding of how project elements would be constructed and operated.

2.2 Description of the Project Area

Topography ranges from steep rugged rock outcrops to relatively gentle slopes. Elevations within the project area range from approximately 4,800 to 6,300 feet above mean sea level. The project area encompasses a number of physiographic provinces and is located within the Platte River drainage system. The area has historically been used for livestock grazing, oil and gas development, wildlife habitat, and recreation. This area provides summer and fall grazing for cattle, sheep, and horses. The area has also been the site of historic and ongoing oil and gas development. The OG and other operators active in the project area continue to implement approved oil and gas development, including drilling new wells and constructing new infrastructure.

2.3 Existing and Planned Oil and Gas Development in the Project Area

2.3.1 Introduction

This section describes existing and planned oil and gas development in the project area. Existing development is defined as what is currently on the ground. Planned development has either already been approved by other permitting mechanisms (including National Environmental Policy Act of 1969 [NEPA] and Application for Permit to Drill [APD] approval) and will be implemented before the end of 2017, or it is anticipated to be approved before the end of 2017. Existing and planned oil and gas infrastructure forms the basis for current and ongoing operations and serves to inform the OG's Proposed Action, which uses this infrastructure to the extent practical in its full-field development.

2.3.2 Existing Oil and Gas Infrastructure

The project area is vast in scale and scope, and numerous small and large operators have ongoing operations in the area. This section uses the best available information from a number of, primarily, public sources to describe the existing oil and gas development in the project area. The use of public information (e.g., oil and gas well data from the Wyoming Oil and Gas Conservation Commission [WOGCC]) provides a more complete picture of existing conditions because it includes information for operators who may not be part of the OG and whose wells and facilities could be missed if only internal, OG data were employed. Information from

publicly available sources has been augmented with additional information directly from the OG where publicly available data is lacking.

As of July 2014, the WOGCC database contained approximately 3,014 records for existing and permitted wells in the project area, including approximately 2,729 oil wells, 189 gas wells, 29 disposal wells, 27 injector (water flood) wells, 3 monitoring wells, and 9 unclassified wells. The database identified 1,234 wells as under active development or producing and 307 wells with WOGCC permits to drill. The remaining wells are inactive or not-producing (e.g., shut-in, temporarily abandoned, permanently abandoned), or their status is unknown. Table 2-1 summarizes the type and status of wells in the project area. Wells with approved WOGCC permits to drill may still require additional approvals prior to drilling, especially for wells that require access to federal surface or mineral estate. The majority of existing wells in the project area are vertical wells (2,269 or 75%), although horizontal (644 or 21%) and directional wells (35 or 1%) have been drilled or are permitted in some areas. Existing and permitted wells in the project area include various combinations of federal, state, and fee ownership of mineral and surface estate, with the most common being fee surface and federal minerals (1,055 or 36%) and fee surface and minerals (850 or 29%).

Existing wells in the project area are accessed by the public road network (e.g., county roads) and existing oil and gas access roads. Oil and gas products are either transported via truck or via crude oil and natural gas pipelines to central processing facilities.

According to the Wyoming Pipeline Authority, rig counts across Wyoming have fluctuated between 40 and 70, with a high in December 2011 and a low in April 2012 (Wyoming State Pipeline Authority 2014). Data specific to Converse County indicates that there have been up to two dozen rigs active in the project area between April and June 2014.

Table 2-1. Oil and Gas Well Type and Status

WELL STATUS	WELL CLASS						TOTAL
	OIL	GAS	DISPOSAL	INJECTOR	OTHER	MONITORING	
<i>Inactive, Not-Producing</i>	1,295	112	14	16	18	2	1,457
<i>Active, Producing</i>	1,128	72	13	11	9	1	1,234
<i>Permit to Drill</i>	303	1	2	0	1	0	307
<i>Unknown Status</i>	3	4	0	0	0	0	7
Total	2,729	189	29	27	28	3	3,005

Source: WOGCC 2014

Note: Well class and status categories from WOGCC database were grouped according to the row and column headings in the table for ease of interpretation.

2.3.2.1 Access/Roads

There are more than 6,756 miles of existing roads in the project area, including approximately 236 miles of State and Federal Highways, 299 miles of county roads, 1,261 miles of light duty roads, and 4,960 miles of rough bladed and two-track roads (BLM 2013a). In addition, the project area is crossed by approximately 96 miles of existing rail lines. These roads and railroads serve a variety of resource purposes, including oil and gas development and production. For purposes of reporting in this document and consistency with the Proposed Action, only certain portion of these roads are assumed to support oil and gas development (see Table 2-2); to be consistent with the Proposed Action, the OG has assumed an average of one mile of access road per existing well pad.

2.3.2.2 Pipeline and Electrical Supply Infrastructure

Existing linear facilities in the project area include 184 miles of gas pipelines. See Table 2-2 for additional details.

2.3.2.3 Powerlines

Rocky Mountain Power provides electricity to the majority of the Project Area. This power provider owns and operates approximately 115 miles of overhead transmission lines (>35 kV), which is consistent with transmission line data available from Platts (Rocky Mountain Power 2013 and Platts 2014). Additionally, there are approximately 492 miles of overhead and 28 miles of buried transmission lines (<35 kV) (RMP 2013). Niobrara Electric services the southeast corner of the Project Area; the OG has been in contact with Niobrara and will provide information as it becomes available.

2.3.3 Planned (but not constructed) Oil and Gas Development in the Project Area

In addition to existing development, planned drilling and completion of oil and gas development wells and infrastructure would continue in the project area through 2017 (anticipated Converse County project initiation or Record of Decision). This planned development is described below and summarized in Table 2-2. Planned development includes facilities disclosed in NEPA documents or approved by other agencies but not yet constructed. Oil and gas development within the project area is still in the exploration and delineation phase; as a result, the exact location of many of the planned but not constructed wells, roads, pipelines, and related infrastructure is unknown at this time. The information included in this section is therefore based on the best available information and estimates developed by the OG.

2.3.3.1 Operator Group Field Development Plan

Planned ongoing oil and natural gas development in the project area includes those facilities described in NEPA documents from the following previously approved or proposed development projects:

- ▲ Spearhead Ranch Environmental Assessment (EA) (56 to 224 wells on 56 well pads)
- ▲ Highland Loop Road EA (37 to 148 wells on 37 well pads)

- ▲ East Converse EA (18 to 72 wells on 18 well pads)
- ▲ Hornbuckle EA (288 wells on 48 well pads)
- ▲ Powder River Basin Oil and Gas Project Environmental Impact Statement (EIS) (up to 150 wells on 40 well pads)
- ▲ Scott Field EA (150 wells on 40 well pads)
- ▲ In or near Douglas Core Area EAs - Proposed (up to 150 wells on 25+ well pads)
- ▲ Mohawk EA – Proposed (up to 32 wells on 7 well pads)

2.3.3.2 Access/Roads

Access to the planned well and production pad locations would require construction of approximately 221 miles of new roads, comprised of collector roads, which will provide primary access to large blocks of land in the project area, and well pad access roads (see Table 2-2).

2.3.3.3 Wells and Associated Infrastructure

Planned development would result in ongoing drilling, completion, and construction of wells and associated infrastructure. Table 2-2 identifies those existing and planned oil and gas facilities present or anticipated within the project area by the end of 2017 and their associated surface disturbance.

Table 2-2. Summary of Existing and Planned Surface Disturbance

FACILITY	EXISTING AS OF 2013 ²			PLANNED BEFORE THE END OF 2017 ²		
	NUMBER OR MILES	SIZE OR WIDTH	EXISTING LONG-TERM SURFACE DISTURBANCE (ACRES)	NUMBER OR MILES	SIZE OR WIDTH	ESTIMATED LONG-TERM SURFACE DISTURBANCE (ACRES)
Wells and Pads	(#)	(acres)		(#)	(acres)	
Horizontal Wells/Well Pads	537/537 ⁴	6 ⁵	3,222	1,048/271	6	1,116
Vertical Wells/Well Pads	2,264/2,264 ⁴	1.5 ⁵	3,396	15/15	1.5	22.5
CBNG Wells/Well Pads	60/60 ⁴	0.2 ⁵	12	0	0	0
Disposal Wells/Well Pads	29/29	10 ⁵	290	0	0	0
Production Pads	67	5 ⁵	335	20	5	100
Well Pad Subtotal	-	-	7,255	-	-	1,239

Table 2-2. Summary of Existing and Planned Surface Disturbance

FACILITY	EXISTING AS OF 2013 ²			PLANNED BEFORE THE END OF 2017 ²		
	NUMBER OR MILES	SIZE OR WIDTH	EXISTING LONG-TERM SURFACE DISTURBANCE (ACRES)	NUMBER OR MILES	SIZE OR WIDTH	ESTIMATED LONG-TERM SURFACE DISTURBANCE (ACRES)
Roads and Rails	(miles)	(feet)		(miles)	(feet)	
Well Pad Access Roads	2,620 ^{1,4}	24	7,622	221 ^{1,7}	32	857
Primary Collector Roads	535 ³	40	2,593	NA	NA	0
Rail Lines	96	40	465	0	0	0
Roads and Rails Subtotal	-	-	10,680	-	-	857
Construction/Production Facilities	(#)	(acres)		(#)	(acres)	
Gas Plant	5 ⁶	40	200	2	100	200
Centralized Processing Facilities	1 ⁶	10	10	0	0	0
Compression Facilities	18 ⁶	5	90	14	5	70
Equipment/Pipe Storage Yards	1	10	10	0	0	0
Workforce Facility	1	10	10	2	10	20
Fresh Water Make-up Ponds	6	8	48	7	8	56
Water Processing/Recycling Facility	-	-	-	1	15	15
Construction/Production Facilities Subtotal	-	-	368	-	-	361
Linear Facilities (miles)	(miles)	(feet)		(miles)	(feet)	
Oil and Gas – Gas Gathering Pipeline(s) Within Common Road Disturbance	184	30	0	75	30	0
Oil and Gas – Gas Gathering Pipeline(s) New Cross-Country Disturbance	NA	NA	NA	75	30	0
Linear Facilities Subtotal	-	-	0	-	-	0
Total Disturbance (acres)			18,303			2,457

Table 2-2. Summary of Existing and Planned Surface Disturbance

FACILITY	EXISTING AS OF 2013 ²			PLANNED BEFORE THE END OF 2017 ²		
	NUMBER OR MILES	SIZE OR WIDTH	EXISTING LONG-TERM SURFACE DISTURBANCE (ACRES)	NUMBER OR MILES	SIZE OR WIDTH	ESTIMATED LONG-TERM SURFACE DISTURBANCE (ACRES)

NA Not Applicable

¹Assumes road length of 1 mile/well pad for existing wells and wells planned before the end of 2017, consistent with assumptions for the Proposed Action.

²Assumes that interim reclamation has been completed by Converse County Project start date and only long-term disturbance remains.

³Existing primary access roads include Converse County roads and Wyoming State Highways (BLM 2013)

⁴[Please Note: “Horizontal Wells” currently includes 33 Directional wells identified in the WOGCC database and “Vertical Wells” includes 4 unknown drilling type wells. The OG assumes these directional wells represent multi-well pads (i.e., larger pad size); the OG is conducting an analysis for all well types to more accurately determine the number of wells per well pad; this information will be included in future versions of the existing surface disturbances. This information will be finalized with submission of the final project boundary.]

⁵Well pad acreages are based on assumptions from the Proposed Action to the extent possible; CBNG well pad acreages based on the BLM Buffalo Field Office EA for Anadarko Petroleum Corporation Table Mountain Phase 4 Coalbed Natural Gas Plan of Development (BLM 2010)

⁶Figures were sourced from the Wyoming State Pipeline Authority (2013). All other figures were provided by the Operator Group from internal company data.

⁷For wells planned before the end of 2017, roads include both collector roads, which provide primary access to large blocks of land in the project area, and well pad access roads, which are spur roads that provide access from collector roads to a specific well pad or group of well pads. Because the locations and mix of proposed collector versus well pad access roads planned before the end of 2017 are not known at this time, the OG has addressed both road types in single “Roads” facility type. To allow consideration of the surface disturbance from these roads, the OG has assumed that the average road width will be between the projected width of collector and access roads, or 48 feet at initial disturbance and 32 feet following interim reclamation.

2.4 Converse County Project Proposed Action

The OG would drill a maximum of 5,000 new oil and gas wells on approximately 1,500 well pads over a ten-year period between 2018 and 2027. The OG would drill the horizontal wellbores at an average rate of 500 wells per year for 10 years; to the greatest extent possible, drilling and development operations would occur on a year-round basis. Approximately two-thirds of the wells drilled would intersect federal mineral estate. The total number of wells (federal, fee, and state) that would be drilled during the life of the project or during any particular year would vary depending on factors (some of which would be outside the control of the OG) such as permit approvals, production success, engineering technology, economic factors, commodity prices, rig availability, and lease stipulations. Each well pad would contain between 1 to 16 well bores. Operators will determine the location of a proposed well by the location of the subsurface reservoir, the topography of the area, and WOGCC spacing rules.

The productive life of each well is estimated to be approximately 30 years. Based on experience near the project area, the OG assumes that less than one percent of the drilled wells might be dry and would be plugged and abandoned as soon as practicable.

To support the 5,000 oil and gas wells, the OG would develop roads, production facilities and production pads (375), disposal (25) and water source pads (50), and pipelines. A summary of surface disturbance from all project elements associated with implementation of the Proposed Action is presented in Table 2-3. The information in Table 2-3 shows new proposed development and surface disturbance that would occur as a result of the OG’s proposed project. Some of the wells could be located on existing pads, but such details are not available at this time and do not change the overall 5,000 wells on 1,500 well pads estimate for this project. Where new wells are located on existing pads, some of the pad locations would likely have been addressed through existing NEPA documents. To the extent practicable, the OG’s Proposed Action leverages existing and planned (but not constructed) facilities.

Table 2-3. Proposed Action Summary of New Surface Disturbance

FACILITY	NUMBER OR MILES	SIZE OR WIDTH	ESTIMATED SHORT-TERM SURFACE DISTURBANCE (ACRES)	SIZE OR WIDTH	ESTIMATED LONG-TERM SURFACE DISTURBANCE (ACRES)
Well Pads	(#)	(acres)		(acres)	
Oil and Gas Well Pads ¹	1,500	12	18,000	6	9,000
Disposal Well Pads	25	10	250	10	250
Production Pads	375	8	3,000	8	3,000
Water Source Well Pads	50	2	100	1	50
Well Pad Subtotal	1,950	-	21,350	-	12,300
Roads²	(miles)	(feet)		(feet)	
Well Pad Access Roads	1,500	45	8,182	24	4,364
Primary Collector Roads	390	75	3,545	50	2,364
Roads Subtotal	1,890	-	11,727	-	6,728
Construction/Production Facilities	(#)	(acres)		(acres)	
Gas Plant	2	100	200	100	200
Oil/Condensate Storage	6	3	18	3	18
Centralized Processing Facilities	2	5	10	0	0
Compression Facilities	50	5	250	5	250
Equipment/Pipe Storage Yard	1	50	50	50	50
Electrical Substation	12	3	36	3	36
Workforce Facility	1	10	10	10	10
Fresh Water Make-up Ponds	30	8	240	0	0
Water Processing/Recycling Facility	4	15	60	15	60
Construction/Production Facilities Subtotal	-	-	874	-	624

Table 2-3. Proposed Action Summary of New Surface Disturbance

FACILITY	NUMBER OR MILES	SIZE OR WIDTH	ESTIMATED SHORT-TERM SURFACE DISTURBANCE (ACRES)	SIZE OR WIDTH	ESTIMATED LONG-TERM SURFACE DISTURBANCE (ACRES)
Linear Facilities (miles)	(miles)	(feet)		(feet)	
Oil and Gas - Gas Gathering Pipeline(s) Within Common Road Disturbance	750	30	2,727	0	0
Oil and Gas - Gas Gathering Pipeline(s) New Cross-Country Disturbance	750	75	6,818	0	0
Oil and Gas - Main Trunk Pipeline(s)	500	75	4,545	0	0
Water – Temporary Surface Water Pipeline (above ground)	900	-	0	-	0
Overhead Electric Distribution - Adjacent to New Road Disturbance ³	1,350	30	4,909	9	1,472
Overhead Electric Distribution - Cross-country Disturbance	150	30	545	9	164
Linear Facilities Subtotal			19,544		1,636
Total Disturbance (acres)			53,495		21,288

¹Note: The OG could drill a limited number of exploratory vertical oil and gas wells; however, because the number of such wells are unknown at this time and the surface disturbance associated with each vertical well pad would be less than that of the proposed horizontal well pads, these vertical wells are assumed to be captured in the disturbance estimates for the 5,000 horizontal well count.

²Widths are for proposed surface disturbance and do not indicate long-term rights-of-way across BLM or National Forest System lands. ROWs are discussed in section 2.4.1.2.

³Assumes a 30-foot wide initial disturbance. Long term disturbance is assumed to be approximately 30 percent of the initial disturbance. Overhead electrical distribution lines would be installed along road ROW to the extent practicable; however, the OG assumes that in some cases, new, cross-country electrical distribution lines may be required.

2.4.1 Project Development

The following sections summarize pre-construction activities, project and well pad access roads development, well pad construction and well bore drilling operations, completion activities, well production and maintenance, and reclamation for each well pad location. In addition, these sections include information on water use and disposal and hazardous and waste management practices. Techniques and procedures may vary somewhat from those presented in this section depending on site-specific conditions, and these variances would be identified at the time of APD submittal.

2.4.1.1 Surveying, Notice of Staking, and Application for Permit to Drill

Prior to the start of construction, operators would complete the following activities:

- ▲ Make a good faith effort to notify the surface owner prior to entry for planning, staking or resource surveying purposes;
- ▲ Stake and survey each location, access road, and pipeline;
- ▲ Submit Notice(s) of Staking, APD(s), and right-of-way (ROW) application(s), as applicable, to the BLM;
- ▲ Participate in onsite evaluations with BLM personnel and surface owners in split-estate situations;
- ▲ Submit site-specific applications (e.g., Surface Use Plan of Operations) and modify them, as needed;
- ▲ Submit detailed construction plans, as needed;
- ▲ Perform cultural, paleontological, biological, and/or other surveys, as required by the BLM.

Each operator would obtain required permits from the BLM prior to initiating project activities on BLM-administered land. To initiate the permitting process, operators would file a Notice of Staking (NOS) and/or APD for each proposed well. The BLM would process the applications to determine if they meet all requirements and would subsequently notify the operator of dates, times, and places to meet and conduct onsite inspections of the proposed locations.

APDs would be submitted to the BLM where appropriate. Any submitted APDs would be technically and administratively complete, and would consist of a completed 3160-3 form, well plat, drilling plan, surface use plan of operations, bonding, operator certification, and onsite inspection (BLM Onshore Order #1 III D). A surface use plan of operations contains information describing construction operations, access roadway(s) and pipeline corridors, water supply and haul route, well site layout, production facilities, waste disposal, and restoration or reclamation associated with the site-specific well development proposal. The drilling plan would generally include information describing the technical drilling aspects of the specific proposal, including subsurface resource protection and royalty accountability. The BLM would determine the suitability of the proposed design, construction techniques, and procedures during the APD-review process.

2.4.1.2 Project Roads

The Proposed Action would use or upgrade the existing road network to the extent practicable. Existing roads would be upgraded as necessary to facilitate safe transport and to maximize use of the existing road system. Upgrades may include, but are not limited to, ditching, drainage improvements, graveling, crowning, and capping the roadbed. Based on experience in the project area, the OG assumes that upgrades to existing roads will not result in appreciable increases in road width.

The Proposed Action includes the construction of 1,890 miles of new roads, which equates to approximately one mile of new road per well pad (1,500 miles) plus 390 miles of additional primary collector roads. New roads to support the proposed action would provide primary access to large blocks of land in the project area, and well pad access roads, which are spur roads that would provide access from collector roads to a specific well pad or group of well pads. The surface disturbance associated with collector roads would be 75 feet wide during construction (reclaimed to a 50-foot wide running surface following interim reclamation),

and the surface disturbance associated with well pad access roads would be 45 feet wide (reclaimed to a 24-foot wide running surface following interim reclamation). Estimated initial and post-interim reclamation surface disturbances from roads would be 11,727 and 6,728 acres respectively. New roads would be constructed and maintained to provide year-round access. The OG would apply for temporary and permanent ROWs for proposed roads across BLM-managed and National Forest System lands. Any roads developed on private surface would be sited, constructed, and maintained in accordance with the landowner's executed surface agreements.

All new roads would be designed, constructed, and maintained in accordance with standards described in Chapter 4 (*Construction and Maintenance*) of *Surface Operating Standards and Guidelines for Oil and Gas Exploration and Development, 4th Edition* (commonly referred to as the Gold Book) (BLM 2007) and BLM Manual 9113 (BLM 2011). Precise design characteristics for new roads would follow standard operating procedures as described below and would vary based on site-specific topography and soil characteristics supplied with individual well plats in APDs. Whenever practicable, roads would be designed to disturb less than the identified initial disturbance width, potentially through the incorporation of additional turnouts or other methods, so long as traffic and safety concerns are satisfied. However, in limited circumstances, larger disturbance widths may be necessary to meet engineering and safety standards. New roads would be constructed with 6" base of 3" minus gravel with a 3:1 slope for ditches on both sides. Water turnouts would be installed within the ROW where necessary to provide proper drainage along the road. Construction activity would not be conducted using frozen or saturated soils material or during periods when watershed damage was likely to occur.

Roads would be built to be permanent, and would remain in place for at least the productive life of the wells. Roads would be maintained and kept in good repair while in service, including maintaining proper crown, ditching, and drainage to prevent unnecessary erosion. The OG would be responsible for road maintenance to the extent set forth in applicable road use agreements with private surface owners and Converse County.

Interim and final reclamation activities for all road disturbances would be consistent with the guidance contained in Chapter 6 (*Reclamation and Abandonment*) of the Gold Book (BLM 2007) and BLM Wyoming Instruction Memorandum 2012-032 (BLM 2012a). Following road construction, stockpiled topsoil would be evenly redistributed over the road embankment and borrow ditch slopes. These areas would be stabilized and reclaimed with the approved seed mix as soon as practicable in the next appropriate seeding season. Temporary roads required for the construction of facilities and other roads, which are not needed for project operations would be reclaimed fully as soon as practicable. Temporary roads would primarily serve pipeline, electrical distribution line, or other facility construction; surface disturbance associated with these temporary features is captured in Table 2-3.

2.4.1.3 Drilling and Completion

WELL PAD CONSTRUCTION

The OG would construct up to 1,500 well pads, each with an initial footprint of up to 12 acres (including areas of cut/fill and the pad itself) during drilling and completion. Under the Proposed Action, each well pad would be designed to accommodate the drilling of multiple wells. Drilling and completion well pads would be

constructed as shown in the typical well pad layout provided in Figure 2-1. If productive, the portions of the well pad not required for routine operations would be reclaimed thereby reducing the pad to an average size of 6 acres for the life of the multiple wells on the pad. The OG could also construct approximately 375 production pads of approximately 8 acres in size see Figure 2-3; these production well pads would not be subject to initial reclamation and would remain at approximately 8 acres over the long term. Some of the projects water supply needs would be met from up to 50 new water supply wells. Well pads for water supply wells would be 2 acres in size, but would be reduced to 1 acre following interim reclamation. Additionally, 20 to 25 disposal well pads, each be 10 acres in size, would be constructed to handle some of the project's produced water disposal needs. A water disposal pad would typically consist of one disposal well, water storage tanks, a pump station, and a dehydration unit. Estimated initial and post-interim reclamation surface disturbances from all oil and gas well pads and associated disposal, water supply, and production pads would be 21,350 and 12,300 respectively. While the Proposed Action is for up to 12-acre well pads, actual individual pad sizes requested during subsequent APDs and analyzed in site-specific NEPA would vary based on the number of wells proposed for the pad, constraints related to lease/landowner agreements, operational safety regulations (e.g., required setback distances and placement considerations for equipment and facilities), and location-specific topography. The OG would attempt to limit surface disturbances from well pads, particularly in circumstances including, but not limited to, areas of extensive cuts and/or fills, proximity to ephemeral drainages. Final determination on the size of individual well pads would be made during the APD process.

Figure 2-2. Example Drilling and Completion Horizontal Well Pad Layout (during production)





Figure 2-3. Example Production Pad Layout



PLEASE NOTE: LOCATION OF FACILITIES ARE FOR
 VISUALIZATION PURPOSES ONLY. ACTUAL LOCATIONS
 TO BE DETERMINED DURING CONSTRUCTION.

- BBL barrel
- W/T water tank
- O/T oil tank
- STL steel

*Note: production pads would contain support facilities only, and would not include oil and gas wells.

Well pad construction activities would be conducted in accordance with the guidelines and standards as set forth in the joint BLM/U.S. Forest Service (USFS) publication: Surface Operating Standards for Oil and Gas Exploration and Development Fourth Edition (BLM 2007). Well pads would be constructed to create a level surface for drilling and/or production equipment utilizing the native materials present at the site. Mineral materials from outside the project area would not be required. Locations would be leveled by balancing cut and fill areas. Site-specific reclamation and construction plans will be developed for individual locations based on on-the-ground conditions. Topsoil would be removed and separately stockpiled to ensure that this resource is protected until it can be reapplied during site reclamation. Based on experience in this area, the OG anticipates that an average six inches of topsoil would be available. If topsoil is stored for longer than 6 months, it would be stabilized and re-vegetated until needed. Topsoil would be stored in an area where it could be retrieved without causing additional disturbance and where it would not impede watershed and drainage flows.

DRILLING

Following road and well pad construction, drilling rigs would be transported to the well site and erected on the well pad. Each rig is expected to drill an average of 12 wells each year. Up to fifty drill rigs are anticipated to be operating in the project area at the peak of the drilling phase. Horizontal wells would be drilled vertically from each surface location to a predetermined point above the target formation, referred to as the “kickoff point.” From here, the wellbore would curve from its vertical trajectory to intersect the target reservoir at the “entry point,” then continue horizontally through the reservoir until reaching the desired bottom hole location.

The quantity and composition of drilling fluids would be determined on a well-by-well basis. Drilling fluids typically consist of fresh water- and oil-based mud. Drilling mud would be specifically engineered and managed throughout the drilling operation to control the flow of fluids (water, oil, and gas) from the well bore. The use of oil- versus water- based mud would be formation-dependent. Oil-based muds would not be used in formations that contain water with total dissolved solids of 10,000 or less. In the project area, this generally means that oil-based mud would only be used below the Fox Hills formation. Cuttings from oil-based muds would not be placed in an onsite cuttings pit unless they are properly treated (fly ash or Soil-bond) and the solidification process is permitted through the WOGCC.

Prior to setting casing, open-hole well logs may be run to evaluate a well’s production potential. If the evaluation concludes that sufficient oil and/or gas is present and recoverable, then steel production casing would be run and cemented in place in accordance with the well design, as specified in the approved APD and conditions of approval. The casing and cementing program would be designed to isolate and protect shallower formations encountered during drilling, prohibiting pressure communication or fluid migration between zones. Setting the surface casing to protect the base of fresh water would be accomplished using the drilling rig itself. The cement would protect the well by preventing formation pressure from damaging the casing and retarding corrosion by minimizing contact between the casing and formation fluids. Certain cased-hole evaluation logs also may be run subsequent to setting and cementing production casing. At the kick off point, the well is directionally drilled with specialized tools to steer the well in a curve to the target formation. Frequently, once the wellbore is drilled into the target formation, the intermediate casing is run and cemented. Occasionally, the well is drilled through the formation to its total planned depth before

casing is run and cemented. In this case, the casing string run would also be the production casing. After the intermediate casing is run and cemented, the lateral, or horizontal leg, of the wellbore is drilled in the formation until the total measured depth is reached. The production casing is run to the total measured depth and may or may not be cemented in the formation. The production casing may also have annular packers on it to compartmentalize the lateral section for completion. Another technique commonly used in conjunction with the production casing are frac sleeves in combination with the annular packers or cement.

COMPLETION

After the well is drilled, cased, and cemented, the drilling rig would be moved off location. The location would be redressed to accommodate the completion activities and facilities, which include cleaning out the well bore, pressure testing the casing, perforating and hydraulic fracturing in the horizontal portion of the well bore, and running production tubing to facilitate commercial production. A completion rig would then be moved onto the well pad.

Hydraulic fracturing would be performed at selected intervals in the target formation to increase the surface area available for mineral drainage and improve fluid movement from the rock into the well bore. These hydraulic fracturing operations would typically consist of pumping a thick fluid mixture (proppant), consisting of approximately 98 percent sand and water, into the down hole under pressure. Chemical additives would be added to the hydraulic fracturing fluids to improve performance. The fracturing fluid would be determined based on compatibility with the formation minerals and fluid composition, and recoverability.

Hydraulic fracturing processes and required disclosures would be conducted in accordance with all WOGCC and other applicable rules. The WOGCC requires operators to disclose the types and amounts of hydraulic fracturing chemicals used prior to stimulation (WOGCC 2010). The OG would also disclose the contents of hydraulic fluid used in the proposed wells to the public through FracFocus, a website managed jointly by the Ground Water Protection Council and the Interstate Oil and Gas Compact Commission (<http://fracfocus.org>). The website allows the public access to general information, water volumes, and chemical information for registered wells in a format consistent with material safety data sheets, including the Chemical Abstract Service number and the ingredient percentage in both the additive and hydraulic fracturing fluids. This registry provides a means for oil and gas operators to voluntarily provide key information to the public in a timely fashion.

The proppant mixture would enter the target formation through perforations in the production casing or openings in a temporarily installed casing string designed to facilitate the fracturing process. Pumping pressures would be monitored throughout the entire program and increased to the point at which fractures initiate in the target formation at the perforations into the formation. The proppant props the created fractures open after the pressure drops, which would facilitate the flow of reservoir fluids into the well bore and to the surface.

The OG would use both fresh water pits and tanks to store water for hydraulic fracturing. Fresh water pits would be permitted through the WOGCC and/or the State Engineer's Office (SEO). Pits on location or fresh water make-up ponds would only be used for fresh water; no water would be flowed back into the fresh water pits. In locations where shallow groundwater is identified, Poseidon tanks may be used. Upon

completion of the hydraulic fracturing operation, temporary production equipment would be used to recover as much of the hydraulic fracturing fluids as practicable and to clean excess sand out of the lateral prior to bringing production equipment on location.

Most operators would have a cuttings pit onsite. Solidification and subsequent reclamation of the cuttings pits would be accomplished as soon as practicable following well completion (BLM IM No. WY-2012-007 and WOGCC 2014). Those operators who do not use cuttings pits would haul their waste to a permitted land farm or disposal facility. Cuttings from oil-based muds would not be placed in the cuttings pit unless properly treated (fly ash or Soil-bond) and permitted through the WOGCC. Flaring would be used during well production testing to determine the pressure, flow, and composition of the gas or oil from the well. Testing duration would depend on well performance but would typically only be conducted long enough for fluid rates to drop to a level production equipment could safely process. Flaring would also be used in emergency situations where equipment or piping is in danger of being over-pressured. In such instances, valves on the equipment would automatically release gas to flare stacks. All flaring would occur at a distance from the wellhead that protects equipment, structures, and personnel safety.

2.4.1.4 Water Supply and Use

Drilling water would be obtained from approved, permitted surface water and groundwater sources in the vicinity. The specific water sources will be identified at the time of APD submittal.

The Proposed Action would result in the use of 50,000-100,000 barrels of water per well during well drilling and completions. This water use would include approximately 2,000 to 6,000 barrels of fresh water per typical well for drilling mud. In addition, water for dust abatement and domestic use would be approximately 15,000 barrels per year (approximately 1,000 barrels per well per year). Fresh water used for drilling and completion, and dust abatement purposes would be obtained from commercial water supply sources in the immediate project area. The specific source of this fresh water used in drilling operations for each well would be identified at the time of APD submittal.

The Proposed Action would include the use of temporary surface lines and trucked water, and would not include the use of buried water pipelines. Fresh water used for drilling and completion purposes would be transported from water supply locations to well pads by trucks. Some water would be delivered to fresh water make-up ponds and then transported to well pads via a surface line; fresh water make-up ponds would have a capacity of 20 acre-feet each, and would be off-channel and lined. These fresh water make-up ponds or the pads on which they are located would be fenced.

Finally, some operators would construct central water recycling facilities that would include lined pits for storing fresh water suitable for drilling and completions as well as lined pits for flowback water that would be treated, as needed, and recycled for use in drilling and completions. In some cases these central water recycling facilities would be co-located with water source wells. These facilities would serve wells by trucking or via temporary surface line delivery of water to well pads.

2.4.1.5 Production

Production facilities at each pad location typically include a well head and rod pump jack, heater-treater, recirculating pump, and a tank battery typically comprised of four to eight storage tanks. Sometimes, a gas lift system or electric submersible pump may be used instead of a rod pump jack. Any of these artificial lift methods used on non-flowing wells require power. The OG anticipates the use of 115 horsepower (hp) Ajax® gas engines, using the best available control technology (BACT) for stack emissions and noise control. These gas pump engines would be permitted and approved by Wyoming Department of Environmental Quality (WDEQ)/ Air Quality Department (AQD) under standard air permitting practices and the pumping unit engine emissions policy. Production facilities would typically be installed on the disturbed portion of each well pad. The OG would maintain and operate facilities to adhere to relevant executive orders and requirements for noise to protect greater sage-grouse and other resources.

Power used during well production would typically be supplied via electric power lines or gas-powered generators. The Proposed Action would consist of approximately 1,500 miles of above ground electric distribution lines required to bring power to the proposed wells and facilities. Above ground distribution lines would be installed adjacent to new and existing roads where feasible, and would require an initial disturbance width of 30 feet (5,454 acres of surface disturbance) and a post-interim disturbance width of 9 feet (1,636 acres of surface disturbance) to allow for access to the lines, which would ultimately have 3-foot diameter disturbance per pole at 15 poles per mile. Based on the experience of the OG in the area, it is anticipated that a trunk line would have 60' tall poles using vertical construction and cross-arm construction for the laterals. Overhead powerlines typically follow lease roads and/or pipeline ROW. When a line is placed cross-country, the third-party power provider would select a route that is accessible by truck. Additionally, the OG anticipates that power providers would follow guidance in the BLM Gold Book, which also refers to Suggested Practices for Raptor Protection on Power Lines (APLIC 2006) during design and installation of these lines.

All permanent above-ground production facilities installed on the producing federal well sites would be painted one of the standard environmental colors recommended by the Rocky Mountain Five-State Interagency Committee to be selected at the BLM's discretion and agreed upon with the surface landowner.

OIL AND GAS PIPELINES AND MIDSTREAM FACILITIES

Based on expected production rates, the OG anticipates that approximately 50 gas compression and processing facilities of approximately 16,000 horsepower, which are capable of handling approximately 100 wells each, would be constructed to facilitate the flow of gas from the proposed well through the pipelines. Compression and processing facilities would also have equipment to strip and recover liquids from the gas; this dehydration equipment would be co-located with the compression equipment and would generally not increase the facility footprint.

Produced gas from the proposed wells would be collected and transported through a new system of gas gathering pipelines designed to collect the natural gas produced from each individual well for transport to a main trunk line. The trunk line would transport the gas to tie-in points with a third-party tie-in/gas processing plant.

The OG assumes that oil and gas gathering pipelines would be installed adjacent to or in a common ROW with new or upgraded roads where feasible approximately half the time, and in new cross-country ROWs for the remainder. Pipelines in road ROWs would require 30 feet of additional initial disturbance. Where paralleling an access road is not feasible and a new cross-country pipeline is necessary, a new 75-foot ROW would be required. The Proposed Action would require approximately 750 miles of gas pipelines installed adjacent to existing roads, resulting in 2,727 acres of temporary disturbance. The installation of 750 miles of cross-country gas pipelines and 500 miles of main trunk pipelines would add another 6,818 acres and 4,545 acres of temporary disturbance, respectively. All surface disturbances resulting from pipeline installation would be subsequently reclaimed, resulting in no post-interim reclamation disturbance.

GAS PLANTS/CENTRALIZED PROCESSING FACILITIES

Gas from the field would go to an existing or new proposed processing facility for distribution. Centralized processing facilities could also house other facilities, including dehydration units, required to process oil and gas products for transport. Oil would be transported by truck or rail to an existing refinery for further processing and distribution. No new rail loadouts are included in the OG's proposed project.

2.4.1.6 Wastewater Management

Based on experience producing other wells in the project area, the OG anticipates produced water production after flowback would average 10-50 barrels per well per day, with a total amount of produced water ranging from 55,000,000-91,000,000 barrels per year at full field development.

Flowback and produced water would be separated from the oil and gas and stored in tanks on or adjacent to the well pads. Both oil tanks and water tanks would typically have a 400 or 500-barrel capacities and would be placed inside of containment constructed completely around the production facilities. The containment would consist of impervious compacted subsoil or lined structures and would hold a minimum of 110 percent of the capacity of the largest tank. Some of the collected flowback and produced water would be transported to disposal facilities authorized for Resource Conservation and Recovery Act (RCRA) exempt waste within the project area. The OG would also consider disposal at 3rd-party evaporation ponds in or near the Project Area, but does not propose the development of such facilities to support the disposal of wastewater for this project. Measurement of all produced fluids would be made per Onshore Order Nos. 4 and 5 and State of Wyoming rules, and would be reported to the State of Wyoming and the Federal government in compliance with reporting requirements.

If and when it proves technologically and economically feasible, the OG would consider recycling and re-use of flowback and produced water in the project area. Potential recycling options could include the use of produced water from existing oil and gas wells or the new wells included in the Proposed Action as a completion water source for use during hydraulic fracturing. Such use could reduce the need to transport water to disposal well or evaporation ponds. If conditions allow, the operators may also recycle water remaining in the freshwater mud system for use during drilling of additional wells on a pad.

2.4.1.7 Reclamation

INTERIM RECLAMATION

Sufficient topsoil to facilitate revegetation would be segregated from the subsoil during construction and stockpiled for future reclamation of the disturbed areas. Topsoil stockpiles would be graded to a “rounded” appearance with slopes of 4:1 or flatter and would be maintained in a weed-free condition through treatment and use of sterile and/or desired native cover crops for soil that is stockpiled for more than 6 months. The salvaged topsoil would be evenly distributed over those disturbed surfaces subject to reclamation upon termination of drilling and completion operations. All disturbed surfaces would be reclaimed as soon and as near as practicable to their original condition.

Portions of well pads not needed for production would be reclaimed primarily through backfilling the cuttings pits, leveling, and recontouring of “nonworking” disturbed areas, redistribution of stockpiled topsoil over these disturbed areas, installation of erosion control measures, and reseeding as recommended by the BLM and/or private surface owner.

Erosion control measures would be implemented as soon as practical to do so and could include surface roughening, wattles, silt fence, crest & toe of slopes, berms, & check dams. Rat and mouse holes would be filled and compacted from bottom to top immediately upon release of the drilling rig from the location or in accordance with guidelines established by the BLM.

Seeding would occur in the next appropriate seeding season following the completion of surface disturbing activities, generally within 180 days of the last well being completed on the pad. In the fall, seeding would take place after September 15th and prior to ground frost, and in the spring after the frost has left the ground and prior to June 1st. Seed mixes will be prescribed either by the surface owner or the BLM.

Following road construction, stockpiled topsoil would be evenly redistributed over the road embankment and borrow ditch slopes. These areas would be stabilized and reclaimed with the approved seed mix as soon as practicable in the next appropriate seeding season, as discussed above. Pipeline ROW disturbance areas would be completely reseeded as soon as practicable in the next appropriate seeding season in accordance with the seeding recommendations obtained from either the private surface owner or the BLM, as appropriate. Prior to re-seeding, the OG will assess soil compaction using on onsite visual inspections. Compacted areas would be scarified by ripping or chiseling to loosen compacted soils where underlying material would not significantly degrade topsoil, with a goal of improving seed establishment. Any required monitoring for reclamation success would be conducted by a qualified operator representative (in coordination with the BLM).

FINAL RECLAMATION

At the time of final abandonment, all surface equipment, including surface gathering pipelines, would be removed from the site. Site and access road locations would be cleared of all production equipment, gravel, surfacing materials, and any other material/equipment that had been imported (including culverts, cattle guards, and fence materials). Drainage basins would be contoured to maintain the profile and dimensions approximate to the natural or otherwise pre-existing conditions of the location. Appropriate erosion control measures would be taken to prevent run-off into drainages in proximity to disturbed areas, and no

depressions would be left to trap water. With the exception of roads or other facilities retained for future use, all remaining disturbances would be reclaimed according the same procedures for interim reclamation. Any follow-up surveys and weed treatments would be conducted by a qualified operator representative.

At final abandonment of wells, the casing would be cut off at the base of the cellar or three feet below the final restored ground level, whichever is deeper. The casing would be capped with a metal plate at least 0.25-inches thick welded in place, and the well location and identity would be permanently inscribed on the cap. The cap would be constructed with a weep hole.

Additional information on interim and final reclamation is available in the project reclamation plan, which will be submitted separately.

2.4.1.8 Source of Construction Materials

Surfacing and base course materials would be obtained from existing, operational gravel pits located on commercial sources in the project area. Details of gravel suppliers would be identified at the time of APD submittal. It is anticipated that these materials would come from within and from sources located within 100 miles of the project area.

2.4.1.9 Hazardous Materials and Waste Management

A variety of chemicals, including lubricants, paints, and additives are used to drill, complete, and operate a well. Some of these substances may contain constituents that are hazardous. Commonly used hazardous materials include greases or lubricants, gasoline, diesel, methanol, solvents, acids, paint, and herbicides. Hazardous materials would not be stored at well locations, although they may be kept in limited quantities on drilling sites and at production facilities for short periods of time. The OG uses limited quantities of methanol on most, if not all, sites in Wyoming as antifreeze. Methanol would be properly stored with appropriate secondary containment. The typical tank size is about 330 gallons, and thus the quantities stored typically do not trigger Tier II reporting. If the OG must store larger quantities methanol that would trigger Tier II reporting, all applicable rules and regulations would be observed. Anticipated storage volumes for natural gas liquids (NGLs) and are unknown at this time.

Activities associated with the transportation of these materials, including packing, container handling, labeling, vehicle placarding, and other safety aspects, are regulated by the US Department Of Transportation under 49 Code of Federal Regulations (CFR), Parts 171–180. None of the chemicals that would be used during drilling, completion, or production operations meet the criteria to be considered acutely hazardous materials/substances or meet the quantities criteria per the BLM Washington Office Instructional Memoranda 93-344. The OG would comply with the Superfund Amendments and Reauthorization Act (SARA) Title III reporting requirements for materials used in quantities greater than 10,000 pounds during drilling and completion operations. For example, cement used to isolate the steel casing from the surrounding wellbore is a reportable SARA Title III material. In addition, extremely hazardous substances, as defined in 40 CFR Part 355, would not be used, produced, stored, transported, or disposed of while drilling or completing a well. Most wastes that would be generated at project facilities are excluded from regulation as hazardous wastes under RCRA under the exploration and production exemption in Subtitle C (40 CFR

261.4[b][5]) and Subpart D. These project wastes are generally considered to be solid wastes. These are commonly referred to as E&P (exploration and production) wastes, or E&P-exempt wastes. The management of E & P wastes is regulated by WOGCC. Exempt wastes include produced water, production fluids such as drilling mud or well stimulation flowback, and contaminated soils. The OG would comply with all regulatory requirements associated with the storage, transportation, and disposal of hazardous waste.

The concentration of nonexempt hazardous substances in the reserve pit at the time of backfilling would not exceed the standards set forth in CERCLA as amended by the SARA. All oil and gas drilling-related CERCLA hazardous substances removed from a location and not reused at another drilling location would be disposed of in accordance with applicable federal and state regulations. Only those hazardous wastes that qualify as exempt under RCRA may be disposed of in the reserve pit.

Any release of oil, gas, salt water, or other such fluids would be immediately cleaned up and transported to an approved disposal site. Spills would be reported to the AO and other appropriate authorities. The OG would develop and maintain site-specific Spill Prevention Control and Countermeasures Plans for each facility in the project area subject to US Environmental Protection Agency's (EPA's) oil spill prevention program under 40 CFR Part 112. To satisfy Spill Prevention Control and Countermeasures Plan requirements, if storage facilities or tanks are constructed, they would be constructed in accordance with applicable regulations. A facility would be subject to 40 CFR Part 112 if it had an aggregate aboveground oil storage capacity greater than 1,320 U.S. gallons or a completely buried storage capacity greater than 42,000 U.S. gallons, and if there were a reasonable expectation of an oil discharge into or upon navigable waters of the U.S. or adjoining shorelines. Oil of any type and in any form would be covered, including but not limited to petroleum, fuel oil, sludge, oil refuse, and other oils of plant and animal origin. A facility that meets the criteria would comply with the Spill Prevention Control and Countermeasures Plan rule by preventing oil spills and developing and implementing a Spill Prevention Control and Countermeasures (SPCC) Plan. For spill prevention, actions that a facility owner/operator can take to prevent oil spills include the following:

- ▲ Using containers suitable for the oil stored.
- ▲ Providing overfill prevention for oil storage containers.
- ▲ Providing sized secondary containment for bulk storage containers. The containment needs to hold the full capacity of the container plus possible rainfall.
- ▲ Providing general secondary containment to catch the most likely oil spill when transferring oil to and from containers and for mobile refuelers and tanker trucks.
- ▲ Periodically inspecting and testing pipes and containers. Inspections must be documented.

The owner or operator of the facility must develop and implement an SPCC Plan that describes oil handling operations; spill prevention practices; discharge or drainage controls; and the personnel, equipment, and resources at the facility that are used to prevent oil spills from reaching navigable waters or adjoining shorelines. Although each SPCC Plan is unique to the facility, there are certain elements that must be described in every plan, including:

- ▲ Define the operating procedures at the facility to prevent oil spills.
- ▲ Identify and describe control measures (such as secondary containment) installed to prevent oil spills from entering navigable waters or adjoining shorelines.
- ▲ List countermeasures to contain, cleanup, and mitigate the effects of an oil spill that has impacted navigable waters or adjoining shorelines.

Operators would maintain a file, per 29 CFR 1910.1200 (g) containing current Material Safety Data Sheets (MSDS) for all chemicals, compounds, and/or substances used during the project. Hazardous materials found on-site may include diesel, gasoline, and engine oil as well as frac fluids, drilling mud, and cementing products which are primarily inhalation hazards, fuels (flammable and/or combustible), materials that may be necessary for well completion/stimulation activities such as flammable or combustible substances and acids/gels (corrosives). Trash containers and portable toilets would be located on construction sites. Garbage, trash, and other waste materials would be collected in portable, self-contained, fully enclosed trash cages during construction, drilling, and completion operations and disposed of at an approved landfill. Trash would not be burned on location. Motor oil would be placed in closed containers and disposed of at an approved disposal facility. In the event small quantities of hazardous wastes are generated at any sites (e.g., from equipment maintenance), they would be properly stored and disposed of at an off-site approved disposal facility.

Construction locations and well sites would be cleaned of other debris and waste materials and removed from the location after drilling and completion operations.

2.4.2 Project Workforce and Transportation

This section provides estimates for the anticipated workforce and vehicle trips associated with the Proposed Action. The information presented in this section is based on available current information that is subject to revision based on changing conditions.

2.4.2.1 Project Workforce

Table 2-4 shows an estimate of timing/phasing of development activities, duration of activities, and approximate numbers of employees anticipated for a typical well in the project area.

Table 2-4. Employment Estimates

ACTIVITY	WORKERS PER CREW	TYPICAL ACTIVITY DURATION
Pre-approval / permitting	6	3 days
Location construction	5	6 / 14 days (single well / multi-well)
Rig mobilization / de-mobilization	11	3 / 5 days (single well/ multi-well)
Drilling	18	10 / 42 days (single well / multi-well)
Completion	11	5 / 8 days (single well/ multi-well)
Well service	22	3 days (single well / multi-well)
Tank battery setup	6	4 days (single well/ multi-well)
Gas-gathering system	15	1 days (single well / multi-well)
Electrical system	8	1 / 2 days (single well/ multi-well)

Source: BLM 2012b

2.4.2.2 Workforce Facilities

One new 10 acre workforce facility containing offices would be constructed to support the proposed development. Based on local housing availability and other factors, the OG may also consider including a man camp to house rig crews at the workforce facility site. No initial reclamation would be possible while the facility is in use, so surface disturbances would be long-term.

2.4.2.3 Project Transportation

The number of vehicle trips per day for project wells would vary by phase. The estimated vehicle average trips by well development phase are presented in Table 2-5 below.

Table 2-5. Daily Average Project Vehicle Traffic Trips per Well

WELL DEVELOPMENT PHASE	AVERAGE TRIPS DAY/WELL ¹	TOTAL TRIPS/WELL
Surveying, Notice of Staking, and Application for Permit to Drill	4	6
Construction	65	372
Drilling	24 ¹	714 ¹
Completion	74	702
Production and Operation Activities ²	4	Dependent on life of well

Source: BLM 2012c

¹Mobilization and demobilization efforts are accounted for in the estimates provided.

²The number of vehicle truck trips during production would vary based on the amount of oil produced. Truck trips during production could also be reduced for multi-well pads.

2.5 References

IN-TEXT CITATION	FULL REFERENCE
BLM 2007	BLM. 2007. United States Department of the Interior and United States Department of Agriculture. Surface Operating Standards for Oil and Gas Exploration and Development (Fourth Edition). Available online at http://www.blm.gov/pgdata/etc/medialib/blm/wo/MINERALS__REALTY__AND_RESOURCE_PROTECTION_/energy/oil_and_gas.Par.18714.File.dat/OILgas.pdf
BLM 2010	BLM. 2010. Buffalo Field Office Environmental Assessment for Anadarko Petroleum Corporation Table Mountain Phase 4 Coalbed Natural Gas Plan of Development WY 070-EA10-258. U.S. Department of the Interior, Bureau of Land Management. Washington, D.C.
BLM 2011	BLM. 2011. Manual 9113 – Roads Manual. Transmittal Sheet. U.S. Department of the Interior, Bureau of Land Management. Washington, D.C.
BLM 2011a	BLM Instruction Memorandum No. WY-2012-007. U.S. Department of the Interior, Bureau of Land Management. Washington, D.C. http://www.blm.gov/pgdata/etc/medialib/blm/wy/resources/efoia/IMS/2012.Par.59729.File.dat/wy2012-007.pdf
BLM 2012a	BLM. 2012. Instruction Memorandum No. WY-2012-032. U.S. Department of the Interior, Bureau of Land Management. Wyoming Bureau of Land Management Reclamation Policy. Washington, D.C.
BLM 2012b	BLM. 2012. Rawlins Field Draft Environmental Impact Statement Continental Divide-Creston Natural Gas Development Project. BLM/WY/PL-13/002+1310. U.S. Department of the Interior, Bureau of Land Management. Washington, D.C.
BLM 2012c	BLM. 2012. Buffalo Field Office Crazy Cat East Oil and Gas Proposal Environmental Assessment for Anadarko Petroleum Corporation. WY- 070-EA13-028. U.S. Department of the Interior, Bureau of Land Management. Washington, D.C.
BLM 2013a	Bureau of Land Management (BLM). 2013 Data on roads wells provided by the Casper Field Office, Casper, Wyoming.
Platts 2014	Platts McGraw Hill Financial, Infrastructure GIS data for Wyoming, January 2014
Rocky Mountain Power 2013	Rocky Mountain Power, Infrastructure GIS data for Wyoming, October 2013
Ventyx 2013	Ventyx <i>Velocity Suite</i> . Version 1. [software]. 2013. Retrieved from: http://www.ventyx.com/en/enterprise/business-operations/business-products/velocity-suite
WOGCC 2010	Wyoming Oil and Gas Conservation Commission (WOGCC). 2010. Rules and Regulations of the Wyoming Oil and Gas Conservation Commission. Casper, Wyoming.
WOGCC 2013	WOGCC. 2013. Wyoming Oil and Gas Conservation Commission Database. Last revised: June 30, 2013. Available: http://wogcc.state.wy.us/ . Accessed: July 22, 2013
WSPA 2013	Wyoming State Pipeline Authority. 2013. Wyoming Pipeline Infrastructure. Last revised: 2013. Available: http://publicserver.wyopipeline.com/flexviewers/WyomingPipelinesInfrastructure/index.html . Accessed: August 14, 2013.